

**Common Name:** KRYLON INDUSTRIAL QUIK-MARK SOLVENT-BASED INVERTED MARKING PAINT (APWA) GREEN

**Manufacturer:** SHERWIN-WILLIAMS

**SDS Revision Date:** 4/7/2015

**SDS Format:** GHS-US

**Grainger Item Number(s):** 38EK96

**Manufacturer Model Number(s):**

## SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION 1. IDENTIFICATION](#)

[SECTION 2. HAZARDS IDENTIFICATION](#)

[SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS](#)

[SECTION 4. FIRST AID MEASURES](#)

[SECTION 5. FIRE-FIGHTING MEASURES](#)

[SECTION 6. ACCIDENTAL RELEASE MEASURES](#)

[SECTION 7. HANDLING AND STORAGE](#)

[SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)

[SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES](#)

[SECTION 10. STABILITY AND REACTIVITY](#)

[SECTION 11. TOXICOLOGICAL INFORMATION](#)

[SECTION 12. ECOLOGICAL INFORMATION](#)

[SECTION 13. DISPOSAL CONSIDERATIONS](#)

[SECTION 14. TRANSPORT INFORMATION](#)

[SECTION 15. REGULATORY INFORMATION](#)

[SECTION 16. OTHER INFORMATION](#)

SAFETY DATA SHEET

03631

## SECTION 1. IDENTIFICATION



PRODUCT NAME:

KRYLON(R\*) INDUSTRIAL QUIK-MARK(TM) SOLVENT-BASED INVERTED MARKING PAINT  
(APWA) GREEN

PRODUCT CODE: 03631

OTHER MEANS OF IDENTIFICATION: NOT AVAILABLE.

PRODUCT TYPE: AEROSOL.

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED  
AGAINST: NOT APPLICABLE.

MANUFACTURER:

THE SHERWIN-WILLIAMS COMPANY  
KRYLON PRODUCTS GROUP

CLEVELAND, OH 44115

EMERGENCY TELEPHONE NUMBER OF THE COMPANY: (216) 566-2917

PRODUCT INFORMATION TELEPHONE NUMBER: (800) 247-3266

REGULATORY INFORMATION TELEPHONE NUMBER: (216) 566-2902

TRANSPORTATION EMERGENCY TELEPHONE NUMBER: (800) 424-9300

## SECTION 2. HAZARDS IDENTIFICATION



OSHA/HCS STATUS:

THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

FLAMMABLE AEROSOLS: CATEGORY 1

GASES UNDER PRESSURE: COMPRESSED GAS

SKIN CORROSION/IRRITATION: CATEGORY 2

SERIOUS EYE DAMAGE/EYE IRRITATION: CATEGORY 2A

CARCINOGENICITY: CATEGORY 2

TOXIC TO REPRODUCTION (UNBORN CHILD): CATEGORY 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (RESPIRATORY TRACT IRRITATION AND NARCOTIC EFFECTS): CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): CATEGORY 2

ASPIRATION HAZARD: CATEGORY 1

PERCENTAGE OF THE MIXTURE CONSISTING OF INGREDIENT(S) OF UNKNOWN TOXICITY: 19.7%

GHS LABEL ELEMENTS:

HAZARD PICTOGRAMS:

FLAME

GAS CYLINDER

HEALTH HAZARD

EXCLAMATION MARK

SIGNAL WORD: DANGER

HAZARD STATEMENTS:

EXTREMELY FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CAUSES SERIOUS EYE IRRITATION.

CAUSES SKIN IRRITATION.

MAY DAMAGE THE UNBORN CHILD.

SUSPECTED OF CAUSING CANCER.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

MAY CAUSE RESPIRATORY IRRITATION.

MAY CAUSE DROWSINESS AND DIZZINESS.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENTS:

GENERAL:

READ LABEL BEFORE USE. KEEP OUT OF REACH OF CHILDREN. IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND.

PREVENTION:

OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED. WEAR PROTECTIVE GLOVES. WEAR EYE OR FACE PROTECTION. KEEP AWAY FROM HEAT, HOT SURFACES, SPARKS, OPEN FLAMES AND OTHER IGNITION SOURCES. NO SMOKING.

PRESSURIZED CONTAINER:

DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE. USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. DO NOT BREATHE DUST OR MIST. WASH HANDS THOROUGHLY AFTER HANDLING.

RESPONSE: GET MEDICAL ATTENTION IF YOU FEEL UNWELL.

IF EXPOSED OR CONCERNED: GET MEDICAL ATTENTION.

IF INHALED:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR PHYSICIAN IF YOU FEEL UNWELL.

IF SWALLOWED:

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. DO NOT INDUCE VOMITING.

IF ON SKIN:

WASH WITH PLENTY OF SOAP AND WATER. TAKE OFF CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSE.

IF SKIN IRRITATION OCCURS: GET MEDICAL ATTENTION.

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

IF EYE IRRITATION PERSISTS: GET MEDICAL ATTENTION.

STORAGE:

STORE LOCKED UP. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F. STORE IN A WELL-VENTILATED PLACE.

DISPOSAL:

DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH ALL LOCAL, REGIONAL, NATIONAL AND INTERNATIONAL REGULATIONS.

SUPPLEMENTAL LABEL ELEMENTS:

DANGER:

RAGS, STEEL WOOL, OTHER WASTE SOAKED WITH THIS PRODUCT, AND SANDING RESIDUE MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY PLACE RAGS, STEEL WOOL, OTHER WASTE SOAKED WITH THIS PRODUCT, AND SANDING RESIDUE IN A SEALED, WATER-FILLED, METAL CONTAINER. DISPOSE OF IN ACCORDANCE WITH LOCAL FIRE REGULATIONS. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. CONTAINS SOLVENTS WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

WARNING:

THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. FOR INDUSTRIAL USE ONLY.

PLEASE REFER TO THE SDS FOR ADDITIONAL INFORMATION. KEEP UPRIGHT IN A COOL, DRY PLACE. DO NOT DISCARD EMPTY CAN IN TRASH COMPACTOR.

HAZARDS NOT OTHERWISE CLASSIFIED: NONE KNOWN.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS



SUBSTANCE/MIXTURE: MIXTURE

OTHER MEANS OF IDENTIFICATION: NOT AVAILABLE.

CAS NUMBER/OTHER IDENTIFIERS:

INGREDIENT NAME	% BY WEIGHT	CAS NUMBER
TOLUENE	20.7	108-88-3
PROPANE	12.2	74-98-6
BUTANE	5.8	106-97-8
LT. ALIPHATIC HYDROCARBON SOLVENT	2.0	64742-89-8
TITANIUM DIOXIDE	0.5	13463-67-7
1-METHYL-2-PYRROLIDONE	0.1	872-50-4

THERE ARE NO ADDITIONAL INGREDIENTS PRESENT WHICH, WITHIN THE CURRENT KNOWLEDGE OF THE SUPPLIER AND IN THE CONCENTRATIONS APPLICABLE, ARE CLASSIFIED AS HAZARDOUS TO HEALTH OR THE ENVIRONMENT AND HENCE REQUIRE REPORTING IN THIS SECTION.

OCCUPATIONAL EXPOSURE LIMITS, IF AVAILABLE, ARE LISTED IN SECTION 8.

### SECTION 4. FIRST AID MEASURES



DESCRIPTION OF NECESSARY FIRST AID MEASURES:

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, OCCASIONALLY LIFTING THE UPPER AND LOWER EYELIDS. CHECK FOR AND REMOVE ANY CONTACT LENSES. CONTINUE TO RINSE FOR AT LEAST 10 MINUTES. GET MEDICAL ATTENTION.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. IF IT IS SUSPECTED THAT FUMES ARE STILL PRESENT, THE RESCUER SHOULD WEAR AN APPROPRIATE MASK OR SELF-CONTAINED BREATHING APPARATUS. IF NOT BREATHING, IF BREATHING IS IRREGULAR OR IF RESPIRATORY ARREST OCCURS, PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN BY TRAINED PERSONNEL. IT MAY BE DANGEROUS TO THE PERSON PROVIDING AID TO GIVE MOUTH-TO-MOUTH RESUSCITATION. GET MEDICAL ATTENTION. IF NECESSARY, CALL A POISON CENTER OR PHYSICIAN. IF UNCONSCIOUS, PLACE IN RECOVERY POSITION AND GET MEDICAL ATTENTION IMMEDIATELY. MAINTAIN AN OPEN AIRWAY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.

SKIN CONTACT:

FLUSH CONTAMINATED SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. WASH CONTAMINATED CLOTHING THOROUGHLY WITH WATER BEFORE REMOVING IT, OR WEAR GLOVES. CONTINUE TO RINSE FOR AT LEAST 10 MINUTES. GET MEDICAL ATTENTION. WASH CLOTHING BEFORE REUSE. CLEAN SHOES THOROUGHLY BEFORE REUSE.

INGESTION:

GET MEDICAL ATTENTION IMMEDIATELY. CALL A POISON CENTER OR PHYSICIAN. WASH OUT MOUTH WITH WATER. REMOVE DENTURES IF ANY. REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. IF MATERIAL HAS BEEN SWALLOWED AND THE EXPOSED PERSON IS CONSCIOUS, GIVE SMALL QUANTITIES OF WATER TO DRINK. STOP IF THE EXPOSED PERSON FEELS SICK AS VOMITING MAY BE DANGEROUS. ASPIRATION HAZARD IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE. DO NOT INDUCE VOMITING. IF VOMITING OCCURS, THE HEAD SHOULD BE KEPT LOW SO THAT VOMIT DOES NOT ENTER THE LUNGS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF UNCONSCIOUS, PLACE IN RECOVERY POSITION AND GET MEDICAL ATTENTION IMMEDIATELY. MAINTAIN AN OPEN AIRWAY. LOOSEN TIGHT CLOTHING SUCH AS A COLLAR, TIE, BELT OR WAISTBAND.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

POTENTIAL ACUTE HEALTH EFFECTS:

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION.

INHALATION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY CAUSE DROWSINESS AND DIZZINESS. MAY CAUSE RESPIRATORY IRRITATION.

SKIN CONTACT: CAUSES SKIN IRRITATION.

INGESTION:

CAN CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. IRRITATING TO MOUTH, THROAT AND STOMACH.

OVER-EXPOSURE SIGNS/SYMPTOMS:

EYE CONTACT:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:  
PAIN OR IRRITATION  
WATERING  
REDNESS

INHALATION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:  
RESPIRATORY TRACT IRRITATION  
COUGHING  
NAUSEA OR VOMITING  
HEADACHE  
DROWSINESS/FATIGUE  
DIZZINESS/VERTIGO  
UNCONSCIOUSNESS  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

SKIN CONTACT:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:  
IRRITATION  
REDNESS  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

INGESTION:

ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:

NAUSEA OR VOMITING  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY:

NOTES TO PHYSICIAN:

TREAT SYMPTOMATICALLY. CONTACT POISON TREATMENT SPECIALIST IMMEDIATELY IF LARGE QUANTITIES HAVE BEEN INGESTED OR INHALED.

SPECIFIC TREATMENTS: NO SPECIFIC TREATMENT.

PROTECTION OF FIRST-AIDERS:

NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. IF IT IS SUSPECTED THAT FUMES ARE STILL PRESENT, THE RESCUER SHOULD WEAR AN APPROPRIATE MASK OR SELF-CONTAINED BREATHING APPARATUS. IT MAY BE DANGEROUS TO THE PERSON PROVIDING AID TO GIVE MOUTH-TO-MOUTH RESUSCITATION. WASH CONTAMINATED CLOTHING THOROUGHLY WITH WATER BEFORE REMOVING IT, OR WEAR GLOVES.

SEE TOXICOLOGICAL INFORMATION (SECTION 11)

## SECTION 5. FIRE-FIGHTING MEASURES



EXTINGUISHING MEDIA:

SUITABLE EXTINGUISHING MEDIA:

USE AN EXTINGUISHING AGENT SUITABLE FOR THE SURROUNDING FIRE.

UNSUITABLE EXTINGUISHING MEDIA: NONE KNOWN.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

EXTREMELY FLAMMABLE AEROSOL. IN A FIRE OR IF HEATED, A PRESSURE INCREASE WILL OCCUR AND THE CONTAINER MAY BURST, WITH THE RISK OF A SUBSEQUENT EXPLOSION. GAS MAY ACCUMULATE IN LOW OR CONFINED AREAS OR TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK, CAUSING FIRE OR EXPLOSION. BURSTING AEROSOL CONTAINERS MAY BE PROPELLED FROM A FIRE AT HIGH SPEED. RUNOFF TO SEWER MAY CREATE FIRE OR EXPLOSION HAZARD.

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:

DECOMPOSITION PRODUCTS MAY INCLUDE THE FOLLOWING MATERIALS:

CARBON DIOXIDE  
CARBON MONOXIDE  
METAL OXIDE/OXIDES

SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS:

PROMPTLY ISOLATE THE SCENE BY REMOVING ALL PERSONS FROM THE VICINITY OF THE INCIDENT IF THERE IS A FIRE. NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. MOVE CONTAINERS FROM FIRE AREA IF THIS CAN BE DONE WITHOUT RISK. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS:

FIRE-FIGHTERS SHOULD WEAR APPROPRIATE PROTECTIVE EQUIPMENT AND SELF-CONTAINED BREATHING APPARATUS (SCBA) WITH A FULL FACE-PIECE OPERATED IN POSITIVE PRESSURE MODE.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

FOR NON-EMERGENCY PERSONNEL:

NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. EVACUATE SURROUNDING AREAS. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. IN THE CASE OF AEROSOLS BEING RUPTURED, CARE SHOULD BE TAKEN DUE TO THE RAPID ESCAPE OF THE PRESSURIZED CONTENTS AND PROPELLANT. IF A LARGE NUMBER OF CONTAINERS ARE RUPTURED, TREAT AS A BULK MATERIAL SPILLAGE ACCORDING TO THE INSTRUCTIONS IN THE CLEAN-UP SECTION. DO NOT TOUCH OR WALK THROUGH SPILLED MATERIAL. SHUT OFF ALL IGNITION SOURCES. NO FLARES, SMOKING OR FLAMES IN HAZARD AREA. AVOID BREATHING VAPOR OR MIST. PROVIDE ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.

FOR EMERGENCY RESPONDERS:

IF SPECIALISED CLOTHING IS REQUIRED TO DEAL WITH THE SPILLAGE, TAKE NOTE OF ANY INFORMATION IN SECTION 8 ON SUITABLE AND UNSUITABLE MATERIALS. SEE ALSO THE INFORMATION IN "FOR NON-EMERGENCY PERSONNEL".

ENVIRONMENTAL PRECAUTIONS:

AVOID DISPERSAL OF SPILLED MATERIAL AND RUNOFF AND CONTACT WITH SOIL, WATERWAYS, DRAINS AND SEWERS. INFORM THE RELEVANT AUTHORITIES IF THE PRODUCT HAS CAUSED ENVIRONMENTAL POLLUTION (SEWERS, WATERWAYS, SOIL OR AIR).

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

SMALL SPILL:

STOP LEAK IF WITHOUT RISK. MOVE CONTAINERS FROM SPILL AREA. USE SPARK-PROOF TOOLS AND EXPLOSION-PROOF EQUIPMENT. DILUTE WITH WATER AND MOP UP IF WATER-SOLUBLE. ALTERNATIVELY, OR IF WATER-INSOLUBLE, ABSORB WITH AN INERT DRY MATERIAL AND PLACE IN AN APPROPRIATE WASTE DISPOSAL CONTAINER. DISPOSE OF VIA A LICENSED WASTE DISPOSAL CONTRACTOR.

LARGE SPILL:

STOP LEAK IF WITHOUT RISK. MOVE CONTAINERS FROM SPILL AREA. USE SPARK-PROOF TOOLS AND EXPLOSION-PROOF EQUIPMENT. APPROACH RELEASE FROM UPWIND. PREVENT ENTRY INTO SEWERS, WATER COURSES, BASEMENTS OR CONFINED AREAS. WASH SPILLAGES INTO AN EFFLUENT TREATMENT PLANT OR PROCEED AS FOLLOWS. CONTAIN AND COLLECT SPILLAGE WITH NON-COMBUSTIBLE, ABSORBENT MATERIAL E.G. SAND, EARTH, VERMICULITE OR DIATOMACEOUS EARTH AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13). DISPOSE OF VIA A LICENSED WASTE DISPOSAL CONTRACTOR. CONTAMINATED ABSORBENT MATERIAL MAY POSE THE SAME HAZARD AS THE SPILLED PRODUCT.

NOTE:

SEE SECTION 1 FOR EMERGENCY CONTACT INFORMATION AND SECTION 13 FOR WASTE DISPOSAL.

## **SECTION 7. HANDLING AND STORAGE**



PRECAUTIONS FOR SAFE HANDLING:

PROTECTIVE MEASURES:

PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT (SEE SECTION 8).

**PRESSURIZED CONTAINER:**

PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C. DO NOT PIERCE OR BURN, EVEN AFTER USE. AVOID EXPOSURE - OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. AVOID EXPOSURE DURING PREGNANCY. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. DO NOT GET IN EYES OR ON SKIN OR CLOTHING. DO NOT BREATHE VAPOR OR MIST. DO NOT SWALLOW. AVOID BREATHING GAS. USE ONLY WITH ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE. STORE AND USE AWAY FROM HEAT, SPARKS, OPEN FLAME OR ANY OTHER IGNITION SOURCE. USE EXPLOSION-PROOF ELECTRICAL (VENTILATING, LIGHTING AND MATERIAL HANDLING) EQUIPMENT. USE ONLY NON-SPARKING TOOLS. EMPTY CONTAINERS RETAIN PRODUCT RESIDUE AND CAN BE HAZARDOUS.

**ADVICE ON GENERAL OCCUPATIONAL HYGIENE:**

EATING, DRINKING AND SMOKING SHOULD BE PROHIBITED IN AREAS WHERE THIS MATERIAL IS HANDLED, STORED AND PROCESSED. WORKERS SHOULD WASH HANDS AND FACE BEFORE EATING, DRINKING AND SMOKING. REMOVE CONTAMINATED CLOTHING AND PROTECTIVE EQUIPMENT BEFORE ENTERING EATING AREAS. SEE ALSO SECTION 8 FOR ADDITIONAL INFORMATION ON HYGIENE MEASURES.

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**

STORE IN ACCORDANCE WITH LOCAL REGULATIONS. STORE AWAY FROM DIRECT SUNLIGHT IN A DRY, COOL AND WELL-VENTILATED AREA, AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10) AND FOOD AND DRINK. PROTECT FROM SUNLIGHT. STORE LOCKED UP. ELIMINATE ALL IGNITION SOURCES. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**



**CONTROL PARAMETERS:**

**OCCUPATIONAL EXPOSURE LIMITS:**

INGREDIENT NAME	EXPOSURE LIMITS
TOLUENE	OSHA PEL Z2 (UNITED STATES, 2/2013). TWA: 200 PPM 8 HOURS. CEIL: 300 PPM AMP: 500 PPM 10 MINUTES.  NIOSH REL (UNITED STATES, 10/2013). TWA: 100 PPM 10 HOURS. TWA: 375 MG/M3 10 HOURS.  STEL: 150 PPM 15 MINUTES. STEL: 560 MG/M3 15 MINUTES.  ACGIH TLV (UNITED STATES, 4/2014). TWA: 20 PPM 8 HOURS.
PROPANE	NIOSH REL (UNITED STATES, 10/2013). TWA: 1000 PPM 10 HOURS. TWA: 1800 MG/M3 10 HOURS.  OSHA PEL (UNITED STATES, 2/2013). TWA: 1000 PPM 8 HOURS. TWA: 1800 MG/M3 8 HOURS.
BUTANE	NIOSH REL (UNITED STATES, 10/2013). TWA: 800 PPM 10 HOURS. TWA: 1900 MG/M3 10 HOURS.



ACGIH TLV (UNITED STATES, 4/2014).  
STEL: 1000 PPM 15 MINUTES.

TITANIUM DIOXIDE ACGIH TLV (UNITED STATES, 4/2014).  
TWA: 10 MG/M3 8 HOURS.

OSHA PEL (UNITED STATES, 2/2013).  
TWA: 15 MG/M3 8 HOURS.  
FORM: TOTAL DUST

1-METHYL-2-PYRROLIDONE AIHA WEEL (UNITED STATES, 10/2011).  
ABSORBED THROUGH SKIN.  
TWA: 10 PPM 8 HOURS.

APPROPRIATE ENGINEERING CONTROLS:

USE ONLY WITH ADEQUATE VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO KEEP WORKER EXPOSURE TO AIRBORNE CONTAMINANTS BELOW ANY RECOMMENDED OR STATUTORY LIMITS. THE ENGINEERING CONTROLS ALSO NEED TO KEEP GAS, VAPOR OR DUST CONCENTRATIONS BELOW ANY LOWER EXPLOSIVE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT.

ENVIRONMENTAL EXPOSURE CONTROLS:

EMISSIONS FROM VENTILATION OR WORK PROCESS EQUIPMENT SHOULD BE CHECKED TO ENSURE THEY COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION LEGISLATION. IN SOME CASES, FUME SCRUBBERS, FILTERS OR ENGINEERING MODIFICATIONS TO THE PROCESS EQUIPMENT WILL BE NECESSARY TO REDUCE EMISSIONS TO ACCEPTABLE LEVELS.

INDIVIDUAL PROTECTION MEASURES:

HYGIENE MEASURES:

WASH HANDS, FOREARMS AND FACE THOROUGHLY AFTER HANDLING CHEMICAL PRODUCTS, BEFORE EATING, SMOKING AND USING THE LAVATORY AND AT THE END OF THE WORKING PERIOD. APPROPRIATE TECHNIQUES SHOULD BE USED TO REMOVE POTENTIALLY CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSING. ENSURE THAT EYEWASH STATIONS AND SAFETY SHOWERS ARE CLOSE TO THE WORKSTATION LOCATION.

EYE/FACE PROTECTION:

SAFETY EYEWEAR COMPLYING WITH AN APPROVED STANDARD SHOULD BE USED WHEN A RISK ASSESSMENT INDICATES THIS IS NECESSARY TO AVOID EXPOSURE TO LIQUID SPLASHES, MISTS, GASES OR DUSTS. IF CONTACT IS POSSIBLE, THE FOLLOWING PROTECTION SHOULD BE WORN, UNLESS THE ASSESSMENT INDICATES A HIGHER DEGREE OF PROTECTION: CHEMICAL SPLASH GOGGLES.

SKIN PROTECTION:

HAND PROTECTION:

CHEMICAL-RESISTANT, IMPERVIOUS GLOVES COMPLYING WITH AN APPROVED STANDARD SHOULD BE WORN AT ALL TIMES WHEN HANDLING CHEMICAL PRODUCTS IF A RISK ASSESSMENT INDICATES THIS IS NECESSARY. CONSIDERING THE PARAMETERS SPECIFIED BY THE GLOVE MANUFACTURER, CHECK DURING USE THAT THE GLOVES ARE STILL RETAINING THEIR PROTECTIVE PROPERTIES. IT SHOULD BE NOTED THAT THE TIME TO BREAKTHROUGH FOR ANY GLOVE MATERIAL MAY BE DIFFERENT FOR DIFFERENT GLOVE MANUFACTURERS. IN THE CASE OF MIXTURES, CONSISTING OF SEVERAL SUBSTANCES, THE PROTECTION TIME OF THE GLOVES CANNOT BE ACCURATELY ESTIMATED.

BODY PROTECTION:

PERSONAL PROTECTIVE EQUIPMENT FOR THE BODY SHOULD BE SELECTED BASED ON THE TASK BEING PERFORMED AND THE RISKS INVOLVED AND SHOULD BE APPROVED BY A SPECIALIST BEFORE HANDLING THIS PRODUCT. WHEN THERE IS A RISK OF IGNITION

FROM STATIC ELECTRICITY, WEAR ANTISTATIC PROTECTIVE CLOTHING. FOR THE GREATEST PROTECTION FROM STATIC DISCHARGES, CLOTHING SHOULD INCLUDE ANTI-STATIC OVERALLS, BOOTS AND GLOVES.

**OTHER SKIN PROTECTION:**

APPROPRIATE FOOTWEAR AND ANY ADDITIONAL SKIN PROTECTION MEASURES SHOULD BE SELECTED BASED ON THE TASK BEING PERFORMED AND THE RISKS INVOLVED AND SHOULD BE APPROVED BY A SPECIALIST BEFORE HANDLING THIS PRODUCT.

**RESPIRATORY PROTECTION:**

USE A PROPERLY FITTED, AIR-PURIFYING OR AIR-FED RESPIRATOR COMPLYING WITH AN APPROVED STANDARD IF A RISK ASSESSMENT INDICATES THIS IS NECESSARY. RESPIRATOR SELECTION MUST BE BASED ON KNOWN OR ANTICIPATED EXPOSURE LEVELS, THE HAZARDS OF THE PRODUCT AND THE SAFE WORKING LIMITS OF THE SELECTED RESPIRATOR.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**



**APPEARANCE:**

PHYSICAL STATE: LIQUID.

COLOR: NOT AVAILABLE.

ODOR: NOT AVAILABLE.

ODOR THRESHOLD: NOT AVAILABLE.

PH: 7

MELTING POINT: NOT AVAILABLE.

BOILING POINT: NOT AVAILABLE.

**FLASH POINT:**

CLOSED CUP: -29 DEG. C (-20.2 DEG. F) [PENSKY-MARTENS CLOSED CUP]

EVAPORATION RATE: 3.22 (BUTYL ACETATE = 1)

FLAMMABILITY (SOLID, GAS): NOT AVAILABLE.

**LOWER AND UPPER EXPLOSIVE (FLAMMABLE) LIMITS:**

LOWER: 0.9%

UPPER: 12.8%

VAPOR PRESSURE: 13.5 KPA (101.325 MMHg) [AT 20 DEG. C]

VAPOR DENSITY: 1 [AIR = 1]

RELATIVE DENSITY: 0.86

SOLUBILITY: NOT AVAILABLE.

PARTITION COEFFICIENT N-OCTANOL/WATER: NOT AVAILABLE.

AUTO-IGNITION TEMPERATURE: NOT AVAILABLE.

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

**VISCOSITY:**

KINEMATIC (ROOM TEMPERATURE): <0.07 CM<sup>2</sup>/S (<7 CST)

KINEMATIC (40 DEG. C (104 DEG. F)): <0.07 CM2/S (<7 CST)

AEROSOL PRODUCT:

TYPE OF AEROSOL: SPRAY

HEAT OF COMBUSTION: 0.00002216 KJ/G

## SECTION 10. STABILITY AND REACTIVITY



REACTIVITY:

NO SPECIFIC TEST DATA RELATED TO REACTIVITY AVAILABLE FOR THIS PRODUCT OR ITS INGREDIENTS.

CHEMICAL STABILITY: THE PRODUCT IS STABLE.

POSSIBILITY OF HAZARDOUS REACTIONS:

UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS REACTIONS WILL NOT OCCUR.

CONDITIONS TO AVOID:

AVOID ALL POSSIBLE SOURCES OF IGNITION (SPARK OR FLAME).

INCOMPATIBLE MATERIALS: NO SPECIFIC DATA.

HAZARDOUS DECOMPOSITION PRODUCTS:

UNDER NORMAL CONDITIONS OF STORAGE AND USE, HAZARDOUS DECOMPOSITION PRODUCTS SHOULD NOT BE PRODUCED.

## SECTION 11. TOXICOLOGICAL INFORMATION



INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	DOSE	EXPOSURE
TOLUENE	LC50 INHALATION VAPOR	RAT	49 G/M3	4 HOURS
	LD50 ORAL	RAT	636 MG/KG	
BUTANE	LC50 INHALATION VAPOR	RAT	658000 MG/M3	4 HOURS
1-METHYL-2-PYRROLIDONE	LD50 DERMAL	RABBIT	8 G/KG	
	LD50 ORAL	RAT	3914 MG/KG	

IRRITATION/CORROSION:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	SCORE	EXPOSURE	OBSERVATION
TOLUENE	EYES: MILD IRRITANT	RABBIT		0.5 MINUTES 100 MILLIGRAMS	
	EYES: MILD	RABBIT		870 MICROGRAMS	

IRRITANT

EYES: RABBIT 24 HOURS  
 SEVERE 2 MILLIGRAMS  
 IRRITANT

SKIN: PIG 24 HOURS  
 MILD 250 MICROLITERS  
 IRRITANT

SKIN: RABBIT 435 MILLIGRAMS  
 MILD  
 IRRITANT

SKIN: RABBIT 24 HOURS  
 MODERATE 20 MILLIGRAMS  
 IRRITANT

SKIN: RABBIT 500 MILLIGRAMS  
 MODERATE  
 IRRITANT

TITANIUM DIOXIDE SKIN: HUMAN 72 HOURS  
 MILD 300 MICROGRAMS  
 IRRITANT INTERMITTENT

1-METHYL-2-PYRROLIDONE EYES: RABBIT 100 MILLIGRAMS  
 MODERATE  
 IRRITANT

SENSITIZATION: NOT AVAILABLE.

MUTAGENICITY: NOT AVAILABLE.

CARCINOGENICITY: NOT AVAILABLE.

CLASSIFICATION:

PRODUCT/INGREDIENT NAME	OSHA	IARC	NTP
TOLUENE		3	
TITANIUM DIOXIDE		2B	

REPRODUCTIVE TOXICITY: NOT AVAILABLE.

TERATOGENICITY: NOT AVAILABLE.

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE):

NAME	CATEGORY	ROUTE OF EXPOSURE	TARGET ORGANS
TOLUENE	CATEGORY 3	NOT APPLICABLE.	RESPIRATORY TRACT IRRITATION AND NARCOTIC EFFECTS
PROPANE	CATEGORY 3	NOT APPLICABLE.	RESPIRATORY TRACT IRRITATION AND NARCOTIC EFFECTS
BUTANE	CATEGORY 3	NOT APPLICABLE.	RESPIRATORY TRACT IRRITATION AND NARCOTIC EFFECTS



UNCONSCIOUSNESS  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

SKIN CONTACT:  
ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:  
IRRITATION  
REDNESS  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

INGESTION:  
ADVERSE SYMPTOMS MAY INCLUDE THE FOLLOWING:  
NAUSEA OR VOMITING  
REDUCED FETAL WEIGHT  
INCREASE IN FETAL DEATHS  
SKELETAL MALFORMATIONS

DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE:

SHORT TERM EXPOSURE:  
POTENTIAL IMMEDIATE EFFECTS: NOT AVAILABLE.  
POTENTIAL DELAYED EFFECTS: NOT AVAILABLE.

LONG TERM EXPOSURE:  
POTENTIAL IMMEDIATE EFFECTS: NOT AVAILABLE.  
POTENTIAL DELAYED EFFECTS: NOT AVAILABLE.

POTENTIAL CHRONIC HEALTH EFFECTS: NOT AVAILABLE.

GENERAL: MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

CARCINOGENICITY:  
SUSPECTED OF CAUSING CANCER. RISK OF CANCER DEPENDS ON DURATION AND LEVEL OF EXPOSURE.

MUTAGENICITY: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

TERATOGENICITY: MAY DAMAGE THE UNBORN CHILD.

DEVELOPMENTAL EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

FERTILITY EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

NUMERICAL MEASURES OF TOXICITY:

ACUTE TOXICITY ESTIMATES:

ROUTE	ATE VALUE
ORAL	2470.5 MG/KG

## SECTION 12. ECOLOGICAL INFORMATION



TOXICITY:

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	EXPOSURE
-------------------------	--------	---------	----------

TOLUENE	ACUTE EC50: 12500 (MICRO)G/L FRESH WATER	ALGAE - PSEUDOKIRCHNERIELLA SUBCAPITATA	72 HOURS
	ACUTE EC50: 11600 (MICRO)G/L FRESH WATER	CRUSTACEANS - GAMMARUS PSEUDOLIMNAEUS - ADULT	48 HOURS
	ACUTE EC50: 6000 (MICRO)G/L FRESH WATER	DAPHNIA - DAPHNIA MAGNA - JUVENILE (FLEDGLING, HATCHLING, WEANLING)	48 HOURS
	ACUTE LC50: 5500 (MICRO)G/L FRESH WATER	FISH - ONCORHYNCHUS KISUTCH - FRY	96 HOURS
	CHRONIC NOEC: 1000 (MICRO)G/L FRESH WATER	DAPHNIA - DAPHNIA MAGNA	21 DAYS
LT. ALIPHATIC HYDROCARBON SOLVENT	ACUTE LC50: >100000 PPM FRESH WATER	FISH - ONCORHYNCHUS MYKISS	96 HOURS
TITANIUM DIOXIDE	ACUTE LC50: >1000000 (MICRO)G/L MARINE WATER	FISH - FUNDULUS HETEROCLITUS	96 HOURS
1-METHYL-2- PYRROLIDONE	ACUTE LC50: 1.23 PPM FRESH WATER	DAPHNIA - DAPHNIA MAGNA	48 HOURS
	ACUTE LC50: 832 PPM FRESH WATER	FISH - LEPOMIS MACROCHIRUS	96 HOURS

PERSISTENCE AND DEGRADABILITY:

PRODUCT/INGREDIENT NAME	AQUATIC HALF-LIFE	PHOTOLYSIS	BIODEGRADABILITY
TOLUENE			READILY

BIOACCUMULATIVE POTENTIAL:

PRODUCT/INGREDIENT NAME	LOGPOW	BCF	POTENTIAL
TOLUENE		90	LOW
LT. ALIPHATIC HYDROCARBON SOLVENT		10 TO 2500	HIGH
TITANIUM DIOXIDE		352	LOW

MOBILITY IN SOIL:

SOIL/WATER PARTITION COEFFICIENT (KOC): NOT AVAILABLE.

OTHER ADVERSE EFFECTS: NO KNOWN SIGNIFICANT EFFECTS OR CRITICAL HAZARDS.

**SECTION 13. DISPOSAL CONSIDERATIONS**

DISPOSAL METHODS:

THE GENERATION OF WASTE SHOULD BE AVOIDED OR MINIMIZED WHEREVER POSSIBLE. DISPOSAL OF THIS PRODUCT, SOLUTIONS AND ANY BY-PRODUCTS SHOULD AT ALL TIMES COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL LEGISLATION AND ANY REGIONAL LOCAL AUTHORITY REQUIREMENTS. DISPOSE OF SURPLUS AND NON-RECYCLABLE PRODUCTS VIA A LICENSED WASTE DISPOSAL CONTRACTOR. WASTE SHOULD NOT BE DISPOSED OF UNTREATED TO THE SEWER UNLESS FULLY COMPLIANT WITH THE REQUIREMENTS OF ALL AUTHORITIES WITH JURISDICTION. WASTE PACKAGING SHOULD BE RECYCLED. INCINERATION OR LANDFILL SHOULD ONLY BE CONSIDERED WHEN RECYCLING IS NOT FEASIBLE. THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF IN A SAFE WAY. EMPTY CONTAINERS OR LINERS MAY RETAIN SOME PRODUCT RESIDUES. DO NOT PUNCTURE OR INCINERATE CONTAINER.

**SECTION 14. TRANSPORT INFORMATION**



	DOT CLASSIFICATION	TDG CLASSIFICATION	MEXICO CLASSIFICATION
UN NUMBER	UN1950	UN1950	UN1950
UN PROPER SHIPPING NAME	AEROSOLS	AEROSOLS	AEROSOLS
TRANSPORT HAZARD CLASS (ES)	2.1 FLAMMABLE GAS, CLASS/DIVISION 2.1	2.1 CLASS 2.1, FLAMMABLE GASES	2.1 CLASS 2.1, FLAMMABLE GASES
PACKING GROUP			
ENVIRONMENTAL HAZARDS	NO.	NO.	NO.
ADDITIONAL INFORMATION	SPECIAL PROVISIONS: LIMITED QUANTITY	SPECIAL PROVISIONS: LIMITED QUANTITY	SPECIAL PROVISIONS: (ERG#126)

	IATA	IMDG
UN NUMBER	UN1950	UN1950
UN PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE	AEROSOLS
TRANSPORT HAZARD CLASS (ES)	2.1 CLASS 2.1, FLAMMABLE GASES	2.1 CLASS 2.1 - FLAMMABLE GASES
PACKING GROUP		
ENVIRONMENTAL HAZARDS	NO.	NO.
ADDITIONAL INFORMATION	SPECIAL PROVISIONS: LIMITED QUANTITY	EMERGENCY SCHEDULES (EMS): LIMITED QUANTITY, F-D, S-U

SPECIAL PRECAUTIONS FOR USER:



MULTI-MODAL SHIPPING DESCRIPTIONS ARE PROVIDED FOR INFORMATIONAL PURPOSES AND DO NOT CONSIDER CONTAINER SIZES. THE PRESENCE OF A SHIPPING DESCRIPTION FOR A PARTICULAR MODE OF TRANSPORT (SEA, AIR, ETC.), DOES NOT INDICATE THAT THE PRODUCT IS PACKAGED SUITABLY FOR THAT MODE OF TRANSPORT. ALL PACKAGING MUST BE REVIEWED FOR SUITABILITY PRIOR TO SHIPMENT, AND COMPLIANCE WITH THE APPLICABLE REGULATIONS IS THE SOLE RESPONSIBILITY OF THE PERSON OFFERING THE PRODUCT FOR TRANSPORT. PEOPLE LOADING AND UNLOADING DANGEROUS GOODS MUST BE TRAINED ON ALL OF THE RISKS DERIVING FROM THE SUBSTANCES AND ON ALL ACTIONS IN CASE OF EMERGENCY SITUATIONS.

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE: NOT AVAILABLE.

## SECTION 15. REGULATORY INFORMATION



U.S. FEDERAL REGULATIONS:

STATE REGULATIONS:

CALIFORNIA PROP. 65:

WARNING:

THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

## SECTION 16. OTHER INFORMATION



HAZARDOUS MATERIAL INFORMATION SYSTEM (U.S.A.):

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARDS	0

CAUTION:

HMIS(R\*) RATINGS ARE BASED ON A 0-4 RATING SCALE, WITH 0 REPRESENTING MINIMAL HAZARDS OR RISKS, AND 4 REPRESENTING SIGNIFICANT HAZARDS OR RISKS ALTHOUGH HMIS(R\*) RATINGS ARE NOT REQUIRED ON SDSS UNDER 29 CFR 1910.1200, THE PREPARER MAY CHOOSE TO PROVIDE THEM. HMIS(R\*) RATINGS ARE TO BE USED WITH A FULLY IMPLEMENTED HMIS(R\*) PROGRAM. HMIS(R\*) IS A REGISTERED MARK OF THE NATIONAL PAINT & COATINGS ASSOCIATION (NPCA). HMIS(R\*) MATERIALS MAY BE PURCHASED EXCLUSIVELY FROM J. J. KELLER (800) 327-6868.

THE CUSTOMER IS RESPONSIBLE FOR DETERMINING THE PPE CODE FOR THIS MATERIAL.

NOTICE TO READER:

IT IS RECOMMENDED THAT EACH CUSTOMER OR RECIPIENT OF THIS SAFETY DATA SHEET (SDS) STUDY IT CAREFULLY AND CONSULT RESOURCES, AS NECESSARY OR APPROPRIATE, TO BECOME AWARE OF AND UNDERSTAND THE DATA CONTAINED IN THIS SDS AND ANY HAZARDS ASSOCIATED WITH THE PRODUCT. THIS INFORMATION IS PROVIDED IN GOOD FAITH AND BELIEVED TO BE ACCURATE AS OF THE EFFECTIVE DATE HEREIN. HOWEVER, NO WARRANTY, EXPRESS OR IMPLIED, IS GIVEN. THE INFORMATION PRESENTED HERE APPLIES ONLY TO THE PRODUCT AS SHIPPED. THE ADDITION OF ANY MATERIAL CAN CHANGE THE COMPOSITION, HAZARDS AND RISKS OF THE PRODUCT. REGULATORY REQUIREMENTS ARE SUBJECT TO CHANGE AND MAY DIFFER BETWEEN VARIOUS LOCATIONS AND JURISDICTIONS. THE CUSTOMER/BUYER/USER IS RESPONSIBLE TO ENSURE THAT HIS ACTIVITIES COMPLY WITH ALL COUNTRY, FEDERAL, STATE, PROVINCIAL OR LOCAL LAWS. THE CONDITIONS FOR USE OF THE PRODUCT ARE NOT UNDER THE CONTROL OF THE MANUFACTURER; THE CUSTOMER/BUYER/USER IS RESPONSIBLE TO DETERMINE THE CONDITIONS NECESSARY FOR THE SAFE USE OF THIS PRODUCT. THE CUSTOMER/BUYER/USER SHOULD NOT USE THE PRODUCT FOR ANY PURPOSE

OTHER THAN THE PURPOSE SHOWN IN THE APPLICABLE SECTION OF THIS SDS WITHOUT FIRST REFERRING TO THE SUPPLIER AND OBTAINING WRITTEN HANDLING INSTRUCTIONS. DUE TO THE PROLIFERATION OF SOURCES FOR INFORMATION SUCH AS MANUFACTURER-SPECIFIC SDS, THE MANUFACTURER CANNOT BE RESPONSIBLE FOR SDSS OBTAINED FROM ANY OTHER SOURCE.

DATE OF ISSUE/DATE OF REVISION: 4/7/2015.

DATE OF PREVIOUS ISSUE: 3/13/2015.

VERSION: 1.01