

SAFETY DATA SHEET

1. Identification

Product identifier ZRC Galvilite Galvanizing Repair Compound

Other means of identification

Product code 20012 - 20014

Recommended use Corrosion protection of iron and steel.

Recommended restrictions None known.

Manufacturer / Importer / Supplier / Distributor information

Supplier/Manufacturer ZRC Worldwide
Address 145 Enterprise Drive, Marshfield, MA 02050
Telephone 781-319-0400
Emergency telephone (CHEMTREC) 703-527-3887 CCN15781

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Skin corrosion/irritation Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

Response Rinse mouth. In case of fire: Use appropriate media to extinguish. If on skin: Wash with plenty of water. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Not classified.

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 1

Hazardous to the aquatic environment, long-term hazard Category 1

Supplemental information

Hazard symbol



Hazard statement Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid release to the environment.

Response Collect spillage.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Zinc	7440-66-6	75 - 85
Solvent naphtha (petroleum), medium aliph.	64742-88-7	4 - 6
Distillates (petroleum), hydrotreated light	64742-47-8	4 - 5
Zinc oxide	1314-13-2	2 - 3
Solvent naphtha (petroleum), light aromatic	64742-95-6	0.5 - 0.9

4. First-aid measures

Inhalation	Move to fresh air. Get medical attention if any discomfort continues.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Get medical attention if any discomfort occurs.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Causes skin irritation. Swallowing may cause gastrointestinal irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

5. Fire-fighting measures

Suitable extinguishing media	Dry chemical, CO ₂ , water spray, fog, or foam.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	By heating and fire, harmful vapors/gases may be formed. Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire-fighting equipment/instructions	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire, cool tanks with water spray. Move containers from fire area if you can do so without risk. In case of fire and/or explosion do not breathe fumes. Water runoff can cause environmental damage.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Collect spillage. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see Section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. For further information, please refer to Section 10 of the SDS.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Fume.
		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

US NIOSH Pocket Guide to Chemical Hazards: Ceiling Limit Value and Time Period (if specified)

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Zinc oxide (CAS 1314-13-2)	TWA	5 mg/m3	Dust.
		5 mg/m3	Fume.

US NIOSH Pocket Guide to Chemical Hazards: Short Term Exposure Limit (STEL)

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Fume.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Do not get in eyes. If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection

Use protective gloves made of: Rubber (natural, latex).

Other

Wear suitable protective clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Gray liquid.

Physical state

Liquid.

Form

Liquid.

Color

Gray.

Odor

Aliphatic. Hydrocarbon.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

291.2 - 404.6 °F (144 - 207 °C)

Flash point

111.2 °F (44.0 °C) Setflash

Evaporation rate

< 1 (n-Butyl acetate=1)

Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.9 %
Flammability limit - upper (%)	7 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1 (25°C / 77°F)
Relative density	2.88 (25°C / 77°F)
Solubility(ies)	Slightly soluble in water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	1800 mPa·s (25°C / 77°F)
Other information	
Bulk density	24 lb/gal
VOC (Weight %)	385 g/l (3.3 lb/gal)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Zinc oxides.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May cause discomfort if swallowed.
Inhalation	Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Causes skin irritation. Swallowing may cause gastrointestinal irritation.

Information on toxicological effects

Acute toxicity Not classified.

Components	Species	Test Results
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5.28 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	3000 mg/kg
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Not classified.	
Respiratory sensitization	Not classified.	
Skin sensitization	Not classified.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Not classified.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not classified.	
Chronic effects	Prolonged exposure may cause chronic effects.	

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Zinc (CAS 7440-66-6)		
Aquatic		
Crustacea	LC50 Daphnia magna	0.068 mg/l, 48 hours
Fish	LC50 Bony fish superclass (Osteichthyes)	0.52 - 3.59 mg/l, 96 hours
Zinc oxide (CAS 1314-13-2)		
Aquatic		
Crustacea	LC50 Water flea (Daphnia magna)	0.098 mg/l, 48 Hours
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	Accumulation in aquatic organisms is expected.	
Mobility in soil	Not available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN number	UN1263
UN proper shipping name	Paint

Transport hazard class(es) 3
Subsidiary class(es) -
Packing group III
Environmental hazards
 Marine pollutant Yes
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1263
UN proper shipping name Paint
Transport hazard class(es) 3
Subsidiary class(es) -
Packaging group III
Environmental hazards Yes
Labels required 3
ERG Code Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1263
UN proper shipping name Paint
Transport hazard class(es) 3
Subsidiary class(es) -
Packaging group III
Environmental hazards
 Marine pollutant Yes
Labels required Not available.
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

General information Limited Quantity exemption may apply.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)
 Zinc (CAS 7440-66-6) LISTED
 Zinc oxide (CAS 1314-13-2) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Zinc	7440-66-6	75 - 85
Zinc oxide	1314-13-2	2 - 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List
Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)
Zinc (CAS 7440-66-6)
Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated light (CAS 64742-47-8) 10000 lbs
Zinc (CAS 7440-66-6) 500 lbs
Zinc oxide (CAS 1314-13-2) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)
Zinc (CAS 7440-66-6)
Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Zinc (CAS 7440-66-6)
Zinc oxide (CAS 1314-13-2)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).


16. Other information, including date of preparation or last revision

Issue date 14-December-2013

Revision date 17-January-2014

Version # 03

NFPA Ratings



References

HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.