

Prepared according to Global Harmonized System (GHS) standards

SECTION 1

CHEMICAL PRODUCT IDENTIFICATION

Bobcat PO Box 128 Gwinner, ND 58040-0128 Tel: 701-241-8700

Product Trade Name: Bobcat Propylene Glycol Antifreeze &

Coolant Premix

CAS Number: Mixture
Synonyms/Other: N/A
Part Number(s): N/A
Recommended Use: Coolant

Restrictions on Use: Not Determined.

Created Date: 6/9/2015 **Preparation/Revision Date:** 6/9/2015

Emergency Phone Number: 1-800-424-9300 (CHEMTREC)

SDS CODE: 13428

SECTION 2

HAZARD IDENTIFICATION

Appearance: Clear, Purple Odor: None

Classification: This material is not considered to be hazardous according to the Globally Harmonized

System of Classification and Labelling Chemicals (GHS), Third Revised Edition.

Target Organs: Not applicable.

Pictogram(s):

Signal Word:

Prevention:

Other Hazards:

Hazard Statement:

None required.
None required.
Not required.
Not determined.
None required.
None required.

Response:None required.Storage Procedures:None required.Disposal:None required.

Other: See section 11 for complete health hazard information.

SECTION 3

COMPOSITION OF INGREDIENTS

Component	CAS Number	Percentage (by weight)
Propylene Glycol	57-55-6	45 - 55%
Water	7732-18-5	45 - 55%

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.



SECTION 4

FIRST AID MEASURES

Eye Contact: If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes,

while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

Skin Contact: Call a doctor if you feel unwell.

Inhalation: Get medical advice or attention if you feel unwell or are concerned.

Ingestion: If you feel unwell or concerned: Get medical advice/attention. Rinse mouth. Do NOT

induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

Other: No additional information

SECTION 5

FIRE FIGHTING MEASURES

Flash Point: Not applicable. Flammable limits: Not applicable. **Extinguishing media:** Not applicable.

Special firefighting procedures: General directions - product will not burn without driving water from material first.

Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect personnel attempting to stop a leak. Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible (safely). Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage tank due to fire. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.

Unusual fire & explosion

hazards:

High temperatures may create heavy flammable vapors that may settle along ground level

and low spots to create an invisible fire hazard.

Byproducts of combustion: Fires involving this product may release oxides of carbon, nitrogen and sulfur; reactive

hydrocarbons and irritating vapors.

Autoignition temperature:

Explosion data:

Not determined. Care should always be exercised in dust/mist areas.

Other: Dispose of fire debris and contaminated extinguishing water in accordance with official

regulations.

Not determined.

SECTION 6

ACCIDENTAL RELEASE MEASURES

Spill control procedures (land): Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).

Spill control procedures

(water):

If a large spill occurs notify appropriate authorities (normally the National Response

Center or Coast Guard at 800-424-8802).

Waste disposal method:

Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

Other:

CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste

mixture will be regulated.



SECTION 7

HANDLING AND STORAGE

Handling procedures: Keep containers closed when not in use. Do not transfer to unmarked containers. Empty

containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation

centers for proper cleaning and reuse.

Handling temperatures should not exceed 60℃ (140℉) to min imize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory

protection. Wash thoroughly after handling.

Storage procedures: Store containers away from heat, sparks, open flame, or oxidizing materials. Extended

storage at excessive temperatures may produce odorous and toxic fumes from product

decomposition.

Additional information: No additional information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection: Applicable mainly to persons in repeated contact situations such as packaging of product,

service/maintenance, and cleanup/spill control personnel.

Respiratory protection: None required if ventilation is adequate. Otherwise a respiratory protection program

meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting

Eye protection: Eye protection is strongly recommended. Wear safety glasses with side shields or

vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

Hand protection: Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin

sensitization and absorption.

Other protection: Use of an apron and overboots of chemically impervious materials such as neoprene or

nitrile rubber is recommended based on level of activity and exposure. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.

Local control measures: Use adequate ventilation when working with material in an enclosed area. Mechanical

methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in

areas where this material is used and stored.

Other: Consumption of food and drink should be avoided in work areas where product is present.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, Purple Odor: None

Odor threshold:Not determined.pH:Not determined.Melting/Freezing point: -37° C (-34°F)Initial boiling point: 125° C (257°F)Boiling range:Not determined.

Flash point: 104℃ (219年) 100% Propylene Gycol

Evaporation rate:

Flammability:

Upper flammable limit:

Lower flammable limit:

Vapor pressure:

Vapor density:

Non-flammable

Non-flammable

Non-flammable

Non-flammable

Non-flammable

Non-flammable

Non-flammable

Non-flammable

Non-flammable

1.04 @ 20 °C

Not determined.

Relative density:

1.04 @ 15.6℃

Solubility: Miscible in water, negligible in most petroleum solvents.



Partition Coefficient: Not determined.

Auto-ignition temperature: Not determined.

Decomposition temperature: Not determined.

Viscosity: Not determined.

Other Not applicable.

SECTION 10 STABILITY AND REACTIVITY

Reactivity

Chemical stability: Material is chemically stable at room temperatures and pressure.

Hazardous polymerization: Will not occur.

Conditions to avoid: Avoid high temperatures and product contamination. **Incompatibility with other** Avoid contact with acids and strong oxidizing materials.

materials:

Decomposition products: Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete

Other: Not applicable.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute toxicity (LD50) *See note at the bottom of the section

Oral: >5000 mg/kg

Dermal: >5000 mg/kg

Inhalation: >20.0 mg/l

Skin irritation: Non-irritant

Eye irritation: Non-irritant

Dermal sensitization: Not expected to have a sensitizing effect. **Respiratory sensitization:** Not expected to have a sensitizing effect.

Aspiration Hazard: Not applicable

Chronic Toxicity

Mutagenicity: Not suspected of causing genetic defects

Carcinogenicity: Not suspected of causing cancer.

Reproductive toxicity: Not expected to have adverse effects on reproduction.

STOT-single exposure: Not expected to have adverse effects.

STOT-repeated exposure: Not expected to have long term adverse effects.

Other: *All data in this section is based off calculations from Part 3 of the Globally Harmonized

SECTION 12 ECOLOGICAL INFORMATION

Environmental toxicity

Fish: > 100 mg/l.
Invertebrates: > 100 mg/l.
Aquatic plants: > 100 mg/l.
Microorganism: > 100 mg/l.

Persistence/Degradability: This product is expected to be readily biodegradable.

Bioaccumulation: Not determined.

Mobility in soil: Not determined.

Other: All classifications are based on calculations in Part 4 of the Globally Harmonized System

of Classification and Labelling of Chemicals (GHS) utilizing information from the

constituent components.



SECTION 13

DISPOSAL CONSIDERATIONS

Waste disposal: This product unadulterated by other materials can be classified as a non-hazardous

waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management

should be in full compliance with federal, state, and local laws.

Other The transportation, storage, treatment and disposal of RCRA waste material must be

conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

SECTION 14 TRANSPORT INFORMATION

Land Transport (DOT): Not Regulated. **Proper Shipping Name:** Not Applicable. Land Transport (TDG): Not Regulated. **Proper Shipping Name:** Not Applicable. Not Regulated. Sea Transport (IMDG): **Proper Shipping Name:** Not Applicable. Not Regulated. Air Transport (IATA): Not Applicable. **Proper Shipping Name:** Not Applicable. Other:

SECTION 15

REGULATORY INFORMATION

Federal Regulation

Clean water act/oil: No components of this product are listed.

TSCA: All components of this material are listed in the U.S. TSCA Inventory.

Other TSCA: Not applicable.

SARA title III: Section 302/304 extremely hazardous substances:

None.

Section 311, 312 hazard categorization:

Acute (immediate health effects):

Chronic (delayed health effects):

NO
Fire (hazard):

NO
Reactivity (hazard):

NO
Pressure (sudden release hazard):

NO

Section 313 toxic chemicals:

Not Applicable.

For stationary/moving sources – reportable quantity (due to): None.

State Regulations

CERCLA:

Right-to-know Not determined.

Other: Releases may be reportable to the Nation Response Center under the Clean Water Act,

33 U.S.C. 1321(b)(3) and (5) - see head of Section 15. Failure to report may result in

substantial civil and criminal penalties.

Recommend contacting the local authorities in the event of any type of spill to determine

local reporting requirements and also to aid in the cleanup.



SECTION 16	OTHER INFORMATION		
	NFPA 704	NPCA-HMIS	KEY
HEALTH:	1	1	0 = Minimal
FIRE:	1	1	1 = Slight
REACTIVITY:	0	0	2 = Moderate
SPECIFIC HAZARD:	None	N/A	3 = Serious
PROTECTION INDEX:	N/A	В	4 = Severe
Version:	1		

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHOR'S KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments: None.