# **STIHL PLATINUM BAR & CHAIN OIL**

Packaged for Stihl Incorporated, 536 Viking Drive, Virginia Beach, VA 23452



# Safety Data Sheet Conforms to HCS 2012 (29 CFR 1910.1200)

# **Section 1. Identification**

Product identifier	
Product Name:	STIHL PLATINUM BAR & CHAIN OIL
Other names:	F-4
Part/Product Number(s):	0781-516-5001, <b>0781-516-5003</b> , <b>0781-516-5005</b> , <b>0781-516-5006</b> , <b>0781-516-5007</b> , <b>7010-871-181</b> , 7010-871-0211
Material Use:	Bar and chain oil, lubricant
Uses advised against:	Not for internal engine use.
Manufacturer:	Omni Specialty Packaging, LLC 10399 Hwy 1 South Shreveport, LA 71115 1-318-524-1100
Issuing date:	May 8, 2015
Revision date:	June 2, 2015
Revision number:	001
Company contact:	OMNI EHS Department; E-Mail: <u>sds@osp.cc;</u> Contact phone: 318-524-1100 (Monday-Friday, 8:00 AM – 4:00 PM, CST)
In case of emergency :	CHEMTREC: Within USA and Canada: 1 (800) 524-9300 (24/7) CHEMTREC Outside USA and Canada: +1 703-527-3887 (24/7

# Section 2. Hazards Identification

OSHA/HCS Status:	This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).			
GHS Classification of the Substance or Mixture:	Not classified			
GHS Label Elements				
Hazard pictograms:	None			
Signal word:	None			
Hazard statement:	None			
Precautionary statements				
General:	Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.			
Prevention:	Not applicable			
Response:	Not applicable			
Storage:	Not applicable			
Disposal:	Not applicable			
Hazards not otherwise classified (HNOC): Defatting to the skin.				

# Section 3. Composition/Information on Ingredients Petroleum mineral oil lubricant base stock with proprietary performance additives mixture.

Components Name	CAS number	Weight %*
Lubricant Base Oil (Petroleum) Highly refined mineral oils (C15-C50)	Various	95 – 99
Bar & Chain Oil Additive Mixture	Proprietary	1-5

This product does not contain known hazardous materials at the ≥ 1% level or known carcinogens at the ≥ 0.1% level as defined by 29 CFR 1910.1200.

\* The exact percentage of composition has been withheld as a trade secret.

escription of necessary fire	
General Advice:	No specific first aid measures are required. Get medical attention if irritation develops and persists.
Eye contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelid should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if irritation develops and persists.
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes an shoes. Get medical attention if irritation or allergic reaction develops and persists.
Inhalation:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. If inhaled, remove to fresh air. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion:	Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.
Protection of first-aiders:	No action shall be taken involving any personal risk or without suitable training. Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protectic clothing (see section 8).

See Section 11 for more detailed information on health effects and symptoms.

Most Important Symptoms and Effects:	Personnel with pre-existing skin disorders should avoid contact with this product. Under normal use conditions, no adverse effects to health are known.
Eye contact:	Not expected to cause prolonged or significant eye irritation.
Skin contact:	Contact with skin is not expected to cause prolonged or significant irritation. Contact with skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.
Inhalation:	Not expected to be harmful if inhaled. Contains petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficult breathing.
Ingestion:	Not expected to be harmful if swallowed.
Note to physician:	Treat symptomatically.

Section 5. Fire-Fightin Uniform Fire Code:	Class IIIB
Flash Point:	>93.3°C (>200°F)
Extinguishing Media	
Suitable Media:	In case of fire, use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water fog, alcohol resistant foam, dry chemical, carbol dioxide (CO2) extinguisher or spray.
Unsuitable Media:	CAUTION: Use of water spray when fighting fire may be inefficient.
Specific Hazards Arising from the Chemical:	Keep product and empty container away from heat and sources of ignition as product will burn. Contact with strong oxidizers may cause fire. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be contained, prevented from being discharged to any waterway, sewer or drain and disposed of in accordance with local regulations.
Hazardous Combustion Products:	Combustion products may include the following: Carbon dioxide (CO2) Carbon monoxide (CO), and Nitrogen oxides.
Protection of Fire Fighters:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

# Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Put on appropriate personal protective equipment (see Section 8). Floors may be slippery; use care to avoid falling.

MSHA/NIOSH (approved or equivalent) and full protective gear.

training. As in any fire, wear self-contained breathing apparatus pressure-demand,

- For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Ensure adequate ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. See also the information in "For non-emergency personnel".
- Environmental precautions: Avoid dispersal of spilled material onto soil or into waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). See Section 12 for ecological information.

## Methods and materials for containment and cleaning up

- Small Spills: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large Spills: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

NOTE: If RQ (Reportable Quantity) is exceeded or if spills enter a body of water, report immediately to the USEPA's National Response Center at (800) 424-8802. Check with your local and state regulators regarding their reporting requirements.

# Section 7. Handling and Storage Precautions for safe handling

Protective measures:	Safety glasses with side shields. Eye protection and face shield should be used if material is used under conditions that increase the chances of splattering. Put on appropriate personal protective equipment (see Section 8). Keep out of reach of children.
Advice on general	
occupational hygiene:	Do not get in eyes, on skin or on clothing. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas.
Conditions for safe storage,	See also Section 8 for additional information on hygiene measures.
Including any incompatibilities:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials, strong oxidizing agents (see Section 10) and food and drink. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination. Avoid contaminating soll or releases into sewage or drainage systems and bodies of water.
Bulk material handling:	Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient.

# **Section 8. Exposure Controls/Personal Protection**

Control parameters Occupational Exposure Limits

Chemical name	ACGIH		OSHA		NIOSH	
Chemical hame	TLV	STEL	PEL	STEL	TWA	Ceiling
Lubricant Base Oll (Petroleum) Highly refined mineral oils (C15-C50)	5 mg/m3 (mist)	10 mg/m3 (mist)	5 mg/m3 (mist)	-		-
Appropriate engineering controls:	Good general venti contaminants. Eme				r exposure	to airborne
Environmental exposure controls: ndividual protection measures	Emissions from ventilation or work process equipment should be checked to en they comply with the requirements of environmental protection legislation. In so cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		ion. In soi ess			
idividual protoction medsures						
Hygiene measures:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.					
Eye/Face Protection:	Wear safety glasses with side shields. A face shield may be necessary under some conditions.		under			
Skin and Body Protection	como contaniono.					
Hand protection:	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. Consult your supervis or Standard Operating Procedure (SOP) for special handling instructions.		supervisor			
Body protection:	No protective equip tasks, personal pro task being perform	tection equipme	ent for the bod			
Other skin protection:	Appropriate footwe selected based on					i be

**Respiratory protection:** 

No respiratory protection is normally required. If user operation generates an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from measured concentrations of this material. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

# Section 9. Physical and Chemical Properties

Appearance	(Typical or Target)
Physical State:	Liquid
Color:	Straw colored
Odor:	Petroleum like
Odor threshold:	Not available
pH:	Not applicable
Boiling Point:	Not available
Flash Point (Closed cup):	>93.3°C (>200°F) (Typical or Target)
Evaporation rate (Butyl acetate = 1):	Not available
Flammability (solid, gas):	Not applicable. Based on - Physical state
Flammable) Limit in Air	Not available
Vapor pressure:	Not available
Vapor density (Air = 1):	>1
Relative density:	0.90 - 0.92 g/l at 15°C (Typical or Target)
Solubility:	In soluble in water
Partition coefficient (n-Octanol/water):	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity - Kinematic (cSt (mm2/s)@ 40°C):	120 - 173
Viscosity - Kinematic (cSt (mm2/s) @ 100°C	:10 – 12.4
VOC %:	0 %

# Section 10. Stability and Reactivity

Reactivity:	Not reactive under normal storage conditions	
Chemical stability:	Stable under normal storage conditions	
Possibility of hazardous reactions:	None under normal processing.	
Hazardous polymerization:	Hazardous polymerization does not occur.	
Conditions to avoid:	Heat, flames and sparks.	
Incompatible materials:	Oxidizing agents and open flames.	
Hazardous decomposition products:	May include: Fumes, Oil vapors, Smoke, Carbon Oxides (including carbon monoxide and carbon dioxide), Aldehydes, Nitrogen oxides, and incomplete combustion products.	

# Section 11. Toxicological Information Information on toxicological effects

**Basis for Assessment:** Information given is based on product data, a knowledge of the components and the toxicity of similar products.

## Likely Routs of Exposure:

Exposure may occur via skin absorption, skin or eye contact, inhalation, ingestion.

### Substance/Mixture

Acute Toxicity	Oral LD50	Dermal LD50	Inhalation LC50
Lubricant Base Oil (Petroleum) Highly refined mineral oils (C15- C50) Mixture - Typical	>2000 mg/Kg (rat)	>2000 mg/Kg (rabbit)	>2.18 mg/L (rat) 4h (mist)

**Aspiration hazard:** 

Not expected to be an aspiration hazard.

## **STIHL PLATINUM BAR & CHAIN OIL**

Skin Corrosion/Irritation:	No known significant effects or critical hazards.
Serious Eye Damage/Irritation:	No known significant effects or critical hazards.
Skin Sensitization:	No known significant effects or critical hazards.
<b>Respiratory Sensitization:</b>	No known significant effects or critical hazards.
Specific Target Organ Toxicity (Single Exposure) - STOT-SE: Specific Target Organ Toxicity (Repeated Exposure) – STOT-RE:	No known significant effects or critical hazards. No known significant effects or critical hazards.
Carcinogenicity:	No known significant effects or critical hazards.
Germ Cell Mutagenicity:	No known significant effects or critical hazards.
Reproductive Toxicity	No known significant effects or critical hazards.

# Information on Toxicity Effects of Compounds

## Lubricant Base Mineral Oil (Petroleum)

Mineral oils are known to cause cancer because of carcinogenic components (e.g. Benzene). The lubricant base mineral oils in this product have been highly refined by a variety of processes including severe solvent extraction, severe hydro cracking or severe hydro treating to reduce aromatics and improve performance characteristics. The oils in the is product meets the IP-346 criteria of less than 3 percent PHA's and are not considered to be a carcinogen by the International Agency for Research on Cancer.

None of the oils in this product requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IRAC) as: carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

# Section 12. Ecological Information

The information is based on data available for the material, the components of the material, and similar materials.

Ecotoxicity: No testing has been performed by the manufacturer. Ecotoxicity hazard is based on an evaluation of data for the components or a similar material. Not expected to be harmful to aquatic organisms.

Mobility:	Base oil component – Low solubility and floats on water and is expected to migrate from water to land. Expected to partition to sediment and wastewater solids.	
Persistence and degradation Biodegradation:	The material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material.	
Bioaccumulative potential Bioaccumulation:	This product is not expected to bioaccumulate through food chain in the environment.	
Other adverse effects:	No known significant effects or critical hazards.	
Other ecological information:	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.	

# Section 13. Disposal Considerations

## Disposal recommendations based on material supplied.

<u>Waste treatment methods</u> :	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Consult the appropriate state, regional, or local regulations for additional requirements. The generation of waste should be avoided or minimized wherever possible.	
Product waste:	Significant quantities of waste product residues should not be disposed of via the sanitary sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-	

	recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Incineration or landfill should only be considered when recycling is not feasible. Oil collection services are available for used oil recycling.
Contaminated packaging:	Empty containers or liners may retain some product residues and could pose a potential fire and explosion hazard. Do not cut, puncture, or weld containers.
Other information:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport Information General information: Petroleum Lubricating oil - Not regulated.

	DOT Classification	IMDG	IATA
Bar & Chain Oil	Not Regulated	Not Regulated	Not Regulated

Special precautions for user: Transport within user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# Section 15. Regulatory Information United States Regulations

United States Inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304: No products were found.

SARA 311/312: Immediate (Ad	cute) Health Effects:	No
Delayed (Chronic) Health Effects:		No
Fire Hazard:		No
Sudden Release of Pressure Hazard:		No
Reactivity Haz	ard:	No
SARA 313:		
The following components on None	of this material are found on	the EPCRA 313 list:
Supplier notification:	This product does not co thresholds.	ntain any hazardous ingredients at or above regulated
CWA (Clean Water Act):	This product does not cor Water Act (40 CFR 122.2	tain any substances regulated as pollutants pursuant to the Clean 1 and 40 CFR 122.42)
CERCLA:		, does not contain any substances regulated as a hazardous prehensive Environmental Response Compensation and Liability Act
State Regulations		
Massachusetts:	None of the components	are at or above regulated thresholds.
New Jersey:		are at or above regulated thresholds.
Pennsylvania:		are at or above regulated thresholds.
California Proposition 65:	Contraction and the second	contains a chemical known to the State of California to cause cancer.
Canada		

Canada WHMIS Hazard Class: Not classified. This Product Is Not Controlled Under WHMIS (Canada)

## International Chemical Inventories:

All components comply with the following chemical inventory requirements: DSL (Canada)

# Section 16. Other Information

NFPA Rating:	Health Hazard – 1	Flammability – 1	Instability/Reactivity – 0
HMIS Rating:	Health Hazard – 1	Flammability – 1	Physical Hazards – 0

(NFPA & HMIS Hazard Rating Key: 0 - Minimum Hazard; 1 - Slight Hazard; 2 - Moderate Hazard; 3 - High Hazard; 4 - Extreme Hazard; \* - Chronic Hazard Indicator, & PPE - Personal Protective Equipment Index A to L. These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS or Hazardous Material Identification System).

## Key to abbreviations:

OSHA = Occupational Safety and Health Administration	LogPow = logarithm of the octanol/water partition coefficient
ACGIH= American Conference of Industrial Hygienists	OEL = Occupational Exposure Limit
ATE = Acute Toxicity Estimate	SDS = Safety Data Sheet
BCF = Bioconcentration Factor	STEL = Short term exposure Limit
CAS = Chemical Abstracts Service Registry Number	UN = United Nations
cSt = Centistroke (mm2/s)	UN Number = United Nations Number, a four digit number
GHS = Global Harmonized System of Classification and Labeling	assigned by the United Nations Committee of Experts on
Of Chemicals.	the Transportation of Dangerous Goods
IATA = International Air Transport Association	
IBC = Intermediate Bulk Container	
IMDG = International Maritime Dangerous Goods	

Prepared By: OMNI Specialty Packaging EH&S Department

Revision Date: June 2, 2015

Status: Final

Revision Note: Revision 001 of OSHA GHS SDS format.

Consumer Product Improvement Act of 2008, General Conformity Certification

For Consumer Product Packages: This product has been evaluated and is certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission. Where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No testing is required to certify compliance with the provisions. The date of the manufacturing is stamped on the product container.

## Disclaimer

All reasonably practicable steps have been taken to ensure the information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.

**End of Safety Data Sheet**