

Page: 1

| SAFETY DATA SHEET | Revision Date: 05/19/2017 |
|--|---------------------------|
| | Print Date: 5/24/2017 |
| | SDS Number: R0172013 |
| PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil | Version: 1.2 |
| 3080 | |

29 CFR 1910.1200 (OSHA HazCom 2012) SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

:

Product identifier

Trade name

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

| Details of the supplier of the safety data | Emergency telephone number |
|--|----------------------------------|
| sheet | 1-800-VALVOLINE (1-800-825-8654) |
| Valvoline LLC | |
| 100 Valvoline Way | Regulatory Information Number |
| Lexington, KY 40509 | 1-800-TEAMVAL |
| United States of America (USA) | |
| 1-800-TEAMVAL | Product Information |
| | 1-800-TEAMVAL |
| | |
| | |

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (%) |
|--|------------|---------------------|-------------------|
| Distillates (Petroleum), Hydrotreated Heavy Paraffinic | 64742-54-7 | Asp. Tox. 1; H304 | 36.003 |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | Asp. Tox. 1; H304 | 6.8809 |
| Benzenesulfonic acid, C10-60- alkyl derivs., sodium salts | 90194-32-4 | Eye Irrit. 2A; H319 | 6.2162 |



Revision Date: 05/19/2017

Print Date: 5/24/2017 SDS Number: R0172013

Version: 1.2

3080

| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | 64742-65-0 | Asp. Tox. 1; H304 | 1.8862 |
|---|------------|-------------------|--------|
|---|------------|-------------------|--------|

SECTION 4. FIRST AID MEASURES

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

SAFETY DATA SHEET

| General advice | : | No hazards which require special first aid measures. |
|---|---|--|
| If inhaled | : | If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. |
| In case of skin contact | : | First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. |
| In case of eye contact | : | Remove contact lenses. Protect unharmed eye. |
| If swallowed | : | Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : | Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. |
| | | Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) |
| Notes to physician | : | No hazards which require special first aid measures. |

SECTION 5. FIREFIGHTING MEASURES



| SAFETY DATA SHEET | Revision Date: 05/19/201 |
|--|--------------------------|
| | Print Date: 5/24/201 |
| | SDS Number: R017201 |
| PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil | Version: 1 |
| 3080 | |

| Suitable extinguishing media | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical |
|---|---|---|
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | carbon dioxide and carbon monoxide Hydrocarbons |
| Specific extinguishing methods | : | |
| | | Product is compatible with standard fire-fighting agents. |
| Further information | : | Standard procedure for chemical fires. |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protective equipment and emergency procedures | : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
|---|---|
| Environmental precautions | : Prevent further leakage or spillage if safe to do so. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. |
| Other information | : Comply with all applicable federal, state, and local regulations. |

SECTION 7. HANDLING AND STORAGE

| Advice on safe handling | Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. |
|-------------------------|--|
| Materials to avoid | : No materials to be especially mentioned. |



| SAFETY DATA SHEET | Revision Date: 05/19/2017 |
|--|---------------------------|
| | Print Date: 5/24/2017 |
| | SDS Number: R0172013 |
| PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil | Version: 1.2 |
| 3080 | |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| Components with workplace control parameters | | | | |
|--|------------|-------------------------------------|---|-----------|
| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE | 64742-55-8 | TWA | 5 mg/m3 Mist | OSHA Z-1 |
| | | TWA | 5 mg/m3 Inhalable fraction | ACGIH |
| | | TWA | 5 mg/m3 Mist | OSHA P0 |
| | | TWA | 5 mg/m3 Mist | NIOSH REL |
| | | ST | 10 mg/m3 Mist | NIOSH REL |
| | | PEL | 5 mg/m3 particulate | CAL PEL |

Components with workplace control parameters

Hazardous components without workplace control parameters

| Components | CAS-No. |
|-------------------------------|--|
| Engineering measures | : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects. |
| Personal protective equipment | |
| Respiratory protection : | No personal respiratory protective equipment normally required. |
| Eye protection : | Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes. |
| Skin and body protection : | Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier). |
| Hygiene measures : | General industrial hygiene practice. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES



SAFETY DATA SHEET

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Revision Date: 05/19/2017

Print Date: 5/24/2017 SDS Number: R0172013

Version: 1.2

3080

| Physical state | : | liquid |
|---|---|---|
| Odour | : | No data available |
| Odour Threshold | : | No data available |
| рН | : | No data available |
| Melting point/freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flash point | : | > 390 °F / > 199 °C Method: Cleveland open cup |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit Lower explosion limit Vapour pressure | : | Calculated Explosive Limit |
| Relative vapour density | : | No data available |
| Relative density | : | 0.876 (15.6 °C) |
| Density | : | 0.8599 g/cm3 (15.6 °C) |
| Solubility(ies) Water solubility | : | No data available |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n- octanol/water | : | No data available |
| Thermal decomposition | : | |
| | | No data available |
| Viscosity Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | 63 mm2/s (40 °C) |



SAFETY DATA SHEET Revision Date: 05/19/2017 Print Date: 5/24/2017 SDS Number: R0172013 PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil Version: 1.2 3080

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

| Reactivity | : No decomposition if stored and applied as directed. |
|------------------------------------|---|
| Chemical stability | : Stable under recommended storage conditions. |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization. |
| Conditions to avoid | : excessive heat |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | carbon dioxide and carbon monoxide Hydrocarbons |

SECTION 11. TOXICOLOGICAL INFORMATION

| Information on likely routes of exposure | : Inhalation Skin contact Eye Contact Ingestion |
|---|--|
| Acute toxicity Not classified based on availab <u>Components:</u> Distillates (Petroleum), Hydrotre Acute oral toxicity | |
| Acute dermal toxicity | : LD50 (Rabbit): > 5 g/kg |
| DISTILLATES (PETROLEUM), Acute oral toxicity | SOLVENT-DEWAXED HEAVY PARAFFINIC: : LD50 (Rat): > 5,000 mg/kg |
| Acute dermal toxicity | : LD50 (Rabbit): > 5,000 mg/kg |
| Skin corrosion/irritation Not classified based on availab <u>Components:</u> Distillates (Petroleum), Hydrotro Result: Slight, transient irritation | eated Heavy Paraffinic: |

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:



SAFETY DATA SHEETRevision Date: 05/19/2017Print Date: 5/24/2017Print Date: 5/24/2017SDS Number: R0172013SDS Number: R0172013PREMIUM CONVENTIONAL SAE 5W-30 Motor OilVersion: 1.230803080

Result: Slight, transient irritation

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts: Result: No skin irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information. **Product:** Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Result: No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: Result: Slight, transient irritation

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts: Result: Irritating to eyes.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. **Reproductive toxicity** Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. Product: No aspiration toxicity classification **Components:**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: May be fatal if swallowed and enters airways.

Page: 8



| SAFETY DATA SHEET | Revision Date: 05/19/2017 |
|--|---------------------------|
| | Print Date: 5/24/2017 |
| | SDS Number: R0172013 |
| PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil | Version: 1.2 |
| 3080 | |

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: May be fatal if swallowed and enters airways.

Further information Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

| Ecotoxicity <u>Product:</u> Ecotoxicology Assessment Acute aquatic toxicity | : | Not classified based on available information. |
|---|---|--|
| Chronic aquatic toxicity | : | Not classified based on available information. |
| <u>Components:</u> Distillates (Petroleum), Hydroti Toxicity to fish | | ted Heavy Paraffinic : LL50 (Fish): > 100 mg/l |
| Toxicity to daphnia and other aquatic invertebrates | : | EL50 (Aquatic invertebrates): > 10,000 mg/l |
| Toxicity to algae | : | EL50 (Algae, algal mat (Algae)): > 100 mg/l |
| Toxicity to fish (Chronic toxicity) | : | NOEC (Fish): 10 mg/l |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Aquatic invertebrates): 10 mg/l |
| Persistence and degradabilit <u>Components:</u> No data available Bioaccumulative potential <u>Components:</u> No data available Mobility in soil <u>Components:</u> No data available Other adverse effects No data available <u>Product:</u> Additional ecological information | - | No data available |

Components:

SECTION 13. DISPOSAL CONSIDERATIONS



SAFETY DATA SHEETRevision Date: 05/19/2017Print Date: 5/24/2017Print Date: 5/24/2017SDS Number: R0172013SDS Number: R0172013PREMIUM CONVENTIONAL SAE 5W-30 Motor OilVersion: 1.2308030803080

| Disposal methods | |
|------------------------|--|
| General advice | : Dispose of in accordance with all applicable local, state and federal regulations. |
| Contaminated packaging | : Empty remaining contents. |

SECTION 14. TRANSPORT INFORMATION

International transport regulations

| REGULATION | | | | | |
|------------|----------------------|---------|------------|---------|-------------|
| ID NUMBER | PROPER SHIPPING NAME | *HAZARD | SUBSIDIARY | PACKING | MARINE |
| | | CLASS | HAZARDS | GROUP | POLLUTANT / |
| | | | | | LTD. QTY. |

U.S. DOT - ROAD

| Not dangerous goods |
|---------------------|
| |

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods



| SAFETY DATA SHEET | Revision Date: 05/19/2017 |
|--|---------------------------|
| | Print Date: 5/24/2017 |
| | SDS Number: R0172013 |
| PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil | Version: 1.2 |
| 3080 | |

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

| EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity This material does not contain any components with a CERCLA RQ. SARA 304 Extremely Hazardous Substances Reportable Quantity This material does not contain any components with a section 304 EHS RQ. | | | | |
|--|-----|---|--|--|
| SARA 311/312 Hazards | : N | lo SARA Hazards | | |
| SARA 313 | k | This material does not contain any chemical components with nown CAS numbers that exceed the threshold (De Minimis) eporting levels established by SARA Title III, Section 313. | | |
| California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment. | | | | |
| The components of this product are reported in the following inventories: DSL : All components of this product are on the Canadian DSL | | | | |
| AICS | | On the inventory, or in compliance with the inventory | | |
| KECI | | On the inventory, or in compliance with the inventory | | |
| REGI | . C | on the inventory, or in compliance with the inventory | | |
| IECSC | : q | (quantity restricted) | | |
| PICCS : On the inventory, or in compliance with the inventory | | | | |
| TSCA : On TSCA Inventory | | | | |

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

| SAFETY DATA SHEET | Revision Date: 05/19/2017 |
|--|---------------------------|
| | Print Date: 5/24/2017 |
| | SDS Number: R0172013 |
| PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil | Version: 1.2 |
| 3080 | |

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/19/2017



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements

| H304 | May be fatal if swallowed and enters airways. |
|------|---|
| H319 | Causes serious eye irritation. |

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index



Revision Date: 05/19/2017

PREMIUM CONVENTIONAL SAE 5W-30 Motor Oil

Version: 1.2

3080

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

SAFETY DATA SHEET

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LČxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System