

Safety Data Sheet

according to OSHA Hazard Communication
29 CFR Part 1910.1200



SECTION 1. Identification

SDS Product #: 99018MS10000810

Product Name: Mineral Spirits 66 1Percent

Supplied by: RelaDyne, LLC
8280 Montgomery Road, Suite 101
Cincinnati, OH 45236
888-830-3156
www.reladyne.com

24 Hour Emergency:
INFOTRAC: 1-800-535-5053

Outside U.S. and Canada
Infotrac: 352-323-3500

NOTE: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

SECTION 2. Hazard(s) Identification

*** EMERGENCY OVERVIEW ***: Flammable liquid and vapor. May be fatal if inhaled. May be fatal if swallowed.

GHS Classification

Asp. Tox. 1, Eye Irrit. 2B, Flam. Liq. 3, STOT SE 3 NE, Skin Irrit. 2

Symbol(s) of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

| | | |
|---------------------------------------|------|---|
| Flammable Liquid, category 3 | H226 | Flammable liquid and vapor. |
| Aspiration Hazard, category 1 | H304 | May be fatal if swallowed and enters airways. |
| Skin Irritation, category 2 | H315 | Causes skin irritation. |
| STOT, single exposure, category 3, NE | H336 | May cause drowsiness or dizziness. |
| Eye Irritation, category 2B | H320 | Causes eye irritation |

GHS PRECAUTIONARY STATEMENTS

| | |
|----------------|---|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray. |
| P264 | Wash thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician |
| P302+P352 | IF ON SKIN: Wash with plenty of water |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |

| | |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312 | Call a POISON CENTER/doctor/physician if you feel unwell. |
| P321 | Specific treatment (see first aid section on this label). |
| P331 | Do NOT induce vomiting. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P370+P378 | In case of fire: Use appropriate method to extinguish. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |

SECTION 3. Composition/Information on Ingredients

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|-----------------------|----------------|--------------|--------------------|-----------------------|
| Aliphatic hydrocarbon | 64742-47-8 | 75-100 | GHS02-GHS07-GHS08 | H226-304-315-320-336 |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

SECTION 4. First-Aid Measures



FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID - INGESTION: Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

SECTION 5. Fire-Fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid and vapor. Can form explosive mixtures at temperatures at or above the flashpoint. Vapors/dust may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Evacuate all unnecessary personnel. Shut down motors, pumps, electrical service and eliminate all sources of ignition. Avoid use of solid water streams. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 7. Handling and Storage



HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Use explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

SECTION 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u> | <u>ACGIH TLV-TWA</u> | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u> | <u>OSHA PEL-CEILING</u> |
|-----------------------|----------------------|-----------------------|---------------------|-------------------------|
| Aliphatic hydrocarbon | 100 ppm | N.D. | 500 ppm | N.D. |

Personal Protection



RESPIRATORY PROTECTION: Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.



SKIN PROTECTION: Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.



EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.



OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

SECTION 9. Physical and Chemical Properties

| | | | |
|-----------------------------------|---------------------------|---------------------------------|-----------|
| Appearance: | Clear, transparent liquid | Physical State: | Liquid |
| Odor: | Typical | Odor Threshold: | N.D. |
| Density, g/cm³: | 0.782 | pH: | N.D. |
| Freeze Point, °F: | N.D. | Viscosity: | N.D. |
| Solubility in Water: | Insoluble | Explosive Limits, vol%: | 0.8 - 6.0 |
| Boiling Range, °F: | 318 - 386 | Flash Point, °F: | 104 |
| Evaporation Rate: | 0.21 (n-butyl acetate=1) | Auto-ignition Temp., °F: | N.D. |
| Vapor Density: | 5 (air=1) | Vapor Pressure: | N.D. |

(See "Other information" Section for abbreviation legend)

SECTION 10. Stability and Reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Keep separate from alkalis. Prevent contact with strong oxidizing agents. Keep away from acids.

HAZARDOUS DECOMPOSITION PRODUCTS: During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

HAZARDOUS POLYMERIZATION: No Information

SECTION 11. Toxicological Information



Information on Toxicological Effects

EFFECTS OF OVEREXPOSURE - INHALATION: Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression).

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Contact with skin may cause mild irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. Harmful or fatal if liquid is aspirated into lungs. Irritating to mouth, throat, and stomach. Can be readily absorbed by the stomach and intestinal tract. Symptoms include burning sensation of the mouth and esophagus, nausea, vomiting, diarrhea, dizziness, staggering gait, drowsiness, loss of consciousness and delirium as well as additional central nervous system effects.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Possible brain damage from overexposure. Overexposure may cause nervous system damage. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Name according to EEC</u> | <u>Oral LD50, mg/kg</u> | <u>Dermal LD50, mg/kg</u> | <u>Vapor LC50, mg/L</u> |
|----------------|------------------------------|-------------------------|---------------------------|-------------------------|
| 64742-47-8 | Aliphatic hydrocarbon | >5,000 | >2,000 | >20.0 |

SECTION 12. Ecological Information

ECOLOGICAL INFORMATION: No Information

SECTION 13. Disposal Considerations



For more guidance and information contact our Waste Services Division at (262) 658-4000.

Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 14. Transport Information

DOT Proper Shipping Name:

Petroleum distillates, n.o.s. (naphtha solvent) - Combustible Liquid

Packing Group:

III

DOT Hazard Class:

No Information

Hazard SubClass:

No Information

DOT UN/NA Number:

UN1268

Resp. Guide Page:

128

SECTION 15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class:

No Information

SECTION 16. Other Information

Revision Date: 4/06/2017 Supersedes Date: 3/13/2015

Datasheet produced by: EH&S - Regulatory Department

HMIS Ratings:

| | | | | | | | |
|---------|---|---------------|---|-------------|---|----------------------|---|
| Health: | 1 | Flammability: | 2 | Reactivity: | 0 | Personal Protection: | X |
|---------|---|---------------|---|-------------|---|----------------------|---|

Volatile Organic Compounds, gr/ltr: 100

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/ REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H320 Causes eye irritation
H336 May cause drowsiness or dizziness.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

This Safety Data Sheet is prepared according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. The information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.