

SAFETY DATA SHEET



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

SECTION 1. IDENTIFICATION

Product name : MM AIRBRAKE SYSTEM ANTIFREEZE 4/1GA
Product code : M2834

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : Anti-freezing agents
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2
Acute toxicity (Oral) : Category 3
Acute toxicity (Inhalation) : Category 3
Acute toxicity (Dermal) : Category 3
Specific target organ toxicity - single exposure : Category 1 (Central nervous system, Eyes)

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to organs (Central nervous system, Eyes).

Precautionary statements
Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
IF exposed: Call a POISON CENTER or doctor/ physician. Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Methanol	67-56-1	>= 90 - < 100

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

SAFETY DATA SHEET



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Call a physician or poison control centre immediately.
If on skin, rinse well with water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Get medical attention immediately.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to organs.
This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO2)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides

MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/04/2019	600000001949	Date of first issue: 09/04/2019

- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.

MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
 Date of first issue: 09/04/2019

Do not breathe vapours/dust.
 Do not smoke.
 Take precautionary measures against static discharges.
 Dispose of rinse water in accordance with local and national regulations.
 Container hazardous when empty.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if

MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/04/2019	600000001949	Date of first issue: 09/04/2019

applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes
Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: blue
Odour	: pungent
Odour Threshold	: not determined
pH	: not determined
Melting point/freezing point	: not determined
Boiling point/boiling range	: 64.7 °C (1013.250 hPa) Value for Component
Flash point	: 12 °C Method: closed cup Value for Component
Evaporation rate	: not determined
Flammability (solid, gas)	: No data available

SAFETY DATA SHEET



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

Self-ignition : not determined

Upper explosion limit / Upper flammability limit : not determined

Lower explosion limit / Lower flammability limit : not determined

Vapour pressure : not determined

Relative vapour density : not determined

Density : 0.7922 g/cm³

Solubility(ies)
Water solubility : completely miscible

Partition coefficient: n-octanol/water : not determined

Decomposition temperature : not determined

Viscosity
Viscosity, dynamic : not determined
Viscosity, kinematic : not determined

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products :

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Eye contact
Skin contact
Ingestion

MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled.

Product:

- Acute oral toxicity : Acute toxicity estimate: 100.15 mg/kg
Method: Calculation method
- Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: 300.45 mg/kg
Method: Calculation method

Components:**Methanol:**

- Acute oral toxicity : LDLo (Humans): 300 mg/kg
Assessment: The component/mixture is toxic after single ingestion.
- Acute inhalation toxicity : Test atmosphere: dust/mist
Assessment: The component/mixture is toxic after short term inhalation.
- Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg
Assessment: The component/mixture is toxic after single contact with skin.

Skin corrosion/irritation

Not classified based on available information.

Components:**Methanol:**

Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:**Methanol:**

Species: Rabbit
Result: Possibly irritating to eyes

MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Methanol:

Test Type: Maximisation Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Causes damage to organs (Central nervous system, Eyes).

Components:

Methanol:

Target Organs: Central nervous system, Eyes
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SAFETY DATA SHEET



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1230
Proper shipping name : Methanol
Class : 3
Subsidiary risk : 6.1
Packing group : II
Labels : 3 (6.1)
Packing instruction (cargo aircraft) : 364

IMDG-Code

UN number : UN 1230
Proper shipping name : METHANOL
Class : 3
Subsidiary risk : 6.1
Packing group : II
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

SAFETY DATA SHEET




MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019 SDS Number: 600000001949 Date of last issue: -
Date of first issue: 09/04/2019

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 09/04/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN