



SAFETY DATA SHEET

SDS ID NO.: 0120SPE012

Revision date 05/01/2020

1. IDENTIFICATION

Product Name Speedway 2-Cycle Engine Oil

Synonym Marine-Terrain 2-Cycle Engine Oil; Marine Terrain TC-W3; Marathon 2 Cycle Oil
Product code 0120SPE012
Chemical family Motor/Lube Oil

Recommended use Engine Oil.
Restrictions on use All others.

Manufacturer, Importer, or Responsible Party Name and Address
Speedway LLC
P.O. Box 1500
Enon, OH 45501

SDS Information 1-937-863-7727

24 Hour Emergency Telephone CHEMTREC: 1-800-424-9300

2. HAZARD IDENTIFICATION

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification

Chronic aquatic toxicity	Category 3
--------------------------	------------

Hazards Not Otherwise Classified (HNOC)

Not applicable

Label Elements

Harmful to aquatic life with long lasting effects

Appearance Blue Liquid	Physical State Liquid	Odor Petroleum
-------------------------------	------------------------------	-----------------------

Precautionary Statements - Prevention

Avoid release to the environment

Precautionary Statements - Response

Not applicable

Precautionary Statements - Storage

Not applicable

Precautionary Statements - Disposal

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Information

Name	CAS Number	% Concentration
Distillates (petroleum), hydrotreated light	64742-47-8	10-30
White Mineral Oil	8042-47-5	1-5

All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First aid measures

General advice	In case of accident or if you feel unwell, seek medical advice immediately (show directions for use or safety data sheet if possible).
Inhalation	Remove to fresh air and keep at rest in a position comfortable for breathing. If symptoms occur get medical attention.
Skin contact	Wash skin with plenty of soap and water. If irritation or other symptoms occur get medical attention. Wash contaminated clothing and clean shoes before reuse.
Eye contact	Immediately flush eyes with plenty of water. Eyelids should be held away from the eyeball to ensure thorough rinsing. Gently remove contacts while flushing. Get medical attention if irritation persists.
Ingestion	Rinse mouth out with water. If spontaneous vomiting occurs, keep head below hips, or if patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. Never give anything by mouth to an unconscious person. Keep affected person warm and at rest. If symptoms develop, seek medical attention.

Most important signs and symptoms, both short-term and delayed with overexposure

Adverse effects Prolonged or repeated exposure may cause dermatitis, folliculitis or oil acne.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	For small fires, Class B fire extinguishing media such as CO ₂ , dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	The product is not combustible per the OSHA Hazard Communication Standard, but will ignite and burn at temperatures exceeding the flash point.
Hazardous combustion products	Smoke, carbon monoxide, and other products of incomplete combustion.
Explosion data	
Sensitivity to mechanical impact:	No.
Sensitivity to static discharge:	No.
Special protective equipment and	Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied

precautions for firefighters	carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as possible. Keep run-off water out of sewers and water sources.			
Additional firefighting tactics	Not applicable			
NFPA	Health 1	Flammability 1	Instability 0	Special Hazard -

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Keep public away. Isolate and evacuate area. Shut off source if safe to do so.
Protective equipment	Use personal protection measures as recommended in Section 8.
Emergency procedures	Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate.
Environmental precautions	Avoid release to the environment. Avoid subsoil penetration. Do not allow material to contaminate ground water system.
Methods and materials for containment	Prevent further leakage or spillage if safe to do so. Prevent spilled material from entering storm drains, sewers, and open waterways.
Methods and materials for cleaning up	Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids. Recover and return free product to proper containers.

7. HANDLING AND STORAGE

Safe handling precautions	<p>Avoid contact with skin, eyes and clothing. Do not swallow. Avoid breathing vapors or mists. Use good personal hygiene practices. Wash thoroughly after handling. Use personal protection measures as recommended in Section 8. Do not cut, drill, grind or weld on empty containers since explosive residues may remain. Refer to applicable EPA, OSHA, NFPA and consistent state and local requirements.</p> <p>Lifetime, continuous skin contact with used motor oils has caused skin cancer in laboratory tests. In testing, thorough washing has been found to prevent the development of skin cancer from used motor oil exposure. Avoid excessive skin contact. Exercise good personal hygiene including the removal and washing of soiled clothing and destroy used motor oil contaminated leather shoes/boots.</p>
Storage conditions	Store in properly closed containers that are appropriately labeled and in a cool, well-ventilated area. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from incompatible materials.
Incompatible materials	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Name	ACGIH TLV	OSHA PELS	NIOSH IDLH
Distillates (petroleum), hydrotreated light 64742-47-8	200 mg/m ³ TWA (total hydrocarbon vapor) Skin - potential significant contribution to overall exposure by the cutaneous route	-	-
White Mineral Oil 8042-47-5	Oil Mist 5 mg/m ³ TWA	Oil Mist TWA: 5 mg/m ³	2500 mg/m ³

Notes: No further information available.

Engineering measures	Local or general exhaust required when using at elevated temperatures that generate vapors or mists.
<u>Personal protective equipment</u>	
Eye protection	Use goggles or face-shield if the potential for splashing exists.
Skin and body protection	Use nitrile rubber, Viton® or PVA gloves for repeated or prolonged skin exposure. Glove suitability is based on workplace conditions and usage. Contact the glove manufacturer for specific advice on glove selection and breakthrough times. Wear appropriate protective clothing.
Respiratory protection	Use a NIOSH approved organic vapor chemical cartridge or supplied air respirators when there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should be used for fire fighting.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Blue Liquid
Physical State	Liquid
Color	Blue
Odor	Petroleum
Odor Threshold	No data available.

<u>Property</u>	<u>Values (method)</u>
pH	No available data.
Melting Point / Freezing Point	No data available.
Initial Boiling Point / Boiling Range	No data available.
Flash Point	> 98 °C / > 208.4 °F (ASTM D93)
Evaporation Rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammability Limit in Air (%):	
Upper Flammability Limit:	No data available.
Lower Flammability Limit:	No data available.
Explosion Limits	No data available.
Vapor Pressure	No data available.
Vapor Density	No data available.
Specific Gravity / Relative Density	0.86
Water Solubility	No data available.
Partition Coefficient	No data available.
Autoignition Temperature	No data available.
Decomposition Temperature	No data available.
Kinematic Viscosity	42.23 cSt @ 40°C (ASTM D445)
VOC Content (%)	No data available.

10. STABILITY AND REACTIVITY

Reactivity	The product is non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.

Hazardous polymerization	Will not occur.
Conditions to avoid	Sources of heat or ignition.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation	Overheating may produce vapors which may cause respiratory irritation, dizziness and nausea.
Eye contact	Exposure to vapor or contact with liquid may cause mild eye irritation, including tearing, stinging, and redness.
Skin contact	Prolonged or repeated contact may dry skin and cause irritation.
Ingestion	May cause irritation of the mouth, throat and gastrointestinal tract.

Acute toxicological data

Name	Oral LD50	Dermal LD50	Inhalation LC50
Distillates (petroleum), hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
White Mineral Oil 8042-47-5	> 5000 mg/kg (Rat)	-	> 2062 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

This product is considered to have a low order of acute and chronic toxicity under normal use and storage conditions

USED MOTOR OIL: Lifetime, continuous skin contact with used motor oils has caused skin cancer in laboratory tests. The combustion process produces compounds (polycyclic aromatic hydrocarbons) in motor oils that increase with use and are responsible for the cancer induction. Thorough washing has been found to prevent the development of skin cancer on animals from used motor oil exposure.

Adverse effects related to the physical, chemical and toxicological characteristics

Signs and symptoms	Prolonged or repeated exposure may cause dermatitis, folliculitis or oil acne.
Acute toxicity	None known.
Skin corrosion/irritation	None known.
Serious eye damage/eye irritation	None known.
Sensitization	None known.
Mutagenic effects	None known.
Carcinogenicity	None known.
Reproductive toxicity	None known.
Specific Target Organ Toxicity (STOT) - single exposure	None known.

Specific Target Organ Toxicity (STOT) - repeated exposure None known.

Aspiration hazard None known.

12. ECOLOGICAL INFORMATION

Ecotoxicity This product should be considered harmful to aquatic organisms, with the potential to cause long lasting adverse effects in the aquatic environment. Used motor and/or lube oils can be toxic to birds and fish.

Name	Fish	Crustacea	Algae/aquatic plants
Distillates (petroleum), hydrotreated light 64742-47-8	96-hr LC50 = 2.2 mg/l Bluegill	-	-
White Mineral Oil 8042-47-5	96-hr LC50 > 1000 mg/L Bluegill	-	-

Persistence and degradability Expected to be inherently biodegradable.

Bioaccumulation Has the potential to bioaccumulate.

Mobility in soil No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Description of waste residues No information available.

Safe handling of wastes Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required.

Disposal of wastes / methods of disposal The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Contaminated packaging disposal Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

UN/Identification No:	Not applicable
UN Proper Shipping Name:	Not Regulated
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

IATA

UN/Identification No:	Not applicable
UN Proper Shipping Name:	Not Regulated
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

IMDG

UN/Identification No:	Not applicable
UN Proper Shipping Name:	Not Regulated
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable
Marine Pollutant:	No

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. REGULATORY INFORMATION**Regulatory Information****US TSCA Chemical Inventory**

This product and/or its components are listed on the TSCA Chemical Inventory or are exempt.

Canada DSL/NDSL Inventory

This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.

EPA Superfund Amendment & Reauthorization Act (SARA)**SARA Section 302**

This product does not contain any component(s) included on EPA's Extremely Hazardous Substance (EHS) List above the de minimis threshold.

SARA Section 304

This product does not contain any component(s) identified as an EHS or a CERCLA Hazardous substance above the de minimis threshold.

SARA Section 311/312

The following EPA hazard categories apply to this product:

None

SARA Section 313

This product does not contain components subject to the reporting requirements of SARA Title III Section 313 Toxic Release Inventory Reporting (Form R) above the de minimis threshold.

U.S. State Regulations**California Proposition 65**

This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.


For more information, go to www.P65Warnings.ca.gov.**State Right-To-Know Regulations** The following component(s) of this material are identified on the regulatory lists below:

Name	New Jersey Right-To-Know	Pennsylvania Right-To-Know	Massachusetts Right-To-Know
Motor Oil MIXTURE	Listed	Not Listed	Not Listed
White Mineral Oil 8042-47-5	Listed	Listed	Listed

16. OTHER INFORMATION**Prepared by**

Toxicology & Product Safety

NFPA

**Revision Notes**

Revision date 05/01/2020
Previous publish date 11/21/2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.