



1. Identification

Product identifier

Product Name EVERCOAT Z-GRIP

Other means of identification

Product Code 100280_100282_100284_100285_800282

UN number or ID number UN3269

Recommended use of the chemical and restrictions on use

Recommended Use Lightweight body filler. Exclusively for Automotive Repair. For professional users only.

Restrictions on use Uses other than recommended use.

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Evercoat
A division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, OH 45242 USA
513-489-7600

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address Info@evercoat.com

Emergency telephone number

Company Phone Number +1 (513) 489-7600 or (800) 729-7600

24 Hour Emergency Phone Number CHEMTREC: 1-800-424-9300 or 1-703-527-3887.

2. Hazard(s) identification

Classification of the substance or mixture

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Category 3 Target organ effects: Respiratory irritation.	
Specific target organ toxicity (repeated exposure)	Category 1

Label elements



Danger

Hazard statements

Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Use explosion-proof electrical, ventilating and lighting equipment.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection and face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Do not breathe dust.
Do not eat, drink or smoke when using this product.
Ground and bond container and receiving equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Use explosion-proof electrical, ventilating and lighting equipment.
Keep cool.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice and attention.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
If skin irritation occurs: Get medical advice and attention.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor if you feel unwell.

Fire

In case of fire: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available.

Other Information

No information available.

3. Composition/information on ingredients**Substance**

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Styrene	100-42-5	10-30%	-	-
Talc (hydrous magnesium silicate)	14807-96-6	10-30%	-	-
Ground Limestone (Calcium Carbonate)	1317-65-3	10-30%	-	-
Magnesite	546-93-0	5-10%	-	-
Crystalline Silica (Quartz)	14808-60-7	0.1-1%	-	-

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures**Description of first aid measures**

General advice	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation.
Effects of Exposure	May cause cancer. May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. Causes damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label
--------------------------------	---

instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Styrene 100-42-5	TWA: 10 ppm STEL: 20 ppm pOt	TWA: 100 ppm (vacated) TWA: 50 ppm	TWA: 50 ppm; TWA: 215 mg/m ³ ; STEL: 100 ppm STEL: 425 mg/m ³ IDLH: 700 ppm
Talc (hydrous magnesium silicate) 14807-96-6	TWA: 2 mg/m ³ respirable particulate matter particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	TWA: 2 mg/m ³ ; containing no Asbestos and <1% Quartz respirable dust IDLH: 1000 mg/m ³
Ground Limestone (Calcium Carbonate) 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ ; total dust TWA: 5 mg/m ³ ; respirable dust
Magnesite 546-93-0	-	-	TWA: 10 mg/m ³ ; total dust TWA: 5 mg/m ³ ; respirable dust
Crystalline Silica (Quartz) 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	TWA: 0.05 mg/m ³ ; respirable dust IDLH: 50 mg/m ³ respirable dust

Chemical name	Alberta	British Columbia	Ontario	Quebec
Styrene 100-42-5	TWA: 20 ppm; TWA: 85 mg/m ³ ;	TWA: 20 ppm; STEL: 40 ppm;	TWA: 35 ppm; STEL: 100 ppm;	TWAEV: 50 mg/m ³ ; STEV: 75 ppm;

	STEL: 40 ppm; STEL: 170 mg/m ³ ;			
Talc (hydrous magnesium silicate) 14807-96-6	TWA: 2 mg/m ³ ; respirable particulate	TWA: 2 mg/m ³ ; respirable particulate	TWA: 2 mg/m ³ ; respirable fraction	TWAEV: 2 mg/m ³ ; respirable dust
Ground Limestone (Calcium Carbonate) 1317-65-3	TWA: 10 mg/m ³ ;	TWA: 10 mg/m ³ ; total dust TWA: 3 mg/m ³ ; respirable fraction STEL: 20 mg/m ³ ;	-	TWAEV: 10 mg/m ³ ; total dust
Magnesite 546-93-0	-	TWA: 10 mg/m ³ ; total dust TWA: 3 mg/m ³ ; respirable fraction	-	TWAEV: 10 mg/m ³ ; total dust
Crystalline Silica (Quartz) 14808-60-7	TWA: 0.025 mg/m ³ ; respirable particulate	TWA: 0.025 mg/m ³ ; respirable	TWA: 0.10 mg/m ³ ; respirable fraction	TWAEV: 0.05 mg/m ³ ; respirable dust

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Styrene	TWA: 10 ppm; STEL: 20 ppm;	TWA: 20 ppm; STEL: 40 ppm;	TWA: 10 ppm; STEL: 20 ppm;	TWA: 10 ppm; STEL: 20 ppm;
Talc (hydrous magnesium silicate)	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter
Crystalline Silica (Quartz)	TWA: 0.025 mg/m ³ ; respirable particulate matter	TWA: 0.025 mg/m ³ ; respirable fraction	TWA: 0.025 mg/m ³ ; respirable particulate matter	TWA: 0.025 mg/m ³ ; respirable particulate matter

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Styrene	TWA: 20 ppm; STEL: 40 ppm; Designated substance	TWA: 10 ppm; STEL: 20 ppm;	TWA: 20 ppm; STEL: 40 ppm; Designated Chemical Substance	TWA: 100 ppm; TWA: 420 mg/m ³ ; STEL: 125 ppm; STEL: 525 mg/m ³ ;
Talc (hydrous magnesium silicate)	TWA: 2 mg/m ³ ; respirable fraction	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter	TWA: 2 mg/m ³ ; respirable fraction	TWA: 20 mppcf;
Ground Limestone (Calcium Carbonate)	TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;		TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;	TWA: 30 mppcf; TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;
Magnesite	TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;		TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;	
Crystalline Silica (Quartz)	TWA: 0.05 mg/m ³ ; respirable fraction	TWA: 0.025 mg/m ³ ; respirable particulate matter	TWA: 0.05 mg/m ³ ; respirable fraction	TWA: 300 particle/mL;

Biological occupational exposure limits

Chemical name	ACGIH
Styrene 100-42-5	150 mg/g creatinine - urine (Mandelic acid plus phenylglyoxylic acid) - end of shift 20 µg/L - urine (Styrene) - end of shift

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Use appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state Liquid
Appearance Green, Yellow, Paste
Color Green
Odor Aromatic
Odor threshold No Data Available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Boiling point (or initial boiling point or boiling range)	145 °C / 293 °F	
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Flash point	31 °C / 87.8 °F	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
SADT (°C)	No data available	None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	43081 mm ² /s	None known
Dynamic viscosity	38201 mPas (@ 20°C)	None known
Solubility	Insoluble	
Water solubility	No data available	None known
Partition coefficient n-octanol/water (log value)	1.36	
Vapor pressure (includes evaporation rate)	No Data Available	None known
Evaporation rate	Not applicable	None known
Density and/or relative density	No data available	
Bulk density	No data available	

Density	7.0-8.0	
Vapor density	No data available	None known
Particle characteristics		None known
Particle Size	No data available	
Particle Size Distribution	No data available	

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC content	Applied 0.40 lbs/gal or 48 g/L, Packaged 1.33 lbs/gal or 159 g/L
Density	7.0-8.0
Bulk density	No information available

10. Stability and reactivity

Reactivity	Stable.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Redness. May cause redness and tearing of the eyes.
----------	---

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------

Styrene 100-42-5	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 11.7 mg/L (Rat) 4 h
---------------------	----------------------	----------------------	-------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Styrene 100-42-5	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2A - Probably carcinogenic to humans	Reasonably Anticipated To Be A Human Carcinogen	Present
Talc (hydrous magnesium silicate) 14807-96-6	A4 - Not Classifiable as a Human Carcinogen	Group 2A	-	Present
Crystalline Silica (Quartz) 14808-60-7	A2 - Suspected Human Carcinogen	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

- A1 - Known Human Carcinogen
- A2 - Suspected human carcinogen
- A3 - Animal Carcinogen
- A4 - Not classifiable as a human carcinogen

IARC (International Agency for Research on Cancer)

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to carcinogenicity in humans

NTP (National Toxicology Program)

- Known - Known Carcinogen
- Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

- X - Present

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

STOT - single exposure Classification based on data available for ingredients. May cause respiratory irritation.

STOT - repeated exposure Classification based on data available for ingredients. Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Other adverse effects Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Neurological effects Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Styrene 100-42-5	EC50: =1.4mg/L (72h, Pseudokirchneriella subcapitata) EC50: =0.72mg/L (96h, Pseudokirchneriella subcapitata) EC50: 0.46 - 4.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 0.15 - 3.2mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 3.24 - 4.99mg/L (96h, Pimephales promelas) LC50: 19.03 - 33.53mg/L (96h, Lepomis macrochirus) LC50: 6.75 - 14.5mg/L (96h, Pimephales promelas) LC50: 58.75 - 95.32mg/L (96h, Poecilia reticulata)	-	EC50: 3.3 - 7.4mg/L (48h, Daphnia magna)
Talc (hydrous magnesium silicate) 14807-96-6	-	LC50: >100g/L (96h, Brachydanio rerio)	-	-

Persistence and degradability Not determined.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Styrene 100-42-5	2.96

Other adverse effects Keep out of drains, sewers, ditches and waterways.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number D001.

California waste information This product contains one or more substances that are listed with the State of California as

a hazardous waste.

14. Transport information

NOTE:

This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN number or ID number	UN3269
Proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing group	III
Reportable quantity (kg)	(Styrene : RQ (kg)= 454.00)
Reportable quantity (lbs)	Styrene : RQ (lb)= 1000.00
Reportable quantity (lbs) (calculated)	Styrene : RQ (lb)= 4985.00
Reportable quantity (kg) (calculated)	Styrene : RQ (kg)= 2263.38
Description	UN3269, Polyester Resin Kit, 3, III
Special Provisions	40, 149

TDG

UN number or ID number	UN3269
UN proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing group	III
Description	UN3269, Polyester Resin Kit, 3, III

MEX

UN number or ID number	UN3269
UN proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing group	III
Description	UN3269, Polyester Resin Kit, 3, III
Special Provisions	236, 340

ICAO (air)

UN number or ID number	UN3269
UN proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing group	III
Description	UN3269, Polyester Resin Kit, 3, III
Special Provisions	A66, A163

IATA

UN number or ID number	UN3269
UN proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing group	III
ERG Code	3L
Special Provisions	A66, A163
Description	UN3269, Polyester Resin Kit, 3, III

IMDG

UN number or ID number	UN3269
UN proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing group	III

EmS-No. F-E, S-D
Special Provisions 236, 340
Description UN3269, Polyester Resin Kit, 3, III, (31°C c.c.)

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies.
DSL/NDSL Complies.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb	-	-	X

CAA (Clean Air Act)

This product contains the following substances which are regulated pollutants to the Clean Air Act (CAA).

Chemical name	Hazardous air pollutants (HAPs)	Ozone-depleting substances (ODS)
Styrene 100-42-5	Present	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Styrene	1000 lb /	-	RQ 1000 lb final RQ

100-42-5	kg (final RQ)		RQ 454 kg final RQ
----------	---------------	--	--------------------

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Styrene - 100-42-5	Carcinogen
Crystalline Silica (Quartz) - 14808-60-7	Carcinogen
Titanium Dioxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Styrene 100-42-5	X	X	X
Talc (hydrous magnesium silicate) 14807-96-6	X	X	X
Ground Limestone (Calcium Carbonate) 1317-65-3	X	X	X
Magnesite 546-93-0	X	X	-
Crystalline Silica (Quartz) 14808-60-7	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Isopentane 78-78-4	X	X	X
Paraffin Wax 8002-74-2	X	X	X
WATER 7732-18-5	-	-	X
2-ethyl-1-hexanol 104-76-7	-	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 3 Instability 1 Special hazards -
HMIS Health hazards 3* Flammability 3 Physical hazards 0 Personal protection B
 Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Europe)
ADR	Agreement concerning the International Carriage of Dangerous Goods by Road (Europe)
AiIC	Australian Inventory of Industrial Chemicals
ATE	Acute Toxicity Estimate
ASTM	American Society for the Testing of Materials
bar	Biological Reference Values for Chemical Compounds in the Work Area
BAT	Biological tolerance values for occupational exposure
BEL	Biological exposure limits
bw	Body weight
Ceiling	Maximum limit value
CMR	Carcinogen, Mutagen or Reproductive Toxicant

DOT	Department of Transportation (United States)
DSL	Domestic Substances List (Canada)
EmS	Emergency Schedule
ENCS	Existing and New Chemical Substances (Japan)
EPA	U.S. Environmental Protection Agency
GHS	Globally Harmonized System
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO	International Civil Aviation Organization
IECSC	Inventory of Existing Chemical Substances in China
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Organization for Standardization
KECI	Korean Existing Chemicals Inventory
LC50	Lethal Concentration to 50% of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
MARPOL	International Convention for the Prevention of Pollution from Ships
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
n.o.s.	Not Otherwise Specified
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No Observed Adverse Effect Level
NOELR	No Observable Effect Loading Rate
NTP	National Toxicology Program (United States)
NZIoC	New Zealand Inventory of Chemicals
OECD	Organization for Economic Cooperation and Development
OEL	Occupational exposure limits
OSHA	Occupational Safety and Health Administration of the US Department of Labor
PBT	Persistent, Bioaccumulative and Toxic substance
PICCS	Philippines Inventory of Chemicals and Chemical Substances
PMT	Persistent, Mobile and Toxic
PPE	Personal protective equipment
QSAR	Quantitative Structure Activity Relationship
RID	Agreement concerning the International Carriage of Dangerous Goods by Rail (Europe)
SADT	Self-Accelerating Decomposition Temperature
SAR	Structure-activity relationship
SARA	Superfund Amendments and Reauthorization Act
SDS	Safety Data Sheet
SL	Surface Limit
STEL	Short Term Exposure Limit
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
TCSI	Taiwan Chemical Substance Inventory
TDG	Transport of Dangerous Goods (Canada)
TSCA	Toxic Substances Control Act (United States)
TWA	Time-Weighted Average
UN	United Nations
VOC	Volatile organic compounds
vPvB	Very Persistent and Very Bioaccumulative
vPvM	Very Persistent and Very Mobile
Sen+	Sensitizer
Sk*	Skin designation
**	Hazard Designation

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set
United Nations World Health Organization (WHO)

Revision Date 12-Feb-2025
Revision Note No information available.

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.
