



Close this window

SDS

Common Name: GREAT STUFF GAPS & CRACKS INSULATING FOAM SEALANT 12OZ HC ES

Manufacturer: DOW CHEMICAL

SDS Revision Date: 1/6/2016

SDS Format: GHS-US

Grainger Item Number(s): 48WK15

Manufacturer Model Number(s):

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

- [1. IDENTIFICATION](#)
- [2. HAZARDS IDENTIFICATION](#)
- [3. COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4. FIRST AID MEASURES](#)
- [5. FIREFIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL CONSIDERATIONS](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION](#)

DOW (R*)

SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

PRODUCT NAME:

GREAT STUFF(TM) GAPS & CRACKS INSULATING FOAM SEALANT 12OZ HC ES

ISSUE DATE: 01/06/2016

PRINT DATE: 02/24/2016

THE DOW CHEMICAL COMPANY ENCOURAGES AND EXPECTS YOU TO READ AND UNDERSTAND THE ENTIRE (M)SDS, AS THERE IS IMPORTANT INFORMATION THROUGHOUT THE DOCUMENT. WE EXPECT YOU TO FOLLOW THE PRECAUTIONS IDENTIFIED IN THIS DOCUMENT UNLESS YOUR USE CONDITIONS WOULD NECESSITATE OTHER APPROPRIATE METHODS OR ACTIONS.

1. IDENTIFICATION



PRODUCT NAME:

GREAT STUFF(TM) GAPS & CRACKS INSULATING FOAM SEALANT 12OZ HC ES

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE:

IDENTIFIED USES: POLYURETHANE FOAM.

COMPANY IDENTIFICATION:

THE DOW CHEMICAL COMPANY
2030 WILLARD H DOW CENTER
MIDLAND MI 48674-0000
UNITED STATES

CUSTOMER INFORMATION NUMBER: 800-258-2436

SDSQQUESTION@DOW.COM

EMERGENCY TELEPHONE NUMBER:

24-HOUR EMERGENCY CONTACT:
CHEMTREC: +1 703-527-3887

LOCAL EMERGENCY CONTACT: 800-424-9300

2. HAZARDS IDENTIFICATION



HAZARD CLASSIFICATION:

THIS MATERIAL IS HAZARDOUS UNDER THE CRITERIA OF THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD 29CFR 1910.1200.

FLAMMABLE AEROSOLS: CATEGORY 2

GASES UNDER PRESSURE: LIQUEFIED GAS

ACUTE TOXICITY: CATEGORY 4 - INHALATION

SKIN IRRITATION: CATEGORY 2

EYE IRRITATION: CATEGORY 2B

RESPIRATORY SENSITISATION: CATEGORY 1

SKIN SENSITISATION: CATEGORY 1

EFFECTS ON OR VIA LACTATION

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: CATEGORY 3

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: CATEGORY 2 - INHALATION

LABEL ELEMENTS:

HAZARD PICTOGRAMS:

FLAME

GAS CYLINDER

HEALTH HAZARD

EXCLAMATION MARK

SIGNAL WORD: DANGER!

HAZARDS:

FLAMMABLE AEROSOL.

CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CAUSES SKIN AND EYE IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

HARMFUL IF INHALED.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.

MAY CAUSE RESPIRATORY IRRITATION.

MAY CAUSE HARM TO BREAST-FED CHILDREN.

MAY CAUSE DAMAGE TO ORGANS (RESPIRATORY TRACT) THROUGH PROLONGED OR REPEATED EXPOSURE IF INHALED.

PRECAUTIONARY STATEMENTS:

PREVENTION:

OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. NO SMOKING.

DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

DO NOT BREATHE DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

AVOID CONTACT DURING PREGNANCY/WHILE NURSING.

WASH SKIN THOROUGHLY AFTER HANDLING.

DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.

WEAR PROTECTIVE GLOVES.

IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION.

RESPONSE:

IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.

IF INHALED:

REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION.

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

STORAGE:

STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

STORE LOCKED UP.

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F.

DISPOSAL:

DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

OTHER HAZARDS: NO DATA AVAILABLE

3. COMPOSITION/INFORMATION ON INGREDIENTS



CHEMICAL NATURE: POLYURETHANE PREPOLYMER

THIS PRODUCT IS A MIXTURE.

COMPONENT	CASRN	CONCENTRATION
DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES	9016-87-9	>=10.0 - <=30.0%
4,4' -METHYLENEDIPHENYL DIISOCYANATE	101-68-8	>=10.0 - <=30.0%
POLYMETHYLENEDIPHENYL-ISOCYANATE, PROPOXYLATED GLYCERIN POLYMER	57029-46-6	>=10.0 - <=30.0%
POLYMETHYLENEDIPHENYL	53862-89-8	>=10.0 - <=30.0%

POLYISOCYANATE,
POLYPROPYLENEGLYCOL COPOLYMER

TRIS(1-CHLORO-2-PROPYL) PHOSPHATE 13674-84-5 >=5.0 - <=10.0%

PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED 63449-39-8 >=5.0 - <=10.0%

ISOBUTANE 75-28-5 >=7.0 - <=13.0%

METHYL ETHER 115-10-6 >=1.0 - <=5.0%

PROPANE 74-98-6 >=1.0 - <=5.0%

NOTE:

NOTE: CAS 101-68-8 IS AN MDI ISOMER THAT IS PART OF CAS 9016-87-9.

4. FIRST AID MEASURES



DESCRIPTION OF FIRST AID MEASURES:

GENERAL ADVICE:

FIRST AID RESPONDERS SHOULD PAY ATTENTION TO SELF-PROTECTION AND USE THE RECOMMENDED PROTECTIVE CLOTHING (CHEMICAL RESISTANT GLOVES, SPLASH PROTECTION). IF POTENTIAL FOR EXPOSURE EXISTS REFER TO SECTION 8 FOR SPECIFIC PERSONAL PROTECTIVE EQUIPMENT.

INHALATION:

MOVE PERSON TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION; IF BY MOUTH TO MOUTH USE RESCUER PROTECTION (POCKET MASK, ETC). IF BREATHING IS DIFFICULT, OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. CALL A PHYSICIAN OR TRANSPORT TO A MEDICAL FACILITY.

SKIN CONTACT:

REMOVE MATERIAL FROM SKIN IMMEDIATELY BY WASHING WITH SOAP AND PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES WHILE WASHING. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. WASH CLOTHING BEFORE REUSE. AN MDI SKIN DECONTAMINATION STUDY DEMONSTRATED THAT CLEANING VERY SOON AFTER EXPOSURE IS IMPORTANT, AND THAT A POLYGLYCOL-BASED SKIN CLEANSER OR CORN OIL MAY BE MORE EFFECTIVE THAN SOAP AND WATER. DISCARD ITEMS WHICH CANNOT BE DECONTAMINATED, INCLUDING LEATHER ARTICLES SUCH AS SHOES, BELTS AND WATCHBANDS. SUITABLE EMERGENCY SAFETY SHOWER FACILITY SHOULD BE AVAILABLE IN WORK AREA.

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH WATER; REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, THEN CONTINUE FLUSHING EYES FOR AT LEAST 15 MINUTES. OBTAIN MEDICAL ATTENTION WITHOUT DELAY, PREFERABLY FROM AN OPHTHALMOLOGIST. SUITABLE EMERGENCY EYE WASH FACILITY SHOULD BE IMMEDIATELY AVAILABLE.

INGESTION:

IF SWALLOWED, SEEK MEDICAL ATTENTION. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:
ASIDE FROM THE INFORMATION FOUND UNDER DESCRIPTION OF FIRST AID MEASURES (ABOVE) AND INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED (BELOW), ANY ADDITIONAL IMPORTANT SYMPTOMS AND EFFECTS ARE DESCRIBED IN SECTION 11: TOXICOLOGY INFORMATION.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

NOTES TO PHYSICIAN:

MAINTAIN ADEQUATE VENTILATION AND OXYGENATION OF THE PATIENT. MAY CAUSE RESPIRATORY SENSITIZATION OR ASTHMA-LIKE SYMPTOMS. BRONCHODILATORS, EXPECTORANTS AND ANTITUSSIVES MAY BE OF HELP. TREAT BRONCHOSPASM WITH INHALED BETA2 AGONIST AND ORAL OR PARENTERAL CORTICOSTEROIDS. RESPIRATORY SYMPTOMS, INCLUDING PULMONARY EDEMA, MAY BE DELAYED. PERSONS RECEIVING SIGNIFICANT EXPOSURE SHOULD BE OBSERVED 24-48 HOURS FOR SIGNS OF RESPIRATORY DISTRESS. EXPOSURE MAY INCREASE "MYOCARDIAL IRRITABILITY". DO NOT ADMINISTER SYMPATHOMIMETIC DRUGS SUCH AS EPINEPHRINE UNLESS ABSOLUTELY NECESSARY. IF YOU ARE SENSITIZED TO DIISOCYANATES, CONSULT YOUR PHYSICIAN REGARDING WORKING WITH OTHER RESPIRATORY IRRITANTS OR SENSITIZERS. TREATMENT OF EXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITION OF THE PATIENT. EXCESSIVE EXPOSURE MAY AGGRAVATE PREEXISTING ASTHMA AND OTHER RESPIRATORY DISORDERS (E.G. EMPHYSEMA, BRONCHITIS, REACTIVE AIRWAYS DYSFUNCTION SYNDROME).

5. FIREFIGHTING MEASURES



SUITABLE EXTINGUISHING MEDIA:

WATER FOG OR FINE SPRAY. DRY CHEMICAL FIRE EXTINGUISHERS. CARBON DIOXIDE FIRE EXTINGUISHERS. FOAM. ALCOHOL RESISTANT FOAMS (ATC TYPE) ARE PREFERRED. GENERAL PURPOSE SYNTHETIC FOAMS (INCLUDING AFFF) OR PROTEIN FOAMS MAY FUNCTION, BUT WILL BE LESS EFFECTIVE.

UNSUITABLE EXTINGUISHING MEDIA:

DO NOT USE DIRECT WATER STREAM. STRAIGHT OR DIRECT WATER STREAMS MAY NOT BE EFFECTIVE TO EXTINGUISH FIRE.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

HAZARDOUS COMBUSTION PRODUCTS:

DURING A FIRE, SMOKE MAY CONTAIN THE ORIGINAL MATERIAL IN ADDITION TO COMBUSTION PRODUCTS OF VARYING COMPOSITION WHICH MAY BE TOXIC AND/OR IRRITATING.

COMBUSTION PRODUCTS MAY INCLUDE AND ARE NOT LIMITED TO:

NITROGEN OXIDES. ISOCYANATES. HYDROGEN CHLORIDE. CARBON MONOXIDE. CARBON DIOXIDE. HYDROGEN CYANIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CONTAINS FLAMMABLE PROPELLANT. AEROSOL CANS EXPOSED TO FIRE CAN RUPTURE AND BECOME FLAMING PROJECTILES. PROPELLANT RELEASE MAY RESULT IN A FIREBALL. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A LONG DISTANCE AND ACCUMULATE IN LOW LYING AREAS. IGNITION AND/OR FLASH BACK MAY OCCUR. DENSE SMOKE IS PRODUCED WHEN PRODUCT BURNS.

ADVICE FOR FIREFIGHTERS:

FIRE FIGHTING PROCEDURES:

KEEP PEOPLE AWAY. ISOLATE FIRE AND DENY UNNECESSARY ENTRY. STAY UPWIND. KEEP OUT OF LOW AREAS WHERE GASES (FUMES) CAN ACCUMULATE. WATER MAY NOT BE EFFECTIVE IN EXTINGUISHING FIRE. DO NOT USE DIRECT WATER STREAM. MAY SPREAD FIRE. FIGHT FIRE FROM PROTECTED LOCATION OR SAFE DISTANCE. CONSIDER THE USE OF UNMANNED HOSE HOLDERS OR MONITOR NOZZLES. ELIMINATE IGNITION SOURCES. MOVE CONTAINER FROM FIRE AREA IF THIS IS POSSIBLE WITHOUT HAZARD. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS AND FIRE-AFFECTED ZONE UNTIL FIRE IS OUT.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

WEAR POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS (SCBA) AND PROTECTIVE FIRE FIGHTING CLOTHING (INCLUDES FIRE FIGHTING HELMET, COAT, TROUSERS, BOOTS, AND GLOVES). AVOID CONTACT WITH THIS MATERIAL DURING FIRE FIGHTING OPERATIONS. IF CONTACT IS LIKELY, CHANGE TO FULL CHEMICAL RESISTANT FIRE FIGHTING CLOTHING WITH SELF-CONTAINED BREATHING APPARATUS. IF THIS IS NOT AVAILABLE, WEAR FULL CHEMICAL RESISTANT CLOTHING WITH SELF-CONTAINED BREATHING APPARATUS AND FIGHT FIRE FROM A REMOTE LOCATION. FOR PROTECTIVE EQUIPMENT IN POST-FIRE OR NON-FIRE CLEAN-UP SITUATIONS, REFER TO THE RELEVANT SECTIONS.

6. ACCIDENTAL RELEASE MEASURES



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

EVACUATE AREA. ONLY TRAINED AND PROPERLY PROTECTED PERSONNEL MUST BE INVOLVED IN CLEAN-UP OPERATIONS. KEEP PERSONNEL OUT OF LOW AREAS. KEEP PERSONNEL OUT OF CONFINED OR POORLY VENTILATED AREAS. KEEP UPWIND OF SPILL. VENTILATE AREA OF LEAK OR SPILL. NO SMOKING IN AREA. CHECK AREA WITH COMBUSTIBLE GAS DETECTOR BEFORE REENTERING AREA. GROUND AND BOND ALL CONTAINERS AND HANDLING EQUIPMENT. CONFINED SPACE ENTRY PROCEDURES MUST BE FOLLOWED BEFORE ENTERING THE AREA. ELIMINATE ALL SOURCES OF IGNITION IN VICINITY OF SPILL OR RELEASED VAPOR TO AVOID FIRE OR EXPLOSION. VAPOR EXPLOSION HAZARD. KEEP OUT OF SEWERS. SEE SECTION 10 FOR MORE SPECIFIC INFORMATION. USE APPROPRIATE SAFETY EQUIPMENT. FOR ADDITIONAL INFORMATION, REFER TO SECTION 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

ENVIRONMENTAL PRECAUTIONS:

PREVENT FROM ENTERING INTO SOIL, DITCHES, SEWERS, WATERWAYS AND/OR GROUNDWATER. SEE SECTION 12, ECOLOGICAL INFORMATION.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

CONTAIN SPILLED MATERIAL IF POSSIBLE. GROUND AND BOND ALL CONTAINERS AND HANDLING EQUIPMENT. ISOLATE AREA UNTIL GAS HAS DISPERSED. USE NON-SPARKING TOOLS IN CLEANUP OPERATIONS. ELIMINATE ALL SOURCES OF IGNITION IN VICINITY

OF SPILL OR RELEASED VAPOR TO AVOID FIRE OR EXPLOSION. CHECK AREA WITH COMBUSTIBLE GAS DETECTOR BEFORE REENTERING AREA. GROUND AND BOND ALL CONTAINERS AND HANDLING EQUIPMENT. COLLECT IN SUITABLE AND PROPERLY LABELED CONTAINERS.

ABSORB WITH MATERIALS SUCH AS:

CLAY. DIRT. MILSORB(R*). SAND. SAWDUST. VERMICULITE. SEE SECTION 10 FOR MORE SPECIFIC INFORMATION. SEE SECTION 13, DISPOSAL CONSIDERATIONS, FOR ADDITIONAL INFORMATION.

7. HANDLING AND STORAGE



PRECAUTIONS FOR SAFE HANDLING:

KEEP AWAY FROM HEAT, SPARKS AND FLAME. NO SMOKING, OPEN FLAMES OR SOURCES OF IGNITION IN HANDLING AND STORAGE AREA. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. AVOID BREATHING VAPOR. NEVER USE AIR PRESSURE FOR TRANSFERRING PRODUCT. WASH THOROUGHLY AFTER HANDLING. KEEP CONTAINER CLOSED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A LONG DISTANCE AND ACCUMULATE IN LOW LYING AREAS. IGNITION AND/OR FLASH BACK MAY OCCUR. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER. CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, CAN CONTAIN VAPORS. DO NOT CUT, DRILL, GRIND, WELD, OR PERFORM SIMILAR OPERATIONS ON OR NEAR EMPTY CONTAINERS. DO NOT ENTER CONFINED SPACES UNLESS ADEQUATELY VENTILATED. USE OF NON-SPARKING OR EXPLOSION-PROOF EQUIPMENT MAY BE NECESSARY, DEPENDING UPON THE TYPE OF OPERATION. SEE SECTION 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

CONDITIONS FOR SAFE STORAGE:

MINIMIZE SOURCES OF IGNITION, SUCH AS STATIC BUILD-UP, HEAT, SPARK OR FLAME. STORE IN A DRY PLACE. SEE SECTION 10 FOR MORE SPECIFIC INFORMATION.

STORAGE STABILITY:

STORAGE TEMPERATURE: 25 DEG. C (77 DEG. F)

STORAGE PERIOD: 12 MONTH

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



CONTROL PARAMETERS: EXPOSURE LIMITS ARE LISTED BELOW, IF THEY EXIST.

COMPONENT	REGULATION	TYPE OF LISTING	VALUE/NOTATION
4,4' -METHYLENEDIPHENYL DIISOCYANATE	DOW IHG	TWA	0.005 PPM
	DOW IHG	STEL	0.02 PPM
	ACGIH	TWA	0.005 PPM
	OSHA Z-1	C	0.2 MG/M3

			0.02 PPM
	NIOSH REL	TWA	0.05 MG/M3 0.005 PPM
	NIOSH REL	C	0.2 MG/M3 0.02 PPM
ISOBUTANE	ACGIH	STEL	1,000 PPM
METHYL ETHER	US WEEL	TWA	1,000 PPM
PROPANE	ACGIH		ASPHYXIAN
	OSHA Z-1	TWA	1,800 MG/M3 1,000 PPM

THIS MATERIAL CONTAINS A SIMPLE ASPHYXIAN WHICH MAY DISPLACE OXYGEN.
INSURE ADEQUATE VENTILATION TO PREVENT AN OXYGEN DEFICIENT ATMOSPHERE.

THE MINIMUM REQUIREMENT OF 19.5% OXYGEN AT SEA LEVEL (148 TORR O₂, DRY AIR) PROVIDES AN ADEQUATE AMOUNT OF OXYGEN FOR MOST WORK ASSIGNMENTS.

EXPOSURE CONTROLS:

ENGINEERING CONTROLS:

USE ONLY WITH ADEQUATE VENTILATION. LOCAL EXHAUST VENTILATION MAY BE NECESSARY FOR SOME OPERATIONS. PROVIDE GENERAL AND/OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE LEVELS BELOW THE EXPOSURE GUIDELINES. EXHAUST SYSTEMS SHOULD BE DESIGNED TO MOVE THE AIR AWAY FROM THE SOURCE OF VAPOR/AEROSOL GENERATION AND PEOPLE WORKING AT THIS POINT. THE ODOR AND IRRITANCY OF THIS MATERIAL ARE INADEQUATE TO WARN OF EXCESSIVE EXPOSURE. LETHAL CONCENTRATIONS MAY EXIST IN AREAS WITH POOR VENTILATION.

INDIVIDUAL PROTECTION MEASURES:

EYE/FACE PROTECTION: USE SAFETY GLASSES (WITH SIDE SHIELDS).

SKIN PROTECTION:

HAND PROTECTION:

USE GLOVES CHEMICALLY RESISTANT TO THIS MATERIAL.

EXAMPLES OF PREFERRED GLOVE BARRIER MATERIALS INCLUDE:

BUTYL RUBBER. CHLORINATED POLYETHYLENE. POLYETHYLENE. ETHYL VINYL ALCOHOL LAMINATE ("EVAL").

EXAMPLES OF ACCEPTABLE GLOVE BARRIER MATERIALS INCLUDE:

NEOPRENE. NITRILE/BUTADIENE RUBBER ("NITRILE" OR "NBR"). VITON. POLYVINYL CHLORIDE ("PVC" OR "VINYL").

NOTICE:

THE SELECTION OF A SPECIFIC GLOVE FOR A PARTICULAR APPLICATION AND DURATION OF USE IN A WORKPLACE SHOULD ALSO TAKE INTO ACCOUNT ALL RELEVANT WORKPLACE

FACTORS SUCH AS, BUT NOT LIMITED TO:

OTHER CHEMICALS WHICH MAY BE HANDLED, PHYSICAL REQUIREMENTS (CUT/PUNCTURE PROTECTION, DEXTERITY, THERMAL PROTECTION), POTENTIAL BODY REACTIONS TO GLOVE MATERIALS, AS WELL AS THE INSTRUCTIONS/SPECIFICATIONS PROVIDED BY THE GLOVE SUPPLIER.

OTHER PROTECTION:

USE PROTECTIVE CLOTHING CHEMICALLY RESISTANT TO THIS MATERIAL. SELECTION OF SPECIFIC ITEMS SUCH AS FACE SHIELD, BOOTS, APRON, OR FULL BODY SUIT WILL DEPEND ON THE TASK.

RESPIRATORY PROTECTION:

ATMOSPHERIC LEVELS SHOULD BE MAINTAINED BELOW THE EXPOSURE GUIDELINE. WHEN ATMOSPHERIC LEVELS MAY EXCEED THE EXPOSURE GUIDELINE, USE AN APPROVED AIR-PURIFYING RESPIRATOR EQUIPPED WITH AN ORGANIC VAPOR SORBENT AND A PARTICLE FILTER. FOR SITUATIONS WHERE THE ATMOSPHERIC LEVELS MAY EXCEED THE LEVEL FOR WHICH AN AIR-PURIFYING RESPIRATOR IS EFFECTIVE, USE A POSITIVE-PRESSURE AIR-SUPPLYING RESPIRATOR (AIR LINE OR SELF-CONTAINED BREATHING APPARATUS). FOR EMERGENCY RESPONSE OR FOR SITUATIONS WHERE THE ATMOSPHERIC LEVEL IS UNKNOWN, USE AN APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS OR POSITIVE-PRESSURE AIR LINE WITH AUXILIARY SELF-CONTAINED AIR SUPPLY. IN CONFINED OR POORLY VENTILATED AREAS, USE AN APPROVED SELF-CONTAINED BREATHING APPARATUS OR POSITIVE PRESSURE AIR LINE WITH AUXILIARY SELF-CONTAINED AIR SUPPLY.

THE FOLLOWING SHOULD BE EFFECTIVE TYPES OF AIR-PURIFYING RESPIRATORS:
ORGANIC VAPOR CARTRIDGE WITH A PARTICULATE PRE-FILTER.

9. PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE:

PHYSICAL STATE: FOAM

COLOR: YELLOW

ODOR: MILD

ODOR THRESHOLD: NO TEST DATA AVAILABLE

PH: NOT APPLICABLE

MELTING POINT/RANGE: NO TEST DATA AVAILABLE

FREEZING POINT: NO TEST DATA AVAILABLE

BOILING POINT (760 MMHg): NOT APPLICABLE

FLASH POINT: CLOSED CUP -104 DEG. C (-155 DEG. F) CLOSED CUP

EVAPORATION RATE (BUTYL ACETATE = 1): NO TEST DATA AVAILABLE

FLAMMABILITY (SOLID, GAS): NO DATA AVAILABLE

LOWER EXPLOSION LIMIT: NO TEST DATA AVAILABLE

UPPER EXPLOSION LIMIT: NO TEST DATA AVAILABLE

VAPOR PRESSURE:

1,151 HPA AT 55 DEG. C (131 DEG. F) NOT REPORTED CONTAINER IS UNDER PRESSURE.

RELATIVE VAPOR DENSITY (AIR = 1): NO TEST DATA AVAILABLE

RELATIVE DENSITY (WATER = 1): 1.06 ESTIMATED.

WATER SOLUBILITY: INSOLUBLE

PARTITION COEFFICIENT N-OCTANOL/WATER: NO DATA AVAILABLE

AUTO-IGNITION TEMPERATURE: NO TEST DATA AVAILABLE

DECOMPOSITION TEMPERATURE: NO TEST DATA AVAILABLE

KINEMATIC VISCOSITY: NOT APPLICABLE

EXPLOSIVE PROPERTIES: NOT EXPLOSIVE

OXIDIZING PROPERTIES: NO

MOLECULAR WEIGHT: NO TEST DATA AVAILABLE

NOTE:

THE PHYSICAL DATA PRESENTED ABOVE ARE TYPICAL VALUES AND SHOULD NOT BE CONSTRUED AS A SPECIFICATION.

10. STABILITY AND REACTIVITY



REACTIVITY: NO DATA AVAILABLE

CHEMICAL STABILITY:

STABLE UNDER RECOMMENDED STORAGE CONDITIONS. SEE STORAGE, SECTION 7.

UNSTABLE AT ELEVATED TEMPERATURES.

POSSIBILITY OF HAZARDOUS REACTIONS:

CAN OCCUR. EXPOSURE TO ELEVATED TEMPERATURES CAN CAUSE PRODUCT TO DECOMPOSE AND GENERATE GAS. THIS CAN CAUSE PRESSURE BUILD-UP AND/OR RUPTURING OF CLOSED CONTAINERS. ACIDS.

CONDITIONS TO AVOID: AVOID TEMPERATURES ABOVE 50 DEG. C

ELEVATED TEMPERATURES CAN CAUSE CONTAINER TO VENT AND/OR RUPTURE. EXPOSURE TO ELEVATED TEMPERATURES CAN CAUSE PRODUCT TO DECOMPOSE.

INCOMPATIBLE MATERIALS:

AVOID CONTACT WITH:

ACIDS. ALCOHOLS. AMINES. AMMONIA. BASES. METAL COMPOUNDS. STRONG OXIDIZERS. PRODUCTS BASED ON DIISOCYANATES LIKE TDI AND MDI REACT WITH MANY MATERIALS TO RELEASE HEAT. THE REACTION RATE INCREASES WITH TEMPERATURE AS WELL AS WITH INCREASED CONTACT; THESE REACTIONS CAN BECOME VIOLENT. CONTACT IS INCREASED BY STIRRING OR IF THE OTHER MATERIAL ACTS AS A SOLVENT. PRODUCTS BASED ON DIISOCYANATES SUCH AS TDI AND MDI ARE NOT SOLUBLE IN WATER AND WILL SINK TO THE BOTTOM, BUT REACT SLOWLY AT THE INTERFACE. THE REACTION FORMS CARBON DIOXIDE GAS AND A LAYER OF SOLID POLYUREA. REACTION WITH WATER WILL GENERATE CARBON DIOXIDE AND HEAT.

HAZARDOUS DECOMPOSITION PRODUCTS:

DECOMPOSITION PRODUCTS DEPEND UPON TEMPERATURE, AIR SUPPLY AND THE PRESENCE OF OTHER MATERIALS. TOXIC GASES ARE RELEASED DURING DECOMPOSITION.

11. TOXICOLOGICAL INFORMATION



TOXICOLOGICAL INFORMATION APPEARS IN THIS SECTION WHEN SUCH DATA IS AVAILABLE.

ACUTE TOXICITY:

ACUTE ORAL TOXICITY:

LOW TOXICITY IF SWALLOWED. SMALL AMOUNTS SWALLOWED INCIDENTALLY AS A RESULT OF NORMAL HANDLING OPERATIONS ARE NOT LIKELY TO CAUSE INJURY; HOWEVER, SWALLOWING LARGER AMOUNTS MAY CAUSE INJURY.

OBSERVATIONS IN ANIMALS INCLUDE: GASTROINTESTINAL IRRITATION.

AS PRODUCT: SINGLE DOSE ORAL LD50 HAS NOT BEEN DETERMINED.

LD50, RAT: >2,000 MG/KG ESTIMATED.

ACUTE DERMAL TOXICITY:

PROLONGED SKIN CONTACT IS UNLIKELY TO RESULT IN ABSORPTION OF HARMFUL AMOUNTS.

AS PRODUCT: THE DERMAL LD50 HAS NOT BEEN DETERMINED.

LD50, RABBIT: >2,000 MG/KG ESTIMATED.

ACUTE INHALATION TOXICITY:

IN CONFINED OR POORLY VENTILATED AREAS, VAPOR CAN EASILY ACCUMULATE AND CAN CAUSE UNCONSCIOUSNESS AND DEATH DUE TO DISPLACEMENT OF OXYGEN. EXCESSIVE EXPOSURE MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT (NOSE AND THROAT) AND LUNGS. MAY CAUSE PULMONARY EDEMA (FLUID IN THE LUNGS.) EFFECTS MAY BE DELAYED. MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SYMPTOMS OF EXCESSIVE EXPOSURE MAY BE ANESTHETIC OR NARCOTIC EFFECTS; DIZZINESS AND DROWSINESS MAY BE OBSERVED. EXCESSIVE EXPOSURE MAY INCREASE SENSITIVITY TO EPINEPHRINE AND INCREASE MYOCARDIAL IRRITABILITY (IRREGULAR HEARTBEATS). DECREASED LUNG FUNCTION HAS BEEN ASSOCIATED WITH OVEREXPOSURE TO ISOCYANATES.

AS PRODUCT: THE LC50 HAS NOT BEEN DETERMINED.

SKIN CORROSION/IRRITATION:

PROLONGED CONTACT MAY CAUSE MODERATE SKIN IRRITATION WITH LOCAL REDNESS.
MATERIAL MAY STICK TO SKIN CAUSING IRRITATION UPON REMOVAL.
MAY STAIN SKIN.

SERIOUS EYE DAMAGE/EYE IRRITATION:

MAY CAUSE MODERATE EYE IRRITATION.
MAY CAUSE SLIGHT TEMPORARY CORNEAL INJURY.

SENSITIZATION:

SKIN CONTACT MAY CAUSE AN ALLERGIC SKIN REACTION.

ANIMAL STUDIES HAVE SHOWN THAT SKIN CONTACT WITH ISOCYANATES MAY PLAY A
ROLE IN RESPIRATORY SENSITIZATION.

MAY CAUSE ALLERGIC RESPIRATORY REACTION.

MDI CONCENTRATIONS BELOW THE EXPOSURE GUIDELINES MAY CAUSE ALLERGIC
RESPIRATORY REACTIONS IN INDIVIDUALS ALREADY SENSITIZED.

ASTHMA-LIKE SYMPTOMS MAY INCLUDE COUGHING, DIFFICULT BREATHING AND A
FEELING OF TIGHTNESS IN THE CHEST.

OCCASIONALLY, BREATHING DIFFICULTIES MAY BE LIFE THREATENING.

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE):

MAY CAUSE RESPIRATORY IRRITATION.

ROUTE OF EXPOSURE: INHALATION

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE):

TISSUE INJURY IN THE UPPER RESPIRATORY TRACT AND LUNGS HAS BEEN OBSERVED
IN LABORATORY ANIMALS AFTER REPEATED EXCESSIVE EXPOSURES TO MDI/POLYMERIC
MDI AEROSOLS.

CARCINOGENICITY:

LUNG TUMORS HAVE BEEN OBSERVED IN LABORATORY ANIMALS EXPOSED TO RESPIRABLE
AEROSOL DROPLETS OF MDI/POLYMERIC MDI (6 MG/M3) FOR THEIR LIFETIME. TUMORS
OCCURRED CONCURRENTLY WITH RESPIRATORY IRRITATION AND LUNG INJURY. CURRENT
EXPOSURE GUIDELINES ARE EXPECTED TO PROTECT AGAINST THESE EFFECTS REPORTED
FOR MDI.

TERATOGENICITY:

IN LABORATORY ANIMALS, MDI/POLYMERIC MDI DID NOT CAUSE BIRTH DEFECTS; OTHER
FETAL EFFECTS OCCURRED ONLY AT HIGH DOSES WHICH WERE TOXIC TO THE MOTHER.

REPRODUCTIVE TOXICITY:

BASED ON INFORMATION FOR COMPONENT(S): MAY CAUSE HARM TO BREASTFED BABIES.

MUTAGENICITY:

IN VITRO GENETIC TOXICITY STUDIES WERE NEGATIVE FOR COMPONENT(S) TESTED.
GENETIC TOXICITY DATA ON MDI ARE INCONCLUSIVE. MDI WAS WEAKLY POSITIVE IN

SOME IN VITRO STUDIES; OTHER IN VITRO STUDIES WERE NEGATIVE. ANIMAL MUTAGENICITY STUDIES WERE PREDOMINANTLY NEGATIVE.

ASPIRATION HAZARD:

BASED ON PHYSICAL PROPERTIES, NOT LIKELY TO BE AN ASPIRATION HAZARD.

COMPONENTS INFLUENCING TOXICOLOGY:

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES:

ACUTE INHALATION TOXICITY:

LC50, RAT, 4 HOUR, DUST/MIST: 0.49 MG/L

FOR SIMILAR MATERIAL(S):

2,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 5873-54-1).

LC50, RAT, 4 HOUR, AEROSOL: 0.31 MG/L

FOR SIMILAR MATERIAL(S):

4,4'-METHYLENEDIPHENYL DIISOCYANATE (CAS 101-68-8).

LC50, RAT, 1 HOUR, AEROSOL: 2.24 MG/L

4,4' -METHYLENEDIPHENYL DIISOCYANATE:

ACUTE INHALATION TOXICITY:

LC50, RAT, 1 HOUR, DUST/MIST: 2.24 MG/L

POLYMETHYLENEPOLYPHENYLISOCYANATE, PROPOXYLATED GLYCERIN POLYMER:

ACUTE INHALATION TOXICITY: THE LC50 HAS NOT BEEN DETERMINED.

POLYMETHYLENEPOLYPHENYL POLYISOCYANATE, POLYPROPYLENEGLYCOL COPOLYMER:

ACUTE INHALATION TOXICITY: THE LC50 HAS NOT BEEN DETERMINED.

TRIS(1-CHLORO-2-PROPYL) PHOSPHATE:

ACUTE INHALATION TOXICITY:

LC50, RAT, 4 HOUR, DUST/MIST: >7 MG/L

PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED:

ACUTE INHALATION TOXICITY: THE LC50 HAS NOT BEEN DETERMINED.

ISOBUTANE:

ACUTE INHALATION TOXICITY:

LC50, MOUSE, 1 HOUR: 52 MG/L

METHYL ETHER:

ACUTE INHALATION TOXICITY:

LC50, RAT, 4 HOUR, GAS: 164000 PPM

PROPANE:

ACUTE INHALATION TOXICITY:

LC50, RAT, MALE AND FEMALE, 4 HOUR, VAPOUR: >425000 PPM

12. ECOLOGICAL INFORMATION



ECOTOXICOLOGICAL INFORMATION APPEARS IN THIS SECTION WHEN SUCH DATA IS AVAILABLE.

TOXICITY:

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES:

ACUTE TOXICITY TO FISH:

THE MEASURED ECOTOXICITY IS THAT OF THE HYDROLYZED PRODUCT, GENERALLY UNDER CONDITIONS MAXIMIZING PRODUCTION OF SOLUBLE SPECIES.

MATERIAL IS PRACTICALLY NON-TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS (LC50/EC50/EL50/LL50 >100 MG/L IN THE MOST SENSITIVE SPECIES TESTED).

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

LC50, DANIO RERIO (ZEBRA FISH), STATIC TEST, 96 HOUR: >1,000 MG/L, OECD TEST GUIDELINE 203 OR EQUIVALENT

ACUTE TOXICITY TO AQUATIC INVERTEBRATES:

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

EC50, DAPHNIA MAGNA (WATER FLEA), STATIC TEST: 24 HOUR, >1,000 MG/L, OECD TEST GUIDELINE 202 OR EQUIVALENT

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS:

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

NOEC, DESMODESMUS SUBSPICATUS (GREEN ALGAE), STATIC TEST, 72 HOUR, GROWTH RATE INHIBITION, 1,640 MG/L, OECD TEST GUIDELINE 201 OR EQUIVALENT

TOXICITY TO BACTERIA:

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

EC50, ACTIVATED SLUDGE, STATIC TEST, 3 HOUR, RESPIRATION RATES.: >100 MG/L

TOXICITY TO SOIL-DWELLING ORGANISMS:

EC50, EISENIA FETIDA (EARTHWORMS), BASED ON INFORMATION FOR A SIMILAR MATERIAL: 14 D, >1,000 MG/KG

TOXICITY TO TERRESTRIAL PLANTS:

EC50, AVENA SATIVA (OATS), GROWTH INHIBITION: 1,000 MG/L

EC50, LACTUCA SATIVA (LETTUCE), GROWTH INHIBITION: 1,000 MG/L

4,4' -METHYLENEDIPHENYL DIISOCYANATE:

ACUTE TOXICITY TO FISH:

THE MEASURED ECOTOXICITY IS THAT OF THE HYDROLYZED PRODUCT, GENERALLY UNDER CONDITIONS MAXIMIZING PRODUCTION OF SOLUBLE SPECIES.

MATERIAL IS PRACTICALLY NON-TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS (LC50/EC50/EL50/LL50 >100 MG/L IN THE MOST SENSITIVE SPECIES TESTED).

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

LC50, DANIO RERIO (ZEBRA FISH), STATIC TEST, 96 HOUR: >1,000 MG/L, OECD

TEST GUIDELINE 203 OR EQUIVALENT

ACUTE TOXICITY TO AQUATIC INVERTEBRATES:

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

EC50, DAPHNIA MAGNA (WATER FLEA), STATIC TEST, 24 HOUR: >1,000 MG/L, OECD TEST GUIDELINE 202 OR EQUIVALENT

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS:

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

NOEC, DESMODESMUS SUBSPICATUS (GREEN ALGAE), STATIC TEST, 72 HOUR, GROWTH RATE INHIBITION, 1,640 MG/L, OECD TEST GUIDELINE 201 OR EQUIVALENT

TOXICITY TO BACTERIA:

BASED ON INFORMATION FOR A SIMILAR MATERIAL:

EC50, ACTIVATED SLUDGE, STATIC TEST, 3 HOUR, RESPIRATION RATES.: >100 MG/L

TOXICITY TO SOIL-DWELLING ORGANISMS

EC50, EISENIA FETIDA (EARTHWORMS), BASED ON INFORMATION FOR A SIMILAR MATERIAL: 14 D, >1,000 MG/KG

TOXICITY TO TERRESTRIAL PLANTS:

EC50, AVENA SATIVA (OATS), GROWTH INHIBITION: 1,000 MG/L

EC50, LACTUCA SATIVA (LETTUCE), GROWTH INHIBITION: 1,000 MG/L

POLYMETHYLENEPOLYPHENYLISOCYANATE, PROPOXYLATED GLYCERIN POLYMER:

ACUTE TOXICITY TO FISH:

FOR THIS FAMILY OF MATERIALS:

MATERIAL IS PRACTICALLY NON-TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS (LC50/EC50/EL50/LL50 >100 MG/L IN THE MOST SENSITIVE SPECIES TESTED).

POLYMETHYLENEPOLYPHENYL POLYISOCYANATE, POLYPROPYLENEGLYCOL COPOLYMER:

ACUTE TOXICITY TO FISH:

NOT EXPECTED TO BE ACUTELY TOXIC TO AQUATIC ORGANISMS.

TRIS(1-CHLORO-2-PROPYL) PHOSPHATE:

ACUTE TOXICITY TO FISH:

MATERIAL IS SLIGHTLY TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS (LC50/EC50 BETWEEN 10 AND 100 MG/L IN THE MOST SENSITIVE SPECIES TESTED).

LC50, LEPOMIS MACROCHIRUS (BLUEGILL SUNFISH), STATIC TEST: 96 HOUR, 84 MG/L, OECD TEST GUIDELINE 203 OR EQUIVALENT

ACUTE TOXICITY TO AQUATIC INVERTEBRATES:

EC50, DAPHNIA MAGNA (WATER FLEA), 48 HOUR: 131 MG/L

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS:

ERC50, PSEUDOKIRCHNERIELLA SUBCAPITATA (GREEN ALGAE), STATIC TEST, 96 HOUR, GROWTH RATE INHIBITION: 82 MG/L, OECD TEST GUIDELINE 201 OR EQUIVALENT

TOXICITY TO BACTERIA:

EC50, ACTIVATED SLUDGE, RESPIRATION INHIBITION, 3 HOUR:
784 MG/L, OECD 209 TEST

CHRONIC TOXICITY TO AQUATIC INVERTEBRATES:

NOEC, DAPHNIA MAGNA (WATER FLEA), SEMI-STATIC TEST, 21 D, NUMBER OF
OFFSPRING: 32 MG/L

LOEC, DAPHNIA MAGNA (WATER FLEA), SEMI-STATIC TEST, 21 D, NUMBER OF
OFFSPRING: >32 MG/L

PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED:

ACUTE TOXICITY TO FISH:

MATERIAL IS HIGHLY TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS (LC50/EC50
BETWEEN 0.1 AND 1 MG/L IN THE MOST SENSITIVE SPECIES TESTED).

LC50, ONCORHYNCHUS MYKISS (RAINBOW TROUT), 96 HOUR: > 0.1 MG/L

ISOBUTANE:

ACUTE TOXICITY TO FISH: NO RELEVANT DATA FOUND.

METHYL ETHER:

ACUTE TOXICITY TO FISH:

MATERIAL IS PRACTICALLY NON-TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS
(LC50/EC50/EL50/LL50 >100 MG/L IN THE MOST SENSITIVE SPECIES TESTED).

LC50, POECILIA RETICULATA (GUPPY), SEMI-STATIC TEST, 96 HOUR: >4,000 MG/L

ACUTE TOXICITY TO AQUATIC INVERTEBRATES:

LC50, DAPHNIA MAGNA (WATER FLEA), 48 HOUR, >4,000 MG/L, OECD TEST GUIDELINE
202 OR EQUIVALENT

PROPANE:

ACUTE TOXICITY TO FISH: NO RELEVANT DATA FOUND.

PERSISTENCE AND DEGRADABILITY:

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES:

BIODEGRADABILITY:

IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MATERIAL REACTS WITH WATER
FORMING PREDOMINANTLY INSOLUBLE POLYUREAS WHICH APPEAR TO BE STABLE.
IN THE ATMOSPHERIC ENVIRONMENT, MATERIAL IS EXPECTED TO HAVE A SHORT
TROPOSPHERIC HALF-LIFE, BASED ON CALCULATIONS AND BY ANALOGY WITH RELATED
DIISOCYANATES.

10-DAY WINDOW: NOT APPLICABLE

BIODEGRADATION: 0%

EXPOSURE TIME: 28 D

METHOD: OECD TEST GUIDELINE 302C OR EQUIVALENT

4,4' -METHYLENEDIPHENYL DIISOCYANATE:

BIODEGRADABILITY:

IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MATERIAL REACTS WITH WATER FORMING PREDOMINANTLY INSOLUBLE POLYUREAS WHICH APPEAR TO BE STABLE. IN THE ATMOSPHERIC ENVIRONMENT, MATERIAL IS EXPECTED TO HAVE A SHORT TROPOSPHERIC HALF-LIFE, BASED ON CALCULATIONS AND BY ANALOGY WITH RELATED DIISOCYANATES.

10-DAY WINDOW: NOT APPLICABLE

BIODEGRADATION: 0%

EXPOSURE TIME: 28 D

METHOD: OECD TEST GUIDELINE 302C OR EQUIVALENT

POLYMETHYLENEDIPHENYLISOCYANATE, PROPOXYLATED GLYCERIN POLYMER:

BIODEGRADABILITY:

FOR THIS FAMILY OF MATERIALS: MATERIAL IS READILY BIODEGRADABLE. PASSES OECD TEST(S) FOR READY BIODEGRADABILITY.

POLYMETHYLENEDIPHENYL POLYISOCYANATE, POLYPROPYLENEGLYCOL COPOLYMER:

BIODEGRADABILITY: EXPECTED TO DEGRADE SLOWLY IN THE ENVIRONMENT.

TRIS(1-CHLORO-2-PROPYL) PHOSPHATE:

BIODEGRADABILITY:

MATERIAL IS EXPECTED TO BIODEGRADE VERY SLOWLY (IN THE ENVIRONMENT). FAILS TO PASS OECD/EEC TESTS FOR READY BIODEGRADABILITY.

10-DAY WINDOW: FAIL

BIODEGRADATION: 14 %

EXPOSURE TIME: 28 D

METHOD: OECD TEST GUIDELINE 301E OR EQUIVALENT

10-DAY WINDOW: NOT APPLICABLE

BIODEGRADATION: 95 %

EXPOSURE TIME: 64 D

METHOD: OECD TEST GUIDELINE 302A OR EQUIVALENT

THEORETICAL OXYGEN DEMAND: 1.17 MG/MG

PHOTODEGRADATION:

TEST TYPE: HALF-LIFE (INDIRECT PHOTOLYSIS)

SENSITIZER: OH RADICALS
ATMOSPHERIC HALF-LIFE: 0.24 D
METHOD: ESTIMATED.

PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED:
BIODEGRADABILITY: EXPECTED TO DEGRADE SLOWLY IN THE ENVIRONMENT.

THEORETICAL OXYGEN DEMAND: 2.89 MG/MG

ISOBUTANE:
BIODEGRADABILITY:
BIODEGRADATION MAY OCCUR UNDER AEROBIC CONDITIONS (IN THE PRESENCE OF OXYGEN).

THEORETICAL OXYGEN DEMAND: 3.58 MG/MG

PHOTODEGRADATION:
TEST TYPE: HALF-LIFE (INDIRECT PHOTOLYSIS)
SENSITIZER: OH RADICALS
ATMOSPHERIC HALF-LIFE: 4.4 D
METHOD: ESTIMATED.

METHYL ETHER:

BIODEGRADABILITY:
MATERIAL IS EXPECTED TO BIODEGRADE VERY SLOWLY (IN THE ENVIRONMENT). FAILS TO PASS OECD/EEC TESTS FOR READY BIODEGRADABILITY.

10-DAY WINDOW: FAIL

BIODEGRADATION: 5%

EXPOSURE TIME: 28 D

METHOD: OECD TEST GUIDELINE 301A OR EQUIVALENT

THEORETICAL OXYGEN DEMAND: 2.08 MG/MG

PHOTODEGRADATION:
TEST TYPE: HALF-LIFE (INDIRECT PHOTOLYSIS)
SENSITIZER: OH RADICALS
ATMOSPHERIC HALF-LIFE: 6.4 D
METHOD: ESTIMATED.

PROPANE:
BIODEGRADABILITY: NO RELEVANT DATA FOUND.
THEORETICAL OXYGEN DEMAND: 3.64 MG/MG

PHOTODEGRADATION:
TEST TYPE: HALF-LIFE (INDIRECT PHOTOLYSIS)
SENSITIZER: OH RADICALS
ATMOSPHERIC HALF-LIFE: 8.4 D
METHOD: ESTIMATED.

BIOACCUMULATIVE POTENTIAL:

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES:

BIOACCUMULATION:

BIOCONCENTRATION POTENTIAL IS LOW (BCF < 100 OR LOG POW < 3). REACTS WITH WATER. IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MOVEMENT IS EXPECTED TO BE LIMITED BY ITS REACTION WITH WATER FORMING PREDOMINANTLY INSOLUBLE POLYUREAS.

BIOCONCENTRATION FACTOR (BCF): 92 CYPRINUS CARPIO (CARP) 28 D

4,4' -METHYLENEDIPHENYL DIISOCYANATE:

BIOACCUMULATION:

BIOCONCENTRATION POTENTIAL IS LOW (BCF <100 OR LOG POW <3). REACTS WITH WATER. IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MOVEMENT IS EXPECTED TO BE LIMITED BY ITS REACTION WITH WATER FORMING PREDOMINANTLY INSOLUBLE POLYUREAS.

BIOCONCENTRATION FACTOR (BCF): 92 CYPRINUS CARPIO (CARP) 28 D

POLYMETHYLENEDIPHENYLISOCYANATE, PROPOXYLATED GLYCERIN POLYMER:

BIOACCUMULATION: NO RELEVANT DATA FOUND.

POLYMETHYLENEDIPHENYL POLYISOCYANATE, POLYPROPYLENEGLYCOL COPOLYMER:

BIOACCUMULATION:

IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MOVEMENT IS EXPECTED TO BE LIMITED BY ITS REACTION WITH WATER FORMING PREDOMINANTLY INSOLUBLE POLYUREAS.

TRIS(1-CHLORO-2-PROPYL) PHOSPHATE:

BIOACCUMULATION:

BIOCONCENTRATION POTENTIAL IS LOW (BCF <100 OR LOG POW <3).

PARTITION COEFFICIENT:

N-OCTANOL/WATER(LOG POW): 2.59 MEASURED

BIOCONCENTRATION FACTOR (BCF):

0.8 - 4.6 CYPRINUS CARPIO (CARP) 42 D MEASURED

PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED:

BIOACCUMULATION:

BIOCONCENTRATION POTENTIAL IS LOW (BCF LESS THAN 100 OR LOG POW GREATER THAN 7).

PARTITION COEFFICIENT:

N-OCTANOL/WATER(LOG POW): 7.4 ESTIMATED.

ISOBUTANE:

BIOACCUMULATION:

BIOCONCENTRATION POTENTIAL IS LOW (BCF <100 OR LOG POW <3).

PARTITION COEFFICIENT:

N-OCTANOL/WATER(LOG POW): 2.76 MEASURED

METHYL ETHER:

BIOACCUMULATION:

BIOCONCENTRATION POTENTIAL IS LOW (BCF <100 OR LOG POW <3).

PARTITION COEFFICIENT:

N-OCTANOL/WATER(LOG POW): 0.10 MEASURED

PROPANE:

BIOACCUMULATION:

BIOCONCENTRATION POTENTIAL IS LOW (BCF <100 OR LOG POW <3).

PARTITION COEFFICIENT:

N-OCTANOL/WATER(LOG POW): 2.36 MEASURED

MOBILITY IN SOIL:

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES:

IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MOVEMENT IS EXPECTED TO BE LIMITED BY ITS REACTION WITH WATER FORMING PREDOMINANTLY INSOLUBLE POLYUREAS.

4,4' -METHYLENEDIPHENYL DIISOCYANATE:

IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MOVEMENT IS EXPECTED TO BE LIMITED BY ITS REACTION WITH WATER FORMING PREDOMINANTLY INSOLUBLE POLYUREAS.

POLYMETHYLENEDIPHENYLISOCYANATE, PROPOXYLATED GLYCERIN POLYMER:

NO RELEVANT DATA FOUND.

POLYMETHYLENEDIPHENYL POLYISOCYANATE, POLYPROPYLENEGLYCOL COPOLYMER:

IN THE AQUATIC AND TERRESTRIAL ENVIRONMENT, MOVEMENT IS EXPECTED TO BE LIMITED BY ITS REACTION WITH WATER FORMING PREDOMINANTLY INSOLUBLE POLYUREAS.

TRIS(1-CHLORO-2-PROPYL) PHOSPHATE:

POTENTIAL FOR MOBILITY IN SOIL IS SLIGHT (KOC BETWEEN 2000 AND 5000).

PARTITION COEFFICIENT(KOC): 1300 ESTIMATED.

PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED:

EXPECTED TO BE RELATIVELY IMMOBILE IN SOIL (KOC > 5000).

GIVEN ITS VERY LOW HENRY'S CONSTANT, VOLATILIZATION FROM NATURAL BODIES OF WATER OR MOIST SOIL IS NOT EXPECTED TO BE AN IMPORTANT FATE PROCESS.

PARTITION COEFFICIENT(KOC): > 5000 ESTIMATED.

ISOBUTANE:

POTENTIAL FOR MOBILITY IN SOIL IS VERY HIGH (KOC BETWEEN 0 AND 50).
PARTITION COEFFICIENT(KOC): 35 ESTIMATED.

METHYL ETHER:

POTENTIAL FOR MOBILITY IN SOIL IS VERY HIGH (KOC BETWEEN 0 AND 50).
PARTITION COEFFICIENT(KOC): 1.29 - 14 ESTIMATED.

PROPANE:

POTENTIAL FOR MOBILITY IN SOIL IS VERY HIGH (KOC BETWEEN 0 AND 50).
PARTITION COEFFICIENT(KOC): 24 - 460 ESTIMATED.

13. DISPOSAL CONSIDERATIONS



DISPOSAL METHODS:

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL PRACTICES MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL AND LOCAL LAWS AND REGULATIONS. REGULATIONS MAY VARY IN DIFFERENT LOCATIONS. WASTE CHARACTERIZATIONS AND COMPLIANCE WITH APPLICABLE LAWS ARE THE RESPONSIBILITY SOLELY OF THE WASTE GENERATOR. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: COMPOSITION INFORMATION. FOR UNUSED & UNCONTAMINATED PRODUCT, THE PREFERRED OPTIONS INCLUDE SENDING TO A LICENSED, PERMITTED: INCINERATOR OR OTHER THERMAL DESTRUCTION DEVICE.

14. TRANSPORT INFORMATION



DOT:

PROPER SHIPPING NAME: AEROSOLS
UN NUMBER: UN 1950
CLASS: 2.1
PACKING GROUP:
REPORTABLE QUANTITY: MDI

CLASSIFICATION FOR SEA TRANSPORT (IMO-IMDG):

PROPER SHIPPING NAME: AEROSOLS

UN NUMBER: UN 1950

CLASS: 2.1

PACKING GROUP:

MARINE POLLUTANT: PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED

TRANSPORT IN BULK ACCORDING TO ANNEX I OR II OF MARPOL 73/78 AND THE IBC OR IGC CODE: CONSULT IMO REGULATIONS BEFORE TRANSPORTING OCEAN BULK

CLASSIFICATION FOR AIR TRANSPORT (IATA/ICAO):

PROPER SHIPPING NAME: AEROSOLS, FLAMMABLE

UN NUMBER: UN 1950

CLASS: 2.1

PACKING GROUP:

THIS INFORMATION IS NOT INTENDED TO CONVEY ALL SPECIFIC REGULATORY OR OPERATIONAL REQUIREMENTS/INFORMATION RELATING TO THIS PRODUCT.

TRANSPORTATION CLASSIFICATIONS MAY VARY BY CONTAINER VOLUME AND MAY BE INFLUENCED BY REGIONAL OR COUNTRY VARIATIONS IN REGULATIONS. ADDITIONAL TRANSPORTATION SYSTEM INFORMATION CAN BE OBTAINED THROUGH AN AUTHORIZED SALES OR CUSTOMER SERVICE REPRESENTATIVE. IT IS THE RESPONSIBILITY OF THE TRANSPORTING ORGANIZATION TO FOLLOW ALL APPLICABLE LAWS, REGULATIONS AND RULES RELATING TO THE TRANSPORTATION OF THE MATERIAL.

15. REGULATORY INFORMATION



OSHA HAZARD COMMUNICATION STANDARD:

THIS PRODUCT IS A "HAZARDOUS CHEMICAL" AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTIONS 311 AND 312:

ACUTE HEALTH HAZARD

CHRONIC HEALTH HAZARD

FIRE HAZARD

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986) SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND WHICH ARE LISTED IN 40 CFR 372.

COMPONENTS	CASRN
DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES	9016-87-9
4,4' -METHYLENEDIPHENYL DIISOCYANATE	101-68-8

PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT:

THE FOLLOWING CHEMICALS ARE LISTED BECAUSE OF THE ADDITIONAL REQUIREMENTS OF PENNSYLVANIA LAW:

COMPONENTS	CASRN
ISOBUTANE	75-28-5
METHYL ETHER	115-10-6

PROPANE

74-98-6

CALIFORNIA PROPOSITION 65 (SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986):

THIS PRODUCT CONTAINS NO LISTED SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM, AT LEVELS WHICH WOULD REQUIRE A WARNING UNDER THE STATUTE.

UNITED STATES TSCA INVENTORY (TSCA):

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE INVENTORY LISTING REQUIREMENTS OF THE U.S. TOXIC SUBSTANCES CONTROL ACT (TSCA) CHEMICAL SUBSTANCE INVENTORY.

16. OTHER INFORMATION



REVISION:

IDENTIFICATION NUMBER: 101265380/A001

ISSUE DATE: 01/06/2016

VERSION: 8.0

MOST RECENT REVISION(S) ARE NOTED BY THE BOLD, DOUBLE BARS IN LEFT-HAND MARGIN THROUGHOUT THIS DOCUMENT.

LEGEND:

ACGIH: USA. ACGIH THRESHOLD LIMIT VALUES (TLV)

ASPHYXIAN: ASPHYXIAN

C: CEILING

DOW IHG: DOW INDUSTRIAL HYGIENE GUIDELINE

NIOSH REL: USA. NIOSH RECOMMENDED EXPOSURE LIMITS

OSHA Z-1:

USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS

STEL: SHORT TERM EXPOSURE LIMIT

TWA: TIME WEIGHTED AVERAGE

US WEEL: USA. WORKPLACE ENVIRONMENTAL EXPOSURE LEVELS (WEEL)

INFORMATION SOURCE AND REFERENCES:

THIS SDS IS PREPARED BY PRODUCT REGULATORY SERVICES AND HAZARD COMMUNICATIONS GROUPS FROM INFORMATION SUPPLIED BY INTERNAL REFERENCES WITHIN OUR COMPANY.

THE DOW CHEMICAL COMPANY URGES EACH CUSTOMER OR RECIPIENT OF THIS (M)SDS TO STUDY IT CAREFULLY AND CONSULT APPROPRIATE EXPERTISE, AS NECESSARY OR APPROPRIATE, TO BECOME AWARE OF AND UNDERSTAND THE DATA CONTAINED IN THIS (M)SDS AND ANY HAZARDS ASSOCIATED WITH THE PRODUCT. THE INFORMATION HEREIN IS PROVIDED IN GOOD FAITH AND BELIEVED TO BE ACCURATE AS OF THE EFFECTIVE DATE SHOWN ABOVE. HOWEVER, NO WARRANTY, EXPRESS OR IMPLIED, IS GIVEN. REGULATORY REQUIREMENTS ARE SUBJECT TO CHANGE AND MAY DIFFER BETWEEN VARIOUS LOCATIONS. IT IS THE BUYER'S/USER'S RESPONSIBILITY TO ENSURE THAT HIS ACTIVITIES COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL OR LOCAL LAWS. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED. SINCE CONDITIONS FOR USE OF THE PRODUCT ARE NOT UNDER THE CONTROL OF THE MANUFACTURER, IT IS THE BUYER'S/USER'S DUTY TO DETERMINE THE CONDITIONS NECESSARY FOR THE SAFE USE OF THIS PRODUCT. DUE TO THE PROLIFERATION OF SOURCES FOR INFORMATION SUCH AS MANUFACTURER-SPECIFIC (M)SDSS, WE ARE NOT AND CANNOT BE RESPONSIBLE FOR (M)SDSS OBTAINED FROM ANY SOURCE OTHER THAN OURSELVES. IF YOU HAVE OBTAINED AN (M)SDS FROM ANOTHER SOURCE OR IF YOU ARE NOT SURE THAT THE (M)SDS YOU HAVE IS CURRENT, PLEASE CONTACT US FOR THE MOST CURRENT VERSION.

(R*) (TM) TRADEMARK OF THE DOW CHEMICAL COMPANY ("DOW") OR AN AFFILIATED COMPANY OF DOW