SDSE1548

ITEM: 4FFF9 - Silicone Sealant, High Temp, Clear, 10.3 oz HU NUMBER: U236752801 DELIVERY: **6392130912**

SAFETY DATA SHEET (SDS)

This SDS should be attached or kept with the respective product with which it is associated.

Associated Items 4FFF9

SUREBOND

SAFETY DATA SHEET

SB-188 HIGH TEMPERATURE SILICONE SEALANT (BLACK)

----SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION -----

PRODUCT NAME: SB-188 HIGH TEMPERATURE SILICONE SEALANT (BLACK)

COMPANY NAME: SUREBOND 3925 STERN AVENUE ST. CHARLES, IL 60174

PHONE: (877) 843-1818

EMERGENCY PHONE (24 HOUR): CHEMTREC: (800) 424-9300 CHEMTREC (OUTSIDE USA): (703) 527-3887

REVISION DATE: 11/20/2015

-----SECTION 2 - HAZARDS IDENTIFICATION -----

GHS CLASSIFICATION GHS CLASSIFICATION: CATEGORY 2B SKIN IRRITATION: CATEGORY 2 SKIN SENSITIZATION: CATEGORY 1B CARCINOGENICITY: CATEGORY 2

GHS LABEL ELEMENTS:

HAZARD SYMBOLS: GHS07: EXCLAMATION MARK GHS08: HEALTH HAZARD

SIGNAL WORD: WARNING

HAZARD STATEMENTS: CAUSES SKIN IRRITATION MAY CAUSE AN ALLERGIC SKIN REACTION CAUSES EYE IRRITATION SUSPECTED OF CAUSING CANCER

PRECAUTIONARY STATEMENTS:

PREVENTION: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE OBTAIN SPECIAL INSTRUCTIONS BEFORE USE DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. AVOID BREATHING DUST, FUME OR VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH HANDS AND OTHER SKIN AREAS THOROUGHLY AFTER HANDLING USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

RESPONSE: IF ON SKIN, WASH WITH PLENTY OF SOAP AND WATER. IF SKIN IRRITATION OR RASH OCCURS, GET MEDICAL ATTENTION.

IF IN EYES, RINSE WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES IF PRESENT AND EASY TO DO. CONTINUE RINSING.

IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

TAKE OF CONTAMINATED CLOTHING AND WASHIT BEFORE REUSE.

STORAGE: STORE LOCKED UP, STORE IN A WELL-VENTILATED PLACE

DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH APPLICABLE LOCAL, REGIONAL, NATIONAL AND INTERNATIONAL REGULATIONS.

OTHER HAZARDS: NONE KNOWN

SUPPLEMENTAL INFORMATION: 95% OF THE MIXTURE CONSISTS OF COMPONENT(S) OF UNKNOWN ACUTE INHALATION TOXICITY.

-----SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS --

SUBSTANCE/MIXTURE: MIXTURE

CHEMICAL NAME

CAS NUMBER CONCENTRATION (%)

SILICONE DIOXIDE

7631-86-9 5.0 - 10.0

DISTILLATES (PETROLEUM), HYDROTREATED 64742-46-7 5.0 - 10.0 MIDDLE

PIGMENTED SEALANTS MAY CONTAIN:

CARBON BLACK

1333-86-4 0.1 - 1.0

TITANIUM DIOXIDE

13463-67-7 0.1 - 1.0

PIGMENT BLUE 15

147-14-8 1.0 - 5.0

1309-37-1 1.0 - 5.0

THERE ARE NO ADDITIONAL INGREDIENTS PRESENT WHICH, WITHIN THE CURRENT KNOWLEDGE OF THE SUPPLIER AND IN THE CONCENTRATIONS APPLICABLE, ARE CLASSIFIED AS HAZARDOUS TO THE HEALTH OR THE ENVIRONMENT AND HENCE REQUIRE REPORTING IN THIS SECTION.

-----SECTION 4 - FIRST AID MEASURES -----

AFTER EYE CONTACT: FLUSH WITH COPIOUS QUANTITIES OF LUKEWARM WATER FOR AT LEAST 15 MINUTES. DO NOT ATTEMPT TO PHYSICALLY REMOVE THE SOLIDS OR GUMS FROM THE EYE. SEEK MEDICAL ATTENTION IMMEDIATELY IF IRRITATION PERSISTS.

AFTER SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH WARM WATER AND NON-ABRASIVE SOAP. SEEK MEDICAL ATTENTION IF YOU FEEL ILL OR A REACTION

AFTER INHALATION:

REMOVE TO FRESH AIR AND PROVIDE WATER, SEEK MEDICAL ATTENTION IF YOU FEEL ILL OR A REACTION DEVELOPS.

AFTER INGESTION: DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON, GET MEDICAL ATTENTION.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED: NONE KNOWN

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: PROVIDE GENERAL SUPPORTIVE MEASURES AND TREAT SYMPTOMATICALLY.

-----SECTION 5 - FIRE FIGHTING MEASURES -----

SUITABLE EXTINGUISHING AGENTS: CARBON DIOXIDE, DRY CHEMICAL, WATER FOG OR FOAM. WATER CAN BE USED TO COOL FIRE EXPOSED CONTAINERS.

UNSUITABLE EXTINGUISHING AGENTS: NONE KNOWN

SPECIAL HAZARDS ARISING FROM THE CHEMICAL: EXPOSURE TO COMBUSTION PRODUCTS SUCH AS CARBON OXIDES, SILICONE OXIDES AND FORMALDEHYDE MAY BE HAZARD TO HEALTH.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING LARGE FIRES INVOLVING CHEMICALS. DETERMINE THE NEED TO EVACUATE OR ISOLATE THE AREA ACCORDING TO YOUR LOCAL EMERGENCY PLAN.

----SECTION 6 - ACCIDENTAL RELEASE MEASURES -----

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: FOLLOW SAFE HANDLING ADVICE AND PERSONAL PROTECTIVE EQUIPMENT RECOMMENDATIONS IN SECTION 8.

ENVIRONMENTAL PRECAUTIONS:

ENVIRONMENTAL FREGATIONS:
DISCHARGED INTO THE ENVIRONMENT MUST BE AVOIDED. RETAIN AND DISPOSE OF CONTAMINATED WASH WATER. LOCAL AUTHORITIES SHOULD BE ADVISED IF SIGNIFICANT SPILLAGES CANNOT BE CONTAINED.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:
RESTRICT ACCESS TO THE AREA OF THE SPILL. PROVIDE VENTILATION, NIOSH/MHSA
APPROVED RESPIRATOR AND PROTECTIVE CLOTHING. SCRAPE UP SEALANT AND PLACE IN
CONTAINER FOR DISPOSAL. CLEAN AREA AS APPROPRIATE SINCE SILICONE MATERIALS
CAN REPRESENT A SLIP HAZARD. CLEANING MAY REQUIRE STEAM, SOLVENTS OR
DETERGENTS. DISPOSE OF SATURATED ABSORBENT OR CLEANING MATERIALS
APPROPRIATELY, SINCE SPONTANEOUS HEATING MAY OCCUR. LOCAL, STATE,
PROVINCIAL, FEDERAL LAWS AND REGULATIONS MAY APPLY TO RELEASES AND DISPOSAL
OF THIS MATERIAL, AS WELL AS THOSE MATERIALS AND ITEMS EMPLOYED IN THE
CLEANUP.

-----SECTION 7 - HANDLING AND STORAGE -----

PRECAUTIONS FOR SAFE HANDLING: HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. TAKE CARE TO PREVENT SPILLS, WASTE AND MINIMIZE RELEASE TO THE ENVIRONMENT.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: STORE IN AN ADEQUATELY VENTILATED AREA UNDER DRY CONDITIONS BETWEEN 50 DEG. F (10 DEG. C) TO 77 DEG. F (25 DEG. C)

KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE

DO NOT STORE WITH STRONG OXIDIZING AGENTS.

-----SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -----

CONTROL PARAMETERS

T CAS NO. VALUE TYPE CONTROL PARAMETERS/ BASIS (FORM OF PERMISSIBLE EXPOSURE) CONCENTRATION INGREDIENT

SILICONE DIOXIDE 7631-86-9 TWA (DUST) 20 MILLION PARTICLES OSHA Z-3 PER CUBIC FOOT (SILICA)

> TWA (DUST) 80 MG/M3/%SiO2 (SILIĆA)

6 MG/M3 (SILICA) NIOSH REL TWA

DISTILLATES 64742-46-7 TWA (MIST) 5 MG/M3 OSHA Z-1 (PETROLEUM), HYDROTREATED TWA (MIST) 5 MG/M3 OSHA PO

TWA (MIST) 5 MG/M3

ST (MIST) 10 MG/M3

CARBON BLACK 1333-86-4 TWA

NIOSH REL

TWA 3.5 MG/M3 3.5 MG/M3

OSHA Z-1

ACGIH TLV

ACGIH

TWA 3 MG/M3

(INHALABLE FRACTION)

TITANIUM DIOXIDE 13463-67-7 TWA

15 MG/M3

IRON OXIDE

TWA

1309-37-1 TWA

10 MG/M3

5 MG/M3 ACGIH TLV

RESPIRABLE FRACTION)

PIGMENT BLUE 15 147-14-8 TWA

1 MG/M3

OSHA PEL

OSHA PEL

NIOSH REL

OSHA PEL

TWA **ACGIH TLV**

10 MG/M3

ENGINEERING CONTROLS:
ENSURE ADEQUATE VENTILATION, ESPECIALLY IN CONFINED AREAS. MINIMIZE
WORKPLACE EXPOSURE CONCENTRATIONS. USE RESPIRATORY PROTECTION UNLESS
LOCAL EXHAUST VENTILATION IS PROVIDED OR EXPOSURES ARE WITHIN GUIDELINES.

PERSONAL PROTECTIVE EQUIPMENT:
SAFETY GLASSES WITH SIDE-PROTECTION, IMPERMEABLE GLOVES (E.G., NEOPRENE,
NITRILE, SILVER SHIELD (R)), COVERALLS OR APRON ARE IMPORTANT IN PREVENTING
CONTAMINATION OF EYES, SKIN AND CLOTHING. WASH THOROUGHLY AFTER HANDLING.

-----SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----

APPEARANCE: PASTE, THIXOTROPIC SEALANT

ODOR: ACETIC ACID

ODOR THRESHOLD: NOT AVAILABLE

MELTING POINT/FREEZING POINT: NOT AVAILABLE

INITIAL BOILING POINT AND BOILING RANGE: NOT AVAILABLE

FLASH POINT: >212 DEG. F (100 DEG. C) CLOSED CUP METHOD

EVAPORATION RATE: NOT APPLICABLE

FLAMMABILITY (SOLID, GAS): NOT CLASSIFIED AS A FLAMMABILITY HAZARD

UPPER FLAMMABILITY OR EXPLOSION LIMIT: NOT AVAILABLE LOWER FLAMMABILITY OR EXPLOSION LIMIT: NOT AVAILABLE

VAPOR PRESSURE: NOT APPLICABLE

VAPOR DENSITY: NOT AVAILABLE

SPECIFIC GRAVITY: 1.01

SOLUBILITY: NOT AVAILABLE

PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE

AUTO-IGNITION TEMPERATURE: NOT AVAILABLE

DECOMPOSITION TEMPERATURE: NOT AVAILABLE

VISCOSITY: NOT APPLICABLE

ACID RESERVE, G NaOH/100 G (CCCR 2001, SECTIONS 43 AND 44): 0.17

VOLATILE ORGANIC CONTENT

30 GRAMS PER LITER, <3% BY WEIGHT (CHEMICALLY CURING SEALANTS AND CAULKS -CARB METHOD 310: VOC LESS WATER, LESS EXEMPT COMPOUNDS AND LVP-VOCS).

-----SECTION 10 - STABILITY AND REACTIVITY -----

REACTIVITY: NOT CLASSIFIED AS A REACTIVITY HAZARD

CHEMICAL STABILITY: STABLE UNDER NORMAL CONDITIONS

POSSIBILITY OF HAZARDOUS REACTIONS:
USE AT ELEVATED TEMPERATURES MAY FORM HIGHLY HAZARDOUS COMPOUNDS. AT ABOVE
150 DEG. C (300 DEG. F) IN THE PRESENCE OF AIR, TRACE QUANTITIES OF
FORMALDEHYDE MAY BE RELEASED. ACETIC ACID IS FORMED UPON CONTACT WITH WATER

CONDITIONS TO AVOID: MOISTURE AND INCOMPATIBLE MATERIALS.

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS OR ELECTROPHILES (E.G. FERRIC CHLORIDE). CONCENTRATED ACIDS OR BASES CAN DEGRADE THE SILICONE POLYMER.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES, SILICONE DIOXIDE, METAL OXIDES, FORMALDEHYDE AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

-----SECTION 11 - TOXICOLOGICAL INFORMATION -----

INFORMATION ON THE LIKELY ROUTES OF EXPOSURE: INHALATION: PROLONGED INHALATION MAY BE HARMFUL. INGESTION: MAY BE HARMFUL IF SWALLOWED. SKIN CONTACT: MAY CAUSE SKIN IRRITATION ON DIRECT CONTACT. EYE CONTACT: MAY CAUSE EYE IRRITATION ON DIRECT CONTACT.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:
MAY CAUSE AN ALLERGIC SKIN REACTION. SUSPECTED OF CAUSING CANCER. ALTHOUGH THE CARBON BLACK (CAS# 1333-86-4) IS ENCAPSULATED BY THE SILICONE SEALANT, PROLONGED OVEREXPOSURE TO CARBON BLACK DUST CAUSES LUNG FIBROSIS. ALTHOUGH THE TITANIUM DIOXIDE (CAS# 13463-67-7) IS ENCAPSULATED BY THE SILICONE SEALANT, PROLONGED OVEREXPOSURE TO TITANIUM DIOXIDE DUST CAUSES TIGHTNESS PAIN IN THE CHEST, COUGHING AND DIFFICULTY BREATHING.

ACUTE TOXICITY:

INGREDIENT NAME RESULT SPECIES DOSE **EXPOSURE**

SILICONE DIOXIDE LD50 ORAL RAT >3,300 MG/KG (CAS#: 7631-86-9) LC50 INHALATION RAT >2,08 MG/L 4 HOURS LD50 DERMAL RABBIT >5,000 MG/KG

DISTILLATES LD50 ORAL RAT 5,000 MG/KG LC50 INHALATION RAT 1.78 MG/L (PETROLEUM) 4 HOURS HYDROTREATED LD50 DERMAL RAT >2,000 MG/KG

(CAS#: 64742-46-7)

CARBON BLACK LD50 ORAL RAT 14.400 MG/KG

(CAS#: 1333-86-4)

TITANIUM DIOXIDE LD50 ORAL

RAT 24,000 MG/KG

PIGMENT BLUE 15 (CAS#: 147-14-8)

LD50 ORAL

RAT >10,000 MG/KG

SKIN CORROSION/IRRITATION: MAY CAUSE SKIN IRRITATION.

SERIOUS EYE DAMAGE/IRRITATION: MAY CAUSE SKIN IRRITATION

ASPIRATION HAZARD: NOT CLASSIFIED BASED ON AVAILABLE INFORMATION.

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE (CAS# 64742-46-7) IS KNOWN TO CAUSE HUMAN ASPIRATION TOXICITY HAZARDS OR HAS TO BE REGARDED AS IF IT CAUSES A HUMAN ASPIRATION TOXICITY HAZARD.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE NOT CLASSIFIED BASED ON AVAILABLE INFORMATION

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: NOT CLASSIFIED BASED ON AVAILABLE INFORMATION.

RESPIRATORY OR SKIN SENSITIZATION:
NOT CLASSIFIED BASED ON AVAILABLE INFORMATION.

CARCINOGENICITY:
NO INGREDIENTS CONSIDERED BY IARC, NTP OR OSHA TO BE CARCINOGENS EXCEPT IN
THE PIGMENTED SEALANTS WHICH MAY CONTAIN:

CARBON BLACK (CAS# 1333-86-4): IARC GROUP 2B - POSSIBLY CARCINOGENIC TO HUMANS.

TITANIUM DIOXIDE (CAS# 13463-67-7): IARC GROUP 2B - POSSIBLY CARCINOGENIC TO HUMANS.

REPRODUCTIVE TOXICITY: NOT CLASSIFIED BASED ON AVAILABLE INFORMATION.

TERATOGENICITY: NOT CLASSIFIED BASED ON AVAILABLE INFORMATION

GERM-CELL MUTAGENICITY: NOT CLASSIFIED BASED ON AVAILABLE INFORMATION.

-----SECTION 12 - ECOLOGICAL INFORMATION -----

ECOTOXICITY: NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY: NO DATA AVAILABLE.

BIOACCUMULATIVE POTENTIAL: NO DATA AVAILABLE.

MOBILITY IN SOIL: NO DATA AVAILABLE

OTHER ADVERSE EFFECTS: NO DATA AVAILABLE.

-----SECTION 13 - DISPOSAL CONSIDERATIONS -----



DISPOSAL INSTRUCTIONS:
THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF AS HAZARDOUS WASTE. DO NOT ALLOW THIS MATERIAL TO DRAIN INTO SEWERS, WATER SUPPLIES. DISPOSE OF CONTENTS, CONTAINER IN ACCORDANCE WITH LOCAL, REGIONAL, NATIONAL AND INTERNATIONAL REGULATIONS

WASTE FROM RESIDUES: DISPOSE OF IN ACCORDANCE WITH LOCAL REGULATIONS.

CONTAMINATED PACKAGING: DISPOSE OF AS UNUSED PRODUCT. EMPTY CONTAINERS SHOULD BE TAKEN TO AN APPROVED WASTE HANDLING SITE FOR RECYCLING OR DISPOSAL.

-----SECTION 14 - TRANSPORT INFORMATION -----

SHIPPING INFORMATION: NOT SUBJECT TO DOT, TDG, IMDG CODE OR IATA REGULATIONS.

-----SECTION 15 - REGULATORY INFORMATION -----

EPCRA - EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW:

CERCLA REPORTABLE QUANTITY:

INGREDIENTS CAS NO. COMPONENT RQ (LBS) CALCULATED PRODUCT RQ

(LBS)

ACETIC ACID 64-19-7 5000

ACETIC ANHYDRIDE 108-24-7 5000

* CALCULATED RQ EXCEEDS REASONABLY ATTAINABLE UPPER LIMIT.

SARA 304 EXTREMELY HAZARDOUS SUBSTANCES REPORTABLE QUANTITY THIS PRODUCT DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 304 EHS RQ.

SARA 311/312 HAZARDS: NO SARA HAZARDS.

SARA 302

NO CHEMICALS IN THIS PRODUCT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313: THIS PRODUCT DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NO. THAT EXCEED THE THRESHOLD REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

5 - 10%

PENNSYLVANIA RIGHT TO KNOW:

DIMETHYL SILOXANE, HYDROXY-TERMINATED 70131-67-8 70 - 90%

SILICONE DIOXIDE 7631-86-9

DISTILLATES (PETROLEUM), HYDROTREATED 64742-46-7 MIDDLE 5 - 10%

ACETIC ACID 64-19-7 0 - 0.1%

ACETIC ANHYDRIDE 108-24-7

0 - 0.1% CARBON BLACK 1333-86-4 0.1 - 1%

TITANIUM DIOXIDE 13463-67-7 0.1 - 1%

1 - 5%

PIGMENT BLUE 15 147-14-8 IRON OXIDE

NEW JERSEY RIGHT TO KNOW:

DIMETHYL SILOXANE, HYDROXY-TERMINATED 70131-67-8 70 - 90%

1309-37-1

SILICONE DIOXIDE 7631-86-9 5 - 10%

DISTILLATES (PETROLEUM), HYDROTREATED 64742-46-7 5 - 10% MIDDLE

CARBON BLACK 1333-86-4 0.1 - 1%

TITANIUM DIOXIDE 13463-67-7 0.1 - 1%

PIGMENT BLUE 15 147-14-8 1 - 5%

IRON OXIDE 1309-37-1 1 - 5%

CALIFORNIA PROPOSITION 65: THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH OR ANY OTHER REPRODUCTIVE DEFECTS.

THE INGREDIENTS OF THIS PRODUCT ARE REPORTED IN THE FOLLOWING INVENTORIES:

ALL CHEMICAL SUBSTANCES IN THIS PRODUCT ARE INCLUDED ON OR EXEMPTED FROM LISTING ON THE TSCA INVENTORY OF CHEMICAL SUBSTANCES.

DSE: ALL CHEMICAL SUBSTANCES IN THIS PRODUCT COMPLY WITH THE CEPA 1999 AND NSNR AND ARE ON OR EXEMPTED FROM LISTING ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL).

NFPA PROFILE: HEALTH 1 FLAMMABILITY 1 REACTIVITY 0

-----SECTION 16 - OTHER INFORMATION -----

DISCLAIMER:
THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AS OF THE DATE
OF PREPARATION OF THIS SDS AND WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, NO
WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA. WE
SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY
PRODUCT, METHOD OR APPARATUS MENTIONED. USER MUST MAKE HIS/HER OWN
INVESTIGATION TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS
FOR HIS/HER PARTICULAR PURPOSE, FOR THE PROTECTION OF THE ENVIRONMENT AND
THE LIEAT LIT AND CAGETY OF THE LISESE OF THIS MATERIAL THE HEALTH AND SAFETY OF THE USERS OF THIS MATERIAL.

SUREBOND 3925 STERN AVENUE ST. CHARLES, IL 60174

877.843.1818

INFO@SUREBOND.COM

WWW.SUREBOND.COM

