

ITEM: 34FW69 Elastomeric Acrylic Sealant, 10oz., Black

DELIVERY: 6392130912

HU NUMBER: U236752801

SDSD3785

SAFETY DATA SHEET (SDS)

This SDS should be attached or kept with the respective product with which it is associated.

MSDS - D3785

Associated Items
34FW69**MATERIAL SAFETY DATA SHEET**

WL0003069

18 00

DATE OF PREPARATION: FEB 19, 2014

-----SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION -----

PRODUCT NUMBER: WL0003069

PRODUCT NAME:
WHITE LIGHTNING(R*) 3006(TM) ULTRA ALL PURPOSE ELASTOMERIC SEALANT, BLACKMANUFACTURER'S NAME:
THE SHERWIN-WILLIAMS CO.
CONSUMER GROUP - INDUSTRIAL
CLEVELAND, OH 44115

TELEPHONE NUMBERS AND WEBSITES:

PRODUCT INFORMATION:
(800) 241-5295
WWW.WLCAULK.COMREGULATORY INFORMATION:
(216) 566-2902
WWW.PAINTDOCS.COM

MEDICAL EMERGENCY: (216) 566-2917

TRANSPORTATION EMERGENCY*: (800) 424-9300

*FOR CHEMICAL EMERGENCY ONLY (SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT)

-----SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS -----

% BY WEIGHT CAS NUMBER INGREDIENT UNITS VAPOR PRESSURE

50 1317-65-3 CALCIUM CARBONATE
ACGIH TLV: 10 MG/M3 AS DUST
OSHA PEL: 10 MG/M3 TOTAL DUST
OSHA PEL: 5 MG/M3 RESPIRABLE
FRACTION0.5 1333-86-4 CARBON BLACK
ACGIH TLV: 3.5 MG/M3
OSHA PEL: 3.5 MG/M3**-----SECTION 3 - HAZARDS IDENTIFICATION -----**HMIS CODES:
HEALTH 1*
FLAMMABILITY 0
REACTIVITY 0ROUTES OF EXPOSURE:
INHALATION OF VAPOR OR SPRAY MIST,
EYE OR SKIN CONTACT WITH THE PRODUCT, VAPOR OR SPRAY MIST.EFFECTS OF OVEREXPOSURE:
EYES: IRRITATION.
SKIN: PROLONGED OR REPEATED EXPOSURE MAY CAUSE IRRITATION.
INHALATION: IRRITATION OF THE UPPER RESPIRATORY SYSTEM.SIGNS AND SYMPTOMS OF OVEREXPOSURE:
REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN
EXPOSURE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE GENERALLY RECOGNIZED.

CANCER INFORMATION:
FOR COMPLETE DISCUSSION OF TOXICOLOGY DATA REFER TO SECTION 11.**-----SECTION 4 - FIRST AID MEASURES -----**EYES:
FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL
ATTENTION.

SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER.

INHALATION:
IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET.

INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

-----SECTION 5 - FIRE FIGHTING MEASURES -----

FLASH POINT: NOT APPLICABLE

LEL: NOT APPLICABLE
UEL: NOT APPLICABLE

FLAMMABILITY CLASSIFICATION: NOT APPLICABLE

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS:
CLOSED CONTAINERS MAY EXPLODE (DUE TO THE BUILD-UP OF PRESSURE) WHEN
EXPOSED TO EXTREME HEAT.DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY
CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN
MEDICAL ATTENTION.SPECIAL FIRE FIGHTING PROCEDURES:
FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS
SHOULD BE USED.WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE
PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE
BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME
HEAT.**-----SECTION 6 - ACCIDENTAL RELEASE MEASURES -----**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
REMOVE ALL SOURCES OF IGNITION. VENTILATE THE AREA.
REMOVE WITH INERT ABSORBENT.**-----SECTION 7 - HANDLING AND STORAGE -----**

STORAGE CATEGORY: NOT APPLICABLE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS
WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE INTERNALLY. KEEP OUT OF
THE REACH OF CHILDREN.**-----SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -----**PRECAUTIONS TO BE TAKEN IN USE:
USE ONLY WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING VAPOR AND SPRAY MIST.
WASH HANDS AFTER USING.THIS COATING MAY CONTAIN MATERIALS CLASSIFIED AS NUISANCE PARTICULATES
(LISTED "AS DUST" IN SECTION 2) WHICH MAY BE PRESENT AT HAZARDOUS LEVELS
ONLY DURING SANDING OR ABRADING OF THE DRIED FILM. IF NO SPECIFIC DUSTS
ARE LISTED IN SECTION 2, THE APPLICABLE LIMITS FOR NUISANCE DUSTS ARE
ACGIH TLV 10 MG/M3 (TOTAL DUST), 3 MG/M3 (RESPIRABLE FRACTION),
OSHA PEL 15 MG/M3 (TOTAL DUST), 5 MG/M3 (RESPIRABLE FRACTION).REMOVAL OF OLD PAINT BY SANDING, SCRAPING OR OTHER MEANS MAY GENERATE DUST
OR FUMES THAT CONTAIN LEAD. EXPOSURE TO LEAD DUST OR FUMES MAY CAUSE BROWN
DAMAGE OR OTHER ADVERSE HEALTH EFFECTS, ESPECIALLY IN CHILDREN OR PREGNANT
WOMEN. CONTROLLING EXPOSURE TO LEAD OR OTHER HAZARDOUS SUBSTANCES REQUIRES
THE USE OF PROPER PROTECTIVE EQUIPMENT, SUCH AS A PROPERLY FITTED
RESPIRATOR (NIOSH APPROVED) AND PROPER CONTAINMENT AND CLEANUP. FOR MORE
INFORMATION, CALL THE NATIONAL LEAD INFORMATION CENTER AT 1-800-424-LEAD
(IN US) OR CONTACT YOUR LOCAL HEALTH AUTHORITY.VENTILATION:
LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO
MATERIALS IN SECTION 2 IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.
REFER TO OSHA STANDARDS 1910.94, 1910.107, 1910.108.RESPIRATORY PROTECTION:
IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY
VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR
APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS IN SECTION 2.WHEN SANDING OR ABRADING THE DRIED FILM, WEAR A DUST/MIST RESPIRATOR
APPROVED BY NIOSH/MSHA FOR DUST WHICH MAY BE GENERATED FROM THIS PRODUCT,
UNDERLYING PAINT, OR THE ABRASIVE.

PROTECTIVE GLOVES: REQUIRED FOR LONG OR REPEATED CONTACT.

EYE PROTECTION: WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS.

-----SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----PRODUCT WEIGHT:
12.80 LB/GAL
1533 G/L

SPECIFIC GRAVITY: 1.54

BOILING POINT:
212 - 213 DEG. F
100 - 100 DEG. C

MELTING POINT: NOT AVAILABLE



VOLATILE VOLUME: 29%

EVAPORATION RATE: SLOWER THAN ETHER

VAPOR DENSITY: HEAVIER THAN AIR

SOLUBILITY IN WATER: NOT AVAILABLE

PH: 8.0

VOLATILE ORGANIC COMPOUNDS (VOC THEORETICAL - AS PACKAGED):
0.17 LB/GAL 20 G/L LESS WATER AND FEDERALLY EXEMPT SOLVENTS
0.12 LB/GAL 14 G/L EMITTED VOC

-----SECTION 10 - STABILITY AND REACTIVITY -----

STABILITY: STABLE

CONDITIONS TO AVOID: NONE KNOWN.

INCOMPATIBILITY: NONE KNOWN.

HAZARDOUS DECOMPOSITION PRODUCTS:
BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

-----SECTION 11 - TOXICOLOGICAL INFORMATION -----

CHRONIC HEALTH HAZARDS:
CARBON BLACK IS CLASSIFIED BY IARC AS POSSIBLY CARCINOGENIC TO HUMANS
(GROUP 2B) BASED ON EXPERIMENTAL ANIMAL DATA, HOWEVER, THERE IS
INSUFFICIENT EVIDENCE IN HUMANS FOR ITS CARCINOGENICITY.

TOXICOLOGY DATA:

CAS NO. INGREDIENT NAME

1317-65-3 CALCIUM CARBONATE
LC50 RAT 4HR: NOT AVAILABLE
LD50 RAT: NOT AVAILABLE

1333-86-4 CARBON BLACK
LC50 RAT 4HR: NOT AVAILABLE
LD50 RAT: NOT AVAILABLE

-----SECTION 12 - ECOLOGICAL INFORMATION -----

ECOTOXICOLOGICAL INFORMATION: NO DATA AVAILABLE.

-----SECTION 13 - DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL METHOD:
WASTE FROM THIS PRODUCT IS NOT HAZARDOUS AS DEFINED UNDER THE RESOURCE
CONSERVATION AND RECOVERY ACT (RCRA) 40 CFR 261.

INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.
DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE/PROVINCIAL, AND LOCAL
REGULATIONS REGARDING POLLUTION.

-----SECTION 14 - TRANSPORT INFORMATION -----

MULTI-MODAL SHIPPING DESCRIPTIONS ARE PROVIDED FOR INFORMATIONAL PURPOSES
AND DO NOT CONSIDER CONTAINER SIZES. THE PRESENCE OF A SHIPPING DESCRIPTION
FOR A PARTICULAR MODE OF TRANSPORT (OCEAN, AIR, ETC.), DOES NOT INDICATE
THAT THE PRODUCT IS PACKAGED SUITABLY FOR THAT MODE OF TRANSPORT. ALL
PACKAGING MUST BE REVIEWED FOR SUITABILITY PRIOR TO SHIPMENT, AND
COMPLIANCE WITH THE APPLICABLE REGULATIONS IS THE SOLE RESPONSIBILITY OF
THE PERSON OFFERING THE PRODUCT FOR TRANSPORT.

US GROUND (DOT): NOT REGULATED FOR TRANSPORTATION.

CANADA (TDG): NOT REGULATED FOR TRANSPORTATION.

IMO: NOT REGULATED FOR TRANSPORTATION.

IATA/ICAO: NOT REGULATED FOR TRANSPORTATION.

-----SECTION 15 - REGULATORY INFORMATION -----

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION:

CAS NO. CHEMICAL/COMPOUND % BY WT % ELEMENT

NO INGREDIENTS IN THIS PRODUCT ARE SUBJECT TO SARA 313 (40 CFR 372.65C)
SUPPLIER NOTIFICATION.

CALIFORNIA PROPOSITION 65:

WARNING:
THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE
CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

TSCA CERTIFICATION:
ALL CHEMICALS IN THIS PRODUCT ARE LISTED, OR ARE EXEMPT FROM LISTING, ON
THE TSCA INVENTORY.

-----SECTION 16 - OTHER INFORMATION -----

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF
THE CANADIAN CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS

ALL OF THE INFORMATION REQUIRED BY THE CPR.

THE ABOVE INFORMATION PERTAINS TO THIS PRODUCT AS CURRENTLY FORMULATED, AND
IS BASED ON THE INFORMATION AVAILABLE AT THIS TIME. ADDITION OF REDUCERS OR
OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND
HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE
MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN
CONNECTION WITH ANY USE OF THIS INFORMATION.

